Page: 1/10

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: November 27, 2018

1 Identification

· Product identifier

· Trade name: Cooling Water Oxidant

· Product code: AR-1062-60

· Recommended use and restriction on use

· Recommended use: Laboratory chemicals

Restrictions on use: No relevant information available.

Details of the supplier of the Safety Data Sheet

· Manufacturer/Supplier:

AguaPhoenix Scientific, Inc.

860 Gitts Run Road Hanover, PA 17331

Phone: (717)632-1291 Toll-Free: (866)632-1291 info@aquaphoenixsci.com

· Distributor:

Aqua Analytics

245 Matheson Blvd East, Units 1 & 2 Mississauga, Ontario Canada L4Z 3C9

(888) 712-4000

· Emergency telephone number:

ChemTel Inc.

(800)255-3924 (North America)

+1 (813)248-0585 (International)

2 Hazard(s) identification

· Classification of the substance or mixture

Met. Corr.1 H290 May be corrosive to metals.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms:





GHS05 GHS07

- · Signal word: Danger
- · Hazard statements:

H290 May be corrosive to metals.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

· Precautionary statements:

(Cont'd. on page 2)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: November 27, 2018

Trade name: Cooling Water Oxidant

(Cont'd. of page 1) P234 Keep only in original container. P261 Avoid breathing spray. P264 Wash thoroughly after handling. P272 Contaminated work clothing must not be allowed out of the workplace. P280 Wear protective gloves/protective clothing/eye protection. P302+P352 If on skin: Wash with plenty of water. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. P310 P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse. Absorb spillage to prevent material damage. P390 Store in corrosive resistant container with a resistant inner liner. P406

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

Other hazards There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Components:	
7664-93-9 Sulfuric acid	5-10%
Met. Corr.1, H290; Skin Corr. 1A, H314; Eye Dam. 1, H318	
16774-21-3 diammonium hexanitratocerate Ox. Sol. 2, H272 Met. Corr.1, H290; Skin Corr. 1C, H314; Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Sens. 1A, H317	1-5%
7732-18-5 Water	>80%

· Additional information:

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret. For the wording of the listed Hazard Statements, refer to section 16.

4 First-aid measures

- Description of first aid measures
- · General information: No special measures required.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Immediately rinse with water.

If skin irritation or rash occurs: Get medical advice/attention.

· After eye contact:

Protect unharmed eye.

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

(Cont'd. on page 3)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: November 27, 2018

Trade name: Cooling Water Oxidant

· Most important symptoms and effects, both acute and delayed:

(Cont'd. of page 2)

Allergic reactions

Irritant to skin and mucous membranes.

Strong irritant with the danger of severe eye injury.

Gastric or intestinal disorders when ingested.

Methaemoglobinaemia

- · Danger: Causes serious eye damage.
- Indication of any immediate medical attention and special treatment needed:

Medical supervision for at least 48 hours.

Treat skin and mucous membrane with antihistamine and corticoid preparations.

If medical advice is needed, have product container or label at hand.

5 Fire-fighting measures

- Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · For safety reasons unsuitable extinguishing agents: No relevant information available.
- Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

For large spills, use respiratory protective device against the effects of fumes/dust/aerosol. Ensure adequate ventilation.

- Environmental precautions Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up

Use neutralising agent: mélange listé ci-dessous.

Water + calcium oxide or calcium carbonate.

Send for recovery or disposal in suitable receptacles.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling
- · Precautions for safe handling:

Prevent formation of aerosols.

Avoid splashes or spray in enclosed areas.

Use only in well ventilated areas.

(Cont'd. on page 4)

Page: 4/10

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: November 27, 2018

Trade name: Cooling Water Oxidant

(Cont'd. of page 3)

- Information about protection against explosions and fires: No special measures required.
- Conditions for safe storage, including any incompatibilities
- Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

Unsuitable material for receptacle: aluminium.

Information about storage in one common storage facility:

Store away from foodstuffs.

Do not store together with reducing agents, heavy-metal compounds, acids and alkalis.

- Further information about storage conditions: Keep containers tightly sealed.
- · Specific end use(s) No relevant information available.

8 Exposure controls/personal protection

- · Control parameters
- · Components with limit values that require monitoring at the workplace:

7664-93-9 Sulfuric acid		
PEL (USA)	Long-term value: 1 mg/m³	
REL (USA)	Long-term value: 1 mg/m³	
TLV (USA)	Long-term value: 0.2* mg/m³ *as thoracic fraction	
EL (Canada)	Long-term value: 0.2 mg/m³ ACGIH A2; IARC 1	
EV (Canada)	Long-term value: 0.2 mg/m³	
LMPE (Mexico)	Long-term value: 0.2* mg/m³ A2;*fracción torácica	

- Exposure controls
- · General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- · Engineering controls: Provide adequate ventilation.
- · Breathing equipment:

Not required under normal conditions of use.

Use suitable respiratory protective device when high concentrations are present.

For large spills, respiratory protection may be advisable.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

Butyl rubber, BR

(Cont'd. on page 5)

Page: 5/10

Safety Data Sheet according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: November 27, 2018

Trade name: Cooling Water Oxidant

(Cont'd. of page 4)

Nitrile rubber, NBR Neoprene gloves Fluorocarbon rubber (Viton)

· Eye protection:



Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear.

- · Body protection: Protective work clothing
- Limitation and supervision of exposure into the environment

No relevant information available.

Information on basic physical and chemical properties		
Appearance: Form:	Liquid	
Color:	Orange	
Odor:	Characteristic	
Odor threshold:	Not determined.	
pH-value at 20 °C (68 °F):	<3	
Melting point/Melting range:	Not determined.	
Boiling point/Boiling range:	100-105 °C (212-221 °F)	
Flash point:	The product is not flammable.	
Flammability (solid, gaseous):	Not applicable.	
Auto-ignition temperature:	Not determined.	
Decomposition temperature:	Not determined.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits		
Lower:	Not determined.	
Upper:	Not determined.	
Oxidizing properties:	Not determined.	
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
Density at 20 °C (68 °F):	>1.05 g/cm³ (>8.76 lbs/gal)	
Relative density:	Not determined.	
Vapor density:	Not determined.	
Evaporation rate:	Not determined.	
Solubility in / Miscibility with		
Water:	Fully miscible.	
Partition coefficient (n-octanol/wat	er): Not determined.	

Page: 6/10

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: November 27, 2018

Trade name: Cooling Water Oxidant

(Cont'd. of page 5)

Dynamic: Not determined. **Kinematic:** Not determined.

• Other information No relevant information available.

10 Stability and reactivity

- · Reactivity: No relevant information available.
- Chemical stability: Stable under normal temperatures and pressures.
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

Possibility of hazardous reactions

Toxic fumes may be released if heated above the decomposition point.

Reacts with alkali (lyes).

Corrosive action on metals.

Reacts with certain metals.

Reacts with reducing agents.

- · Conditions to avoid No relevant information available.
- · Incompatible materials No relevant information available.
- · Hazardous decomposition products

Under fire conditions only:

Toxic metal oxide smoke

Sulfur oxides (SOx)

Nitrogen oxides (NOx)

11 Toxicological information

- Information on toxicological effects
- · Acute toxicity:
- LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral LD50 >5000 mg/kg (rat)

- · Primary irritant effect:
- · On the skin: Irritant to skin and mucous membranes.
- On the eye: Strong irritant with the danger of severe eye injury.
- · Sensitization: Sensitization possible through skin contact.

· IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

· NTP (National Toxicology Program):

7664-93-9 Sulfuric acid

K

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

· Probable route(s) of exposure:

Ingestion.

Inhalation.

(Cont'd. on page 7)

Page: 7/10

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: November 27, 2018

Trade name: Cooling Water Oxidant

(Cont'd. of page 6)

Eye contact.

Skin contact.

· Acute effects (acute toxicity, irritation and corrosivity):

Causes serious eye damage.

Irritating to skin.

- · Repeated dose toxicity: Repeated exposure may result in skin sensitivity.
- · Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- · Carcinogenicity: Based on available data, the classification criteria are not met.
- · Reproductive toxicity: Based on available data, the classification criteria are not met.
- STOT-single exposure: Based on available data, the classification criteria are not met.
- · STOT-repeated exposure: Based on available data, the classification criteria are not met.
- · Aspiration hazard: Based on available data, the classification criteria are not met.

12 Ecological information

- · Toxicity
- · Aquatic toxicity Toxic for aquatic organisms
- · Persistence and degradability No relevant information available.
- · Bioaccumulative potential: No relevant information available.
- · Mobility in soil: No relevant information available.
- · Additional ecological information
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· Other adverse effects No relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

- Uncleaned packagings
- **Recommendation:** Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information		
· UN-Number · DOT, ADR/RID/ADN, IMDG, IATA	UN3264	
· UN proper shipping name · DOT	Corrosive liquid, acidic, inorganic, n.o.s. (Sulfuric acid, diammonium hexanitratocerate)	

(Cont'd. on page 8)

Safety Data Sheet according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: November 27, 2018

Trade name: Cooling Water Oxidant

	(Cont'd. of page 7)
· ADR/RID/ADN	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (SULPHURIC ACID, diammonium hexanitratocerate), ENVIRONMENTALLY HAZARDOUS
· IMDG, IATA	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (SULPHURIC ACID, diammonium hexanitratocerate)
Transport hazard class(es)	
· DOT	
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
Class	8
· Label	8
· ADR/RID/ADN	
· Class · Label	8 (C1) 8
·IMDG	
Class	8
Label	8
·IATA	
· Class · Label	8
· Packing group	0
DOT, ADR/RID/ADN, IMDG, IATA	III
· Environmental hazards · Marine pollutant:	Yes (DOT) Symbol (fish and tree)
 Special precautions for user Danger code (Kemler): EMS Number: Segregation groups 	Warning: Corrosive substances 80 F-A,S-B Acids
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	f Not applicable.

Page: 9/10

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: November 27, 2018

Trade name: Cooling Water Oxidant

(Cont'd. of page 8)

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · United States (USA)
- ·SARA
- Section 302 (extremely hazardous substances):

None of the ingredients are listed.

- Section 355 (extremely hazardous substances):
 - 7664-93-9 Sulfuric acid
- Section 313 (Specific toxic chemical listings):
 - 7664-93-9 Sulfuric acid
 - 16774-21-3 diammonium hexanitratocerate
- · TSCA (Toxic Substances Control Act)
 - 7664-93-9 Sulfuric acid
- 16774-21-3 diammonium hexanitratocerate
- 7732-18-5 Water
- · Proposition 65 (California)
- · Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

EPA (Environmental Protection Agency):

16774-21-3 diammonium hexanitratocerate

|II

· IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

· Canadian Domestic Substances List (DSL):

None of the ingredients are listed.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Cont'd. on page 10)

Page: 10/10

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: November 27, 2018

Trade name: Cooling Water Oxidant

(Cont'd. of page 9)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

OSHA: Occupational Safety & Health Administration

Ox. Sol. 2: Oxidizing solids – Category 2 Met. Corr.1: Corrosive to metals – Category 1

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1A: Skin corrosion/irritation – Category 1A Skin Corr. 1C: Skin corrosion/irritation – Category 1C Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1A: Skin sensitisation – Category 1A

· Sources

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com