according to 29CFR1910/1200 and GHS Rev. 3

Initial preparation date: : 12.27.2014

Butylated Hydroxy Toluene

SECTION 1: Identification of the substance/mixture and of the supplier

Product name: Butylated Hydroxy Toluene

Manufacturer/Supplier Article number: S25212A

Recommended uses of the product and restrictions on use: Laboratory

Manufacturer Details:

AquaPhoenix Scientific 860 Gitts Run Road, Hanover, PA 17331 (717) 632-1291

Supplier Details:

Fisher Science Education 6771 Silver Crest Road, Nazareth, PA 18064 800 955-1177

Emergency telephone number:

Emergency Telephone No.: 800-255-3924

SECTION 2: Hazards identification

Classification of the substance or mixture:



Environmentally Damaging

Acute hazards to the aquatic environment, category 1 Chronic hazards to the aquatic environment, category 1

Acute aquatic toxicity, category 1.
Chronic aquatic toxicity, category 1.
Hazards Not Otherwise Classified - Combustible Dust.

Signal word: Warning

Hazard statements:

Very toxic to aquatic life with long lasting effects.

Very toxic to aquatic life.

Precautionary statements:

Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face protection.

Use personal protective equipment as required.

Collect spillage.

Store in a dry place.

Dispose of contents/container.

Other Non-GHS Classification: None

SECTION 3: Composition/information on ingredients

Ingredients:

Ingredients:

according to 29CFR1910/1200 and GHS Rev. 3

Initial preparation date: : 12.27.2014

Butylated Hydroxy Toluene				
CAS 128-37-0	2,6-Di-tert-butyl-4-methylphenol	99 %		
Percentages are by weight				

SECTION 4: First aid measures

Description of first aid measures

After inhalation:

Move exposed individual to fresh air. Loosen clothing as necessary and position individual in a comfortable position. Seek medical advice if discomfort or irritation persists. If breathing difficult, give oxygen. Do not use mouth to mouth resuscitation if inhaled or ingested. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

After skin contact:

Wash affected area with soap and water. Rinse/flush exposed skin gently using water for 15-20 minutes. Seek medical advice if discomfort or irritation persists. Remove contaminated clothing and shoes.

After eye contact:

Protect unexposed eye. Remove contact lens(es) if able to do so during rinsing. Rinse/flush exposed eye(s) gently using water for 15-20 minutes occasionally lifting the upper and lower eyelids. Seek medical assistance.

After swallowing:

Rinse mouth thoroughly. Do not induce vomiting. Have exposed individual drink sips of water. Seek medical attention immediately. Call poison control center.

Most important symptoms and effects, both acute and delayed:

Irritation. Nausea. Headache. Shortness of breath.

Indication of any immediate medical attention and special treatment needed:

If seeking medical attention, provide SDS document to physician.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing agents:

If in laboratory setting, follow laboratory fire suppression procedures. Use appropriate fire suppression agents for adjacent combustible materials or sources of ignition.

Unsuitable extinguishing agents: None

Special hazards arising from the substance or mixture:

Combustion products may include carbon oxides or other toxic vapors. Thermal decomposition can lead to release of irritating gases and vapors. Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard.

Advice for firefighters:

Protective equipment:

Use NIOSH-approved respiratory protection/breathing apparatus.

Additional information (precautions):

Move product containers away from fire or keep cool with water spray as a protective measure, where feasible. Use spark-proof tools and explosion-proof equipment.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Transfer to a disposal or recovery container. Use spark-proof tools and explosion-

according to 29CFR1910/1200 and GHS Rev. 3

Initial preparation date: : 12.27.2014

Butylated Hydroxy Toluene

proof equipment. Use respiratory protective device against the effects of fumes/dust/aerosol. Ensure adequate ventilation. Keep away from ignition sources. Protect from heat. Stop the spill, if possible. Contain spilled material by diking or using inert absorbent.

Environmental precautions:

Prevent from reaching drains, sewer or waterway. Collect contaminated soil for characterization per Section 13.

Methods and material for containment and cleaning up:

If in a laboratory setting, follow Chemical Hygiene Plan procedures. Place into properly labeled containers for recovery or disposal. If necessary, use trained response staff/contractor. Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Avoid dispersal of dust in the air. Collect solids in powder form using vacuum with HEPA filter.

Reference to other sections: None SECTION 7: Handling and storage

Precautions for safe handling:

Minimize dust generation and accumulation. Wash hands after handling. Avoid dispersal of dust in the air. Avoid ingestion and inhalation. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations. Follow good hygiene procedures when handling chemical materials. Do not eat, drink, smoke, or use personal products when handling chemical substances. If in a laboratory setting, follow Chemical Hygiene Plan. Use only in well ventilated areas. Avoid generation of dust or fine particulate. Avoid contact with skin, eyes and clothing.

Conditions for safe storage, including any incompatibilities:

Provide ventilation for containers. Avoid storage near extreme heat, ignition sources or open flame. Store away from foodstuffs. Store away from oxidizing agents. Store in cool, dry conditions in well sealed containers. Keep container tightly closed. Store with like hazards.

SECTION 8: Exposure controls/personal protection





Control parameters: 128-37-0, Butylated Hydroxytoluene, ACGIH TLV: 2 mg/m3 TWA, NIOSH:

10 mg/m3 TWA.

Appropriate engineering controls: Emergency eye wash fountains and safety showers should be available in

the immediate vicinity of use/handling. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor or dusts (total/respirable) below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above. Use under a fume hood. It is recommended that all dust control equipment such as local exhaust ventilation and material transport systems involved in handling of this product contain explosion relief vents or an explosion suppression system or an oxygen deficient environment. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into

the work area (i.e., there is no leakage from the equipment).

Respiratory protection: Not required under normal conditions of use. Use suitable respiratory

protective device when high concentrations are present. Use suitable respiratory protective device when aerosol or mist is formed. For spills,

respiratory protection may be advisable.

according to 29CFR1910/1200 and GHS Rev. 3

Initial preparation date: : 12.27.2014

Butylated Hydroxy Toluene

Protection of skin: The glove material has to be impermeable and resistant to the product/

the substance/ the preparation being used/handled. Selection of the glove material on consideration of the penetration times, rates of diffusion and

the degradation.

Eye protection: Safety glasses with side shields or goggles.

General hygienic measures: The usual precautionary measures are to be adhered to when handling

chemicals. Keep away from food, beverages and feed sources.

Immediately remove all soiled and contaminated clothing. Wash hands

before breaks and at the end of work. Do not inhale

gases/fumes/dust/mist/vapor/aerosols. Avoid contact with the eyes and

skin.

SECTION 9: Physical and chemical properties

Appearance (physical state, color):	White, semi-transparent solid	Explosion limit lower: Explosion limit upper:	Not determined Not determined
Odor:	Slightly phenolic odor	Vapor pressure at 20°C:	0.02 mbar @ 20 deg C
Odor threshold:	Not determined	Vapor density:	7.6
pH-value:	Not determined	Relative density:	1.048
Melting/Freezing point:	- 71 C	Solubilities:	Insoluble in water; Acetone - soluble; Methanol - soluble.; Toluene -; soluble.
Boiling point/Boiling range:	265 C	Partition coefficient (noctanol/water):	log pow: 5.1
Flash point (closed cup):	127 C	Auto/Self-ignition temperature:	345 C
Evaporation rate:	Not determined	Decomposition temperature:	Not determined
Flammability (solid, gaseous):	Not determined	Viscosity:	a. Kinematic: Not determined b. Dynamic: Not determined
Density at 20°C:	Not determined		

SECTION 10: Stability and reactivity

Reactivity:

Nonreactive under normal conditions.

Chemical stability:

No decomposition if used and stored according to specifications. Light Sensitive.

Possible hazardous reactions:

None under normal processing.

Conditions to avoid:

Store away from oxidizing agents, strong acids or bases. Temperatures above 50 C. dust generation. Light. Incompatible Materials.

Incompatible materials:

Strong acids. Strong bases. Copper. Brass. Oxidizing agents. Acid chlorides. Acid anhydrides. Peroxides. metals.

Hazardous decomposition products:

Carbon oxides (CO, CO2).

according to 29CFR1910/1200 and GHS Rev. 3

Initial preparation date: : 12.27.2014

Butylated Hydroxy Toluene

SECTION 11: Toxicological information

Acute Toxicity:

Dermal:

LC50 Rat male and female >2,000 mg/kg.

Chronic Toxicity: No additional information.

Skin corrosion/irritation: No additional information.

Serious eye damage/irritation:

Rabbit: No eye irritation.

Respiratory or skin sensitization: No additional information.

Carcinogenicity: No additional information.

Germ cell mutagenicity:

Ames test S. typhimurium Result: negative mouse - male and female Result: negative

Reproductive Toxicity: No additional information.

STOT-single and repeated exposure: No additional information.

Additional toxicological information:

No additional information.

SECTION 12: Ecological information

Ecotoxicity:

Fish., LC50 - Oryzias latipes - 5.3 mg/l - 48 h.

Invertebrates, static test EC50 - Daphnia magna (Water flea) - 0.48 mg/l - 48 h.

Bacteria, Growth inhibition EC50 - Protozoa - 1.7 mg/l - 24 h.

Persistence and degradability:

Readily degradable in the environment.

Bioaccumulative potential: No additional information.

Mobility in soil: No additional information.

Other adverse effects: No additional information.

SECTION 13: Disposal considerations

Waste disposal recommendations:

Product/containers must not be disposed together with household garbage. It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities (US 40CFR262.11). Consult federal state/ provincial and local regulations regarding the proper disposal of waste material that may incorporate some amount of this product. Dilute with water and flush to sewer.

SECTION 14: Transport information

US DOT

UN Number:

ADR, ADN, DOT, IMDG, IATA

3077

according to 29CFR1910/1200 and GHS Rev. 3

Initial preparation date: : 12.27.2014

Butylated Hydroxy Toluene

Limited Quantity Exception:

RQ (if applicable): None

Proper shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (2,6-di-

tert-Butyl-p-cresol). **Hazard Class:** 9 **Packing Group:** III.

Marine Pollutant (if applicable): No

additional information. **Comments:** None

None

Non Bulk:

RQ (if applicable): None

Proper shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (2,6-di-

tert-Butyl-p-cresol). **Hazard Class:** 9 **Packing Group:** III.

Marine Pollutant (if applicable): No

additional information. **Comments:** None





SECTION 15: Regulatory information

United States (USA)

Bulk:

SARA Section 311/312 (Specific toxic chemical listings):

None of the ingredients are listed.

SARA Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

RCRA (hazardous waste code):

None of the ingredients are listed.

TSCA (Toxic Substances Control Act):

All ingredients are listed.

CERCLA (Comprehensive Environmental Response, Compensation, and Liability Act):

None of the ingredients are listed.

Proposition 65 (California):

Chemicals known to cause cancer:

None of the ingredients are listed.

Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

Canada

Canadian Domestic Substances List (DSL):

All ingredients are listed.

SECTION 16: Other information

according to 29CFR1910/1200 and GHS Rev. 3

Initial preparation date: : 12.27.2014

Butylated Hydroxy Toluene

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations. Note. The responsibility to provide a safe workplace remains with the user. The user should consider the health hazards and safety information contained herein as a guide and should take those precautions required in an individual operation to instruct employees and develop work practice procedures for a safe work environment. The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by the use of this material. It is the responsibility of the user to comply with all applicable laws and regulations applicable to this material.

NFPA: 2-0-0 **HMIS**: 0-0-0

GHS Full Text Phrases: None

Abbreviations and Acronyms:

IMDG International Maritime Code for Dangerous Goods.

PNEC. Predicted No-Effect Concentration (REACH).

CFR Code of Federal Regulations (USA)

SARA Superfund Amendments and Reauthorization Act (USA).

RCRA. Resource Conservation and Recovery Act (USA).

TSCA. Toxic Substances Control Act (USA).

NPRI National Pollutant Release Inventory (Canada).

DOT US Department of Transportation.

IATA International Air Transport Association.

GHS Globally Harmonized System of Classification and Labelling of Chemicals.

ACGIH American Conference of Governmental Industrial Hygienists

CAS Chemical Abstracts Service (division of the American Chemical Society).

NFPA National Fire Protection Association (USA).

HMIS Hazardous Materials Identification System (USA).

WHMIS Workplace Hazardous Materials Information System (Canada).

DNEL Derived No-Effect Level (REACH).