

World Headquarters
Hach Company
P.O.Box 389
Loveland, CO USA 80539
(970) 669-3050

MSDS No: M00297

MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: Molybdovanadate Reagent
Catalog Number: 2076032

Hach Company
P.O.Box 389
Loveland, CO USA 80539
(970) 669-3050

Emergency Telephone Numbers:
(Medical and Transportation)
(303) 623-5716 24 Hour Service
(515)232-2533 8am - 4pm CST

MSDS Number: M00297
Chemical Name: Not applicable
CAS No.: Not applicable
Chemical Formula: Not applicable
Chemical Family: Not applicable
Hazard: Harmful if inhaled. Carcinogen. Causes eye burns.
Date of MSDS Preparation:
Day: 23
Month: 09
Year: 2004

2. COMPOSITION / INFORMATION ON INGREDIENTS

Ammonium Molybdate

CAS No.: 12054-85-2
TSCA CAS Number: 1202767 7
Percent Range: 1.0 - 5.0
Percent Range Units: weight / volume
LD50: None reported.
LC50: None reported.
TLV: 5 mg/m³ as Mo
PEL: 5 mg/m³ as Mo
Hazard: Toxic. May cause irritation.

Ammonium Metavanadate

CAS No.: 7803556
TSCA CAS Number: 7803-55-6
Percent Range: < 1.0
Percent Range Units: weight / volume
LD50: Oral rat LD50 = 160 mg/kg; Oral rat LD50 = 58,100 µg/kg
LC50: Inhalation rat LC50 = 7800 µg/m³/4H
TLV: 0.05 mg/m³ as V₂O₅
PEL: Ceiling 0.05 mg/m³ as V₂O₅
Hazard: Toxic. May cause irritation.

Demineralized Water

CAS No.: 7732185
TSCA CAS Number: 7732-18-5
Percent Range: 50.0 - 60.0
Percent Range Units: volume / volume
LD50: None reported
LC50: None reported
TLV: Not established
PEL: Not established

Hazard: No effects anticipated.

Other component

CAS No.: Not applicable

TSCA CAS Number: Not applicable

Percent Range: < 1.0

Percent Range Units: weight / volume

LD50: Not applicable

LC50: Not applicable

TLV: Not established

PEL: Not established

Hazard: Any ingredient(s) of this product listed as "Other component(s)" is not considered a health hazard to the user of this product.

Sulfuric Acid

CAS No.: 7664-93-9

TSCA CAS Number: 7664-93-9

Percent Range: 35.0 - 45.0

Percent Range Units: weight / volume

LD50: Oral rat LD50 = 2140 mg/kg.

LC50: Inhalation rat LC50 = 87 ppm/4 hr

TLV: 1 mg/m³ (TWA); 3 mg/m³ (STEL)

PEL: 1 mg/m³

Hazard: Causes severe burns. Harmful if inhaled. Recognized carcinogen.

3. HAZARDS IDENTIFICATION

Emergency Overview:

Appearance: Clear, yellow liquid

Odor: None

CAUSES EYE BURNS HARMFUL IF INHALED CAUSES SKIN IRRITATION

HMIS:

Health: 3

Flammability: 0

Reactivity: 2

Protective Equipment: X - See protective equipment, Section 8.

NFPA:

Health: 3

Flammability: 0

Reactivity: 2

Symbol: Water Reactive

Potential Health Effects:

Eye Contact: Causes severe burns

Skin Contact: Causes irritation

Skin Absorption: None reported

Target Organs: None reported

Ingestion: Causes: severe burns May cause: loss of coordination copper deficiency gout May effect enzyme activity. Molybdenum compounds may cause loss of coordination, enzyme activity effects, copper deficiency and gout.

Target Organs: None reported

Inhalation: Causes: severe burns May cause: difficult breathing mouth soreness teeth erosion

Target Organs: Lungs

Medical Conditions Aggravated: Pre-existing: Eye conditions Bin conditions Respiratory conditions Gout

Chronic Effects: Molybdenum poisoning signs include loss of appetite, listlessness and reduced growth rate. Excessive exposure to molybdenum compounds may cause gout and anemia. Chronic overexposure may cause erosion of the teeth enzyme activity effects copper deficiency chronic irritation or inflammation of the lungs cancer

Cancer / Reproductive Toxicity Information:

This product does NOT contain any OSHA listed carcinogens.

An ingredient of this mixture is: IARC Group 1: Recognized Carcinogen
Sulfuric Acid - The IARC evaluation was based on exposure to the mist or vapor of concentrated sulfuric acid generated during chemical processes.

This product does NOT contain any NTP listed chemicals.

Additional Cancer / Reproductive Toxicity Information: Contains: an experimental teratogen. an experimental mutagen.

Toxicologically Synergistic Products: None reported

4. FIRST AID

Eye Contact: Immediately flush eyes with water for 15 minutes. Call physician.

Skin Contact (First Aid): Wash skin with plenty of water for 15 minutes. Remove contaminated clothing. Call physician immediately.

Ingestion (First Aid): Do not induce vomiting. Give 1-2 glasses of water. Call physician immediately. Never give anything by mouth to an unconscious person.

Inhalation: Remove to fresh air. Give artificial respiration if necessary. Call physician.

5. FIRE FIGHTING MEASURES

Flammable Properties: During a fire, corrosive and toxic gases may be generated by thermal decomposition. Not flammable, but reacts with most metals to form flammable hydrogen gas.

Flash Point: Not applicable

Method: Not applicable

Flammability Limits:

Lower Explosion Limits: Not applicable

Upper Explosion Limits: Not applicable

Autoignition Temperature: Not applicable

Hazardous Combustion Products: Toxic fumes of: ammonia nitrogen oxides. sulfur oxides.

Fire / Explosion Hazards: May react violently with: reducers

Static Discharge: None reported.

Mechanical Impact: None reported

Extinguishing Media: Dry chemical. Do NOT use water.

Fire Fighting Instruction: As in any fire, wear self-contained breathing apparatus pressure-demand and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Spill Response Notice:

Only persons properly qualified to respond to an emergency involving hazardous substances may respond to a spill according to federal regulations (OSHA 29 CFR 1910.120(a)(v)) and per your company's emergency response plan and guidelines/procedures. See Section 13, Special Instructions for disposal assistance.

Containment Technique: Absorb spilled liquid with non-reactive sorbent material. Stop spilled material from being released to the environment.

Clean-up Technique: Cover spilled material with an alkali, such as soda ash or sodium bicarbonate. Scoop up slurry into a large beaker. Dilute with a large excess of water. Adjust to a pH between 6 and 9 with an alkali, such as soda ash or sodium bicarbonate. Flush reacted material to the drain with a large excess of water. Decontaminate the area of the spill with a soap solution.

Evacuation Procedure: Evacuate local area (15 foot radius or as directed by your facility's emergency response plan) when: any quantity is spilled. If conditions warrant, increase the size of the evacuation.

Special Instructions (for accidental release): Mixture contains a component which is regulated as a water pollutant. Product is regulated as RCRA hazardous waste.

304 EHS RQ (40 CFR 355): Sulfuric Acid - RQ 1000 lbs.

D.O.T. Emergency Response Guide Number: 154

7. HANDLING / STORAGE

Handling: Avoid contact with eyes skin clothing Do not breathe mist or vapors. Wash thoroughly after handling. Use with adequate ventilation. Maintain general industrial hygiene practices when using this product.

Storage: Store between 10° and 25°C. Protect from: light Store away from: oxidizers reducers metals

Flammability Class: Not applicable

8. EXPOSURE CONTROLS / PROTECTIVE EQUIPMENT

Engineering Controls: Have an eyewash station nearby. Have a safety shower nearby. Use general ventilation to minimize exposure to mist, vapor or dust. Maintain general industrial hygiene practices when using this product.

Personal Protective Equipment:

Eye Protection: chemical splash goggles

Skin Protection: disposable latex gloves lab coat

Inhalation Protection: adequate ventilation

Precautionary Measures: Avoid contact with: eyes skin clothing Do not breathe: mist/vapor Wash thoroughly after handling. Use with adequate ventilation. Protect from: light

TLV: Not established

PEL: Not established

9. PHYSICAL / CHEMICAL PROPERTIES

Appearance: Clear, yellow liquid

Physical State: Liquid

Molecular Weight: Not applicable

Odor: None

pH: < 0.5

Vapor Pressure: Not determined

Vapor Density (air = 1): Not determined

Boiling Point: 100°C (212°F)

Melting Point: Not determined

Specific Gravity (water = 1): 1.375

Evaporation Rate (water = 1): 0.06

Volatile Organic Compounds Content: Not applicable

Partition Coefficient (n-octanol / water): Not applicable

Solubility:

Water: Soluble

Acid: Soluble

Other: Not determined

Metal Corrosivity:

Steel: 11.273 in/yr

Aluminum: Not determined

10. STABILITY / REACTIVITY

Chemical Stability: Stable when stored under proper conditions.

Conditions to Avoid: Extreme temperatures Heating to decomposition.

Reactivity / Incompatibility: May react violently in contact with: oxidizers reducers Incompatible with: metals

Hazardous Decomposition: Heating to decomposition releases toxic and/or corrosive fumes of: ammonia nitrogen oxides sulfur oxides Contact with metals may release flammable hydrogen gas.

Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

Product Toxicological Data:

LD50: None reported

LC50: None reported

Dermal Toxicity Data: None reported

Skin and Eye Irritation Data: This product is not corrosive to skin. Slight to well defined erythema. Absent to slight edema. (OECD Number 404, Acute Dermal Irritation/Corrosion)

Mutation Data: Ammonium Metavanadate: DNA damage - Human lymphocytes and ovary - 200 µmol/L; Mutation in somatic cells - hamster - lung - 5 µmol/L

Reproductive Effects Data: Intraperitoneal hamster TDLo = 2820 µg/kg - Musculoskeletal abnormalities; Intraperitoneal hamster TDLo = 11280 µg/kg - Post-implantation mortality

Ingredient Toxicological Data: Sulfuric Acid: Oral rat LD50 = 2140 mg/kg, Inhalation rat LC50 = 347 ppm/1 hr;
Ammonium Metavanadate: Oral rat LD50 = 58 mg/kg, Ammonium Molybdate (anhydrous): Oral rat LD50 = 333 mg/kg

12. ECOLOGICAL INFORMATION

Product Ecological Information: --

No ecological data available for this product.

Ingredient Ecological Information: Sulfuric Acid: The 48-Hour TLm in flounder is 100-300 ppm.

13. DISPOSAL CONSIDERATIONS

EPA Waste ID Number: D002

Special Instructions (Disposal): Work in an approved fume hood. Dilute to 3 to 5 times the volume with cold water. Adjust to a pH between 6 and 9 with an alkali, such as soda ash or sodium bicarbonate. Open cold water tap completely, slowly pour the reacted material to the drain. Allow cold water to run for 5 minutes to completely flush the system.

Empty Containers: Rinse three times with an appropriate solvent. Dispose of empty container as normal trash.

NOTICE (Disposal): These disposal guidelines are based on federal regulations and may be superseded by more stringent state or local requirements. Please consult your local environmental regulators for more information.

14. TRANSPORT INFORMATION

D.O.T.:

D.O.T. Proper Shipping Name: Corrosive Liquid, Acidic, Inorganic, N.O.S.

(<45% Sulfuric Acid in Solution)

DOT Hazard Class: 8

DOT Subsidiary Risk: NA

DOT ID Number: UN3264

DOT Packing Group: III

I.C.A.O.:

I.C.A.O. Proper Shipping Name: Corrosive Liquid, Acidic, Inorganic, N.O.S.

(<45% Sulfuric Acid in Solution)

ICAO Hazard Class: 8

ICAO Subsidiary Risk: NA

ICAO ID Number: UN3264

ICAO Packing Group: III

I.M.O.:

I.M.O. Proper Shipping Name: Corrosive Liquid, Acidic, Inorganic, N.O.S.

(<45% Sulfuric Acid in Solution)

I.M.O. Hazard Class: 8

I.M.O. Subsidiary Risk: NA

I.M.O. ID Number: UN3264

I.M.O. Packing Group: III

Additional Information: This product may be shipped as part of a chemical kit composed of various compatible dangerous goods for analytical or testing purposes. This kit would have the following classification: Proper Shipping Name: Chemical Kit Hazard Class: 9 UN Number 3316

15. REGULATORY INFORMATION

U.S. Federal Regulations:

O.S.H.A.: This product meets the criteria for a hazardous substance as defined in the Hazard Communication Standard. (29 CFR 1910.1200)

E.P.A.:

S.A.R.A. Title III Section 311/312 Categorization (40 CFR 370): Immediate (Acute) Health Hazard Reactive Delayed (Chronic) Health Hazard

S.A.R.A. Title III Section 313 (40 CFR 372): This product contains a chemical(s) subject to the reporting requirements of Section 313 of Title III of SARA.

Sulfuric Acid and Ammonium Molybdate

302 (EHS) TPQ (40 CFR 355): Sulfuric Acid 1000 lbs.

304 CERCLA RQ (40 CFR 302.4): Sulfuric Acid Ammonium vanadate 1000 lbs.

304 EHS RQ (40 CFR 355): Sulfuric Acid - RQ 1000 lbs.

Clean Water Act (40 CFR 116.4): Sulfuric acid - RQ 1000 lbs.

RCRA: Contains RCRA regulated substances. See Section 13, EPA Waste ID Number.

C.P.S.C.: The label for this product bears the signal word "POISON" because the concentration of Sulfuric Acid in the product is greater than/equal to 10%.

State Regulations:

California Prop. 65: No Prop. 65 listed chemicals are present in this product.

Identification of Prop. 65 Ingredient(s): Not applicable

Trade Secret Registry: Not applicable

National Inventories:

U.S. Inventory Status: All ingredients in this product are listed on the TSCA 8(b) Inventory (40 CFR 710).

TSCA CAS Number: Not applicable

16. OTHER INFORMATION

Intended Use: Indicator for phosphate

References: 29 CFR 1900 - 1910 (Code of Federal Regulations - Labor). Air Contaminants, Federal Register, Vol. 54, No. 12. Thursday, January 19, 1989. pp. 2332-2983. Fire Protection Guide on Hazardous Materials, 10th Ed. Quincy, MA: National Fire Protection Fire Protection Guide on Hazardous Materials, 10th Ed. Quincy, MA: National Fire Protection Association, 1991. In-house information. Technical Judgment. TLV's Threshold Limit Values and Biological Exposure Indices for 1992-1993. American Conference of Governmental Industrial Hygienists, 1992. IARC Monographs on the Evaluation of the Carcinogenic Risks to Humans. World Health Organization (Volumes 1-42) Supplement 7. France: 1987.

Revision Summary: Updates in Section(s) 14,

Legend:

NA - Not Applicable	w/w - weight/weight
ND - Not Determined	w/v - weight/volume
NV - Not Available	v/v - volume/volume

USER RESPONSIBILITY: Each user should read and understand this information and incorporate it in individual site safety programs in accordance with applicable hazard communication standards and regulations.

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED TO BE ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF.

HACH COMPANY ©2004