

World Headquarters
Hach Company
P.O.Box 389
Loveland, CO USA 80539
(970) 669-3050

MSDS No: M00187

SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: Molybdate 3 Reagent for Silica

Catalog Number: 2367077

Hach Company
P.O.Box 389
Loveland, CO USA 80539
(970) 669-3050

Emergency Telephone Numbers:
(Medical and Transportation)
(303) 623-5716 24 Hour Service
(515)232-2533 8am - 4pm CST

MSDS Number: M00187

Chemical Name: Not applicable

CAS Number: Not applicable

Additional CAS No. (for hydrated forms): Not applicable

Chemical Formula: Not applicable

Chemical Family: Mixture

Intended Use: Laboratory Reagent Silica determination

2. HAZARDS IDENTIFICATION

GHS Classification:

Hazard categories: Corrosive to Metals: Met. Corr. 1 Skin Corrosion/Irritation: Skin Corr. 1A Specific Target Organ Toxicity - Repeated Exposure: STOT RE. 2

GHS Label Elements:

DANGER



Hazard statements: May be corrosive to metals. Causes severe skin burns and eye damage. May cause damage to organs through prolonged or repeated exposure.

Precautionary statements: Do not breathe dust/fume/gas/mist/vapours/spray. Wear eye protection. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

HMIS:

Health: 3

Flammability: 0

Reactivity: 1

Protective Equipment: X - See protective equipment, Section 8.

NFPA:

Health: 3

Flammability: 0

Reactivity: 1

Symbol: Not applicable

WHMIS Hazard Classification: Class D, Division 1, Subdivision A - Very toxic materials (immediate effects) Class E - Corrosive material

WHMIS Symbols: Corrosive Acute Poison

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Components according to GHS:

Sodium Bisulfate

CAS Number: 7681-38-1
Chemical Formula: NaHSO₄
GHS Classification: Acute Tox. 5-Orl, H303; Eye Dam. 1, H318
Percent Range: 10.0 - 20.0
Percent Range Units: weight / volume
PEL: 15 mg/m³ as total dust; 5 mg/m³ as respirable dust
TLV: 10 mg/m³ as inhalable dust; 3 mg/m³ as respirable dust

WHMIS Symbols: Corrosive

Molybdic Acid

CAS Number: 7782-91-4
Chemical Formula: H₂MoO₄
GHS Classification: Acute Tox. 5-Orl, H303; Acute Tox. 5-Derm, H313; Eye Irrit. 2A, H319; STOT Single 3, H335; STOT Rep. 1, H372
Percent Range: 5.0 - 15.0
Percent Range Units: weight / weight
PEL: 5 mg/m³ as Mo
TLV: 10 mg/m³ as Mo

WHMIS Symbols: Acute PoisonOther Toxic Effects

Sulfuric Acid

CAS Number: 7664-93-9
Chemical Formula: H₂SO₄
GHS Classification: Met. Corr. 1 H290; Skin Corr. 1A, H314; Aquatic Acute 3, H402
Percent Range: 5.0 - 15.0
Percent Range Units: volume / volume
PEL: 1 mg/m³
TLV: 1 mg/m³

WHMIS Symbols: Acute PoisonCorrosive

Hazardous Components according to GHS: No

Demineralized Water

CAS Number: 7732-18-5
Chemical Formula: H₂O
GHS Classification: Not a dangerous substance according to GHS.
Percent Range: 60.0 - 70.0
Percent Range Units: volume / volume
PEL: Not established
TLV: Not established

WHMIS Symbols: Not applicable

4. FIRST AID MEASURES

General Information: In the event of exposure, show this Material Safety Data Sheet and label (where possible) to a doctor.

Advice to doctor: Treat symptomatically.

Eye Contact: Immediately flush eyes with water for 15 minutes. Call physician.

Skin Contact (First Aid): Remove contaminated clothing. If exposed to paper within, wash with soap and plenty of water for 15 minutes. Call physician if irritation develops.

Inhalation: Remove to fresh air. Give artificial respiration if necessary. Call physician.

Ingestion (First Aid): Do not induce vomiting. Give 1-2 glasses of water. Never give anything by mouth to an unconscious person. Call physician immediately.

5. FIRE FIGHTING MEASURES

Flammable Properties: During a fire, corrosive and toxic gases may be generated by thermal decomposition.

Fire Fighting Instruction: As in any fire, wear self-contained breathing apparatus pressure-demand and full protective gear. Evacuate area and fight fire from a safe distance.

Extinguishing Media: Water. Dry chemical. Carbon dioxide

Extinguishing Media NOT To Be Used: Not applicable

Fire / Explosion Hazards: None reported

Hazardous Combustion Products: None reported

6. ACCIDENTAL RELEASE MEASURES

Spill Response Notice:

Only persons properly qualified to respond to an emergency involving hazardous substances may respond to a spill according to federal regulations (OSHA 29 CFR 1910.120(a)(v)) and per your company's emergency response plan and guidelines/procedures. See Section 13, Special Instructions for disposal assistance. Outside of the US, only persons properly qualified according to state or local regulations should respond to a spill involving chemicals.

Containment Technique: Absorb spilled liquid with non-reactive sorbent material. Stop spilled material from being released to the environment. Dike large spills to keep spilled material from entering sewage and drainage systems or bodies of water.

Clean-up Technique: If permitted by regulation, Cover spilled material with an alkali, such as soda ash or sodium bicarbonate. Scoop up slurry into a large beaker. Dilute with a large excess of water. Adjust to a pH between 6 and 9 with an alkali, such as soda ash or sodium bicarbonate. Flush reacted material to the drain with a large excess of water. Decontaminate the area of the spill with a soap solution. Otherwise, Pick up spill for disposal and place in a closed container. Dispose of in accordance with local, state and federal regulations or laws.

Evacuation Procedure: Evacuate local area (15 foot radius or as directed by your facility's emergency response plan) when any quantity is spilled. If conditions warrant, increase the size of the evacuation.

DOT Emergency Response Guide Number: 154

7. HANDLING AND STORAGE

Handling: Avoid contact with eyes skin clothing Do not breathe mist or vapors. Wash thoroughly after handling. Use with adequate ventilation. Maintain general industrial hygiene practices when using this product.

Storage: Store between 10° and 25°C. Keep away from: oxidizers reducers alkalies

Flammability Class: Not applicable

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Use general ventilation to minimize exposure to mist, vapor or dust. Maintain general industrial hygiene practices when using this product.

Personal Protective Equipment:

Eye Protection: chemical splash goggles

Skin Protection: lab coat neoprene latex gloves In the EU, the selected gloves must satisfy the specifications of EU Directive 89/686/EEC and standard EN 374 derived from it.

Inhalation Protection: adequate ventilation

Precautionary Measures: Avoid contact with: eyes skin clothing Do not breathe: mist/vapor Wash thoroughly after handling. Use with adequate ventilation. Keep away from: oxidizers reducers alkalies

TLV: Not established

PEL: Not established

For Occupational Exposure Limits (OEL) for ingredients, see section 3 - Composition/Information on Ingredients.:

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear, colorless to light yellow liquid

Physical State: Liquid

Molecular Weight: Not applicable

Odor: Not determined

Odor Threshold: Not determined

pH: < 0.5

Metal Corrosivity:

Corrosivity Classification: Classified as corrosive to metals.
Steel: 5.97 in/yr (151.6 mm/yr)
Aluminum: Not determined
Specific Gravity/ Relative Density (water = 1; air =1): 1.2 - 1.3
Viscosity: Not determined
Solubility:
Water: Soluble
Acid: Soluble
Other: Not determined
Partition Coefficient (n-octanol / water): Not determined
Coefficient of Water / Oil: Not determined
Melting Point: Not applicable
Decomposition Temperature: Not determined
Boiling Point: ~ 100 °C
Vapor Pressure: Not determined
Vapor Density (air = 1): Not determined
Evaporation Rate (water = 1): Not determined
Volatile Organic Compounds Content: Not applicable
Flammable Properties: During a fire, corrosive and toxic gases may be generated by thermal decomposition.
Flash Point: > 212 °F; > 100 °C
Method: Closed cup
Flammability Limits:
Lower Explosion Limits: Not applicable
Upper Explosion Limits: Not applicable
Autoignition Temperature: Not applicable
Explosive Properties:
Not classified according to GHS criteria.
Oxidizing Properties:
Not classified according to GHS criteria.
Reactivity Properties:
Not classified as self-reactive, pyrophoric, self-heating or emitting flammable gases in contact with water according to GHS criteria.
Gas under Pressure:
Not classified according to GHS criteria.

10. STABILITY AND REACTIVITY

Chemical Stability: Stable when stored under proper conditions.
Mechanical Impact: None reported
Static Discharge: None reported.
Reactivity / Incompatibility: Incompatible with: reducers oxidizers strong bases
Hazardous Decomposition: Heating to decomposition releases toxic and/or corrosive fumes of: sulfur oxides
Conditions to Avoid: Extreme temperatures Heating to decomposition.

11. TOXICOLOGICAL INFORMATION

Toxicokinetics, Metabolism and Distribution: No information available for mixture.
Toxicologically Synergistic Products: None reported
Acute Toxicity: Acute Toxicity Estimate (ATE) - Calculated from Ingredient Toxicity Data Route Data Given Below
ATE Oral Rat LD50 = 7099 mg/kg
Specific Target Organ Toxicity - Single Exposure (STOT-SE): Based on classification principles, the classification criteria are not met.
Specific Target Organ Toxicity - Repeat Exposure (STOT-RE): Target Organs Respiratory Tract Liver
Skin Corrosion/Irritation: Corrosive to skin.
Based on classification principles and extreme pH.
Eye Damage: Corrosive to eyes.
Sensitization: Based on classification principles, the classification criteria are not met.
CMR Effects/Properties (carcinogenic, mutagenic or toxic to reproduction): Potential carcinogen
Contains Molybdc Acid. Limited animal data showing casual relationship between molybdenum trioxide and lung carcinogenicity. The trioxide becomes molybdc acid in aqueous solution.
The substance is not mutagenic.

An ingredient of this mixture is: IARC Group 1: Recognized Carcinogen
Sulfuric Acid - The IARC evaluation was based on exposure to the mist or vapor of concentrated sulfuric acid generated during chemical processes.

An ingredient of this mixture is: NTP Listed Group 1: Recognized Carcinogen
Sulfuric Acid Mist or Vapor

This product does NOT contain any OSHA listed carcinogens.

Symptoms/Effects:

Ingestion: May cause: burns of the mouth and esophagus nausea vomiting diarrhea circulatory disturbances rapid pulse and respirations loss of appetite anemia liver damage Molybdenum compounds may cause loss of coordination, enzyme activity effects, copper deficiency and gout.

Inhalation: May cause: irritation of nose and throat difficult breathing teeth erosion mouth soreness anemia liver damage

Skin Absorption: None Reported

Chronic Effects: Molybdenum poisoning signs include loss of appetite, listlessness and reduced growth rate. Excessive exposure to molybdenum compounds may cause gout and anemia. Chronic overexposure may cause enzyme activity effects copper deficiency erosion of the teeth chronic irritation or inflammation of the lungs cancer

Medical Conditions Aggravated: Pre-existing: Eye conditions Skin conditions Respiratory conditions Liver conditions Gout

12. ECOLOGICAL INFORMATION

Product Ecological Information: --

No ecological data available for this product. Mobility in soil: No data available Based on classification principles, not classified as hazardous to the environment.

CEPA Categorization: Persistent Not Bioaccumulative Not inherently toxic to aquatic organisms

Ingredient Ecological Information: Sulfuric Acid: The 48-Hour TLm in flounder is 100-300 ppm.

13. DISPOSAL CONSIDERATIONS

EPA Waste ID Number: D002

Special Instructions (Disposal): Dilute to 3 to 5 times the volume with cold water. Adjust to a pH between 6 and 9 with an alkali, such as soda ash or sodium bicarbonate. Open cold water tap completely, slowly pour the reacted material to the drain. Allow cold water to run for 5 minutes to completely flush the system.

Empty Containers: Rinse three times with an appropriate solvent. Dispose of empty container as normal trash. Rinsate from empty containers may contain sufficient product to require disposal as hazardous waste.

NOTICE (Disposal): These disposal guidelines are based on federal regulations and may be superseded by more stringent state or local requirements. Please consult your local environmental regulators for more information. In Europe: Chemical and analysis solutions must be disposed of in compliance with the respective national regulations. Product packaging must be disposed of in compliance with the country-specific regulations or must be passed to a packaging return system.

14. TRANSPORT INFORMATION

D.O.T.:

D.O.T. Proper Shipping Name: Corrosive Liquid, Acidic, Inorganic, N.O.S.
(Sulphuric Acid/Sodium Bisulphate Solution)

Hazard Class: 8

Subsidiary Risk: NA

ID Number: UN3264

Packing Group: III

T.D.G.:

Proper Shipping Name: Corrosive Liquid, Acidic, Inorganic, N.O.S.
(Sulphuric Acid/Sodium Bisulphate Solution)

Hazard Class: 8

Subsidiary Risk: NA

UN Number/PIN: 3264

Packing Group: III

I.C.A.O.:

I.C.A.O. Proper Shipping Name: Corrosive Liquid, Acidic, Inorganic, N.O.S.
(Sulphuric Acid/Sodium Bisulphate Solution)

Hazard Class: 8

Subsidiary Risk: NA

ID Number: UN3264

Packing Group: III

I.M.O.:

Proper Shipping Name: Corrosive Liquid, Acidic, Inorganic, N.O.S.
(Sulphuric Acid/Sodium Bisulphate Solution)

Hazard Class: 8

Subsidiary Risk: NA

ID Number: UN3264

Packing Group: III

Additional Information: There is a possibility that this product could be contained in a reagent set or kit composed of various compatible dangerous goods. If the item is NOT in a set or kit, the classification given above applies. If the item IS part of a set or kit, the classification would change to the following: UN3316 Chemical Kit, Class 9, PG II or III. If the item is not regulated, the Chemical Kit classification does not apply.

15. REGULATORY INFORMATION

U.S. Federal Regulations:

O.S.H.A.: This product meets the criteria for a hazardous substance as defined in the Hazard Communication Standard. (29 CFR 1910.1200)

E.P.A.:

S.A.R.A. Title III Section 311/312 Categorization (40 CFR 370): Immediate (Acute) Health Hazard Delayed (Chronic) Health Hazard Reactive

S.A.R.A. Title III Section 313 (40 CFR 372): This product does NOT contain any chemical subject to the reporting requirements of Section 313 of Title III of SARA.

--

302 (EHS) TPQ (40 CFR 355): Sulfuric Acid 1000 lbs.

304 CERCLA RQ (40 CFR 302.4): Sulfuric Acid 1000 lbs.

304 EHS RQ (40 CFR 355): Sulfuric Acid - RQ 1000 lbs.

Clean Water Act (40 CFR 116.4): Sulfuric acid - RQ 1000 lbs.

RCRA: Contains RCRA regulated substances. See Section 13, EPA Waste ID Number.

State Regulations:

California Prop. 65: No Prop. 65 listed chemicals are present in this product.

Identification of Prop. 65 Ingredient(s): None

California Perchlorate Rule CCR Title 22 Chap 33: Not applicable

Trade Secret Registry: Not applicable

National Inventories:

U.S. Inventory Status: All ingredients in this product are listed on the TSCA 8(b) Inventory (40 CFR 710).

CAS Number: Not applicable

Canadian Inventory Status: All ingredients of this product are DSL Listed.

EEC Inventory Status: All ingredients used to make this product are listed on EINECS / ELINCS.

Australian Inventory (AICS) Status: All ingredients are listed.

New Zealand Inventory (NZIoC) Status: All components either listed or exempt.

Korean Inventory (KECI) Status: All components of this product are either listed, listed as the anhydrous compound or exempt.

Japan (ENCS) Inventory Status: All components either listed or exempt.

China (PRC) Inventory (MEP) Status: All components either listed or exempt.

16. OTHER INFORMATION

References: CCINFO MSDS/FTSS. Canadian Centre for Occupational Health and Safety. Hamilton, Ontario Canada: 30 June 1993. The Merck Index, 11th Ed. Rahway, New Jersey: Merck and Co., Inc., 1989. Sax, N. Irving. Dangerous Properties of Industrial Materials, 7th Ed. New York: Van Nostrand Reinhold Co., 1989. In-house information. Technical Judgment. Air Contaminants, Federal Register, Vol. 54, No. 12. Thursday, January 19, 1989. pp. 2332-2983. TLV's Threshold Limit Values and Biological Exposure Indices for 1992-1993. American Conference of Governmental Industrial Hygienists, 1992. IARC Monographs on the Evaluation of the Carcinogenic Risks to Humans. World Health Organization (Volumes 1-42) Supplement 7. France: 1987.

Complete Text of H phrases referred to in Section 3: H290 May be corrosive to metals. H314 Causes severe skin burns and eye damage. . H318 Causes serious eye damage. . H319 Causes serious eye irritation. H335 May cause respiratory irritation. .

Revision Summary: Substantial revision to comply with EU Reg 1272/2008, Reg 1907/2006 and UN GHS (ST/SG/AC.10/36/Add.3).

Date of MSDS Preparation:

Day: 03

Month: June

Year: 2014

MSDS Prepared: MSDS prepared by Product Compliance Department extension 3350

CCOHS Evaluation Note: It is offered under exemption from WHMIS labeling as specified in the Controlled Products Regulation (CPR) Section 17. It is offered under the interim policy that was established by Health Canada permitting use of GHS-formatted safety data sheets in Canada prior to revision of CPR to GHS. This product has been classified and labeled in accordance with the requirements of GHS (ST/SG/AC.10/36/Add.3). This SDS has been prepared in accordance with the requirements of GHS (ST/SG/AC.10/36/Add.3).

Legend:

NA - Not Applicable

ND - Not Determined

NV - Not Available

w/w - weight/weight

w/v - weight/volume

v/v - volume/volume

USER RESPONSIBILITY: Each user should read and understand this information and incorporate it in individual site safety programs in accordance with applicable hazard communication standards and regulations.

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED TO BE ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF.

HACH COMPANY ©2015