### acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: November 12, 2018

Revision: November 12, 2018

### **1** Identification

- · Product identifier
- · Trade name: Phenolphthalein Indicator
- Product code: PH1605SS
- · Recommended use and restriction on use
- · Recommended use: Laboratory chemicals
- Restrictions on use: No relevant information available.
- · Details of the supplier of the Safety Data Sheet
- Manufacturer/Supplier: AquaPhoenix Scientific, Inc. 860 Gitts Run Road Hanover, PA 17331 Phone: (717)632-1291 Toll-Free: (866)632-1291 info@aquaphoenixsci.com
- Emergency telephone number: ChemTel Inc.
   (800)255-3924 (North America) +1 (813)248-0585 (International)

### 2 Hazard(s) identification

## Classification of the substance or mixture Flam. Liq. 2 H225 Highly flammable liquid and vapor. Acute Tox. 4 H302 Harmful if swallowed. Acute Tox. 4 H312 Harmful in contact with skin. Acute Tox. 4 H332 Harmful if inhaled. Eye Irrit. 2A H319 Causes serious eye irritation. Carc. 2 H351 Suspected of causing cancer. Repr. 2 H361 Suspected of damaging fertility or the unborn child. STOT SE 2 H371 May cause damage to the central nervous system and optic nerve. STOT SE 3 H336 May cause drowsiness or dizziness. Label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:



### Signal word: Danger Hazard statements:

Hazard statements.H225Highly flammable liquid and vapor.H302+H312+H332Harmful if swallowed, in contact with skin or if inhaled.H319Causes serious eye irritation.H351Suspected of causing cancer.

(Cont'd. on page 2)

### acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: November 12, 2018

Revision: November 12, 2018

### Trade name: Phenolphthalein Indicator

	(Cont'd. of page
H361	Suspected of damaging fertility or the unborn child.
H371	May cause damage to the central nervous system and optic nerve.
H336	May cause drowsiness or dizziness.
Precautionary	statements:
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe mist/vapors/spray.
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection.
P303+P361+P3	353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin wit water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P3	338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, present and easy to do. Continue rinsing.
P308+P311	IF exposed or concerned: Call a poison center/doctor.
P330	Rinse mouth.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire: Use for extinction: Alcohol resistant foam or water spray.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

### **3** Composition/information on ingredients

### · Chemical characterization: Mixtures

 • Components:
 67-63-0
 Propan-2-ol
 25%

 • Flam. Liq. 2, H225
 • Eye Irrit. 2A, H319; STOT SE 3, H336
 15.5%

 • 64-17-5
 Ethanol
 15.5%

 • Flam. Liq. 2, H225
 • Eye Irrit. 2A, H319
 9.5%

 • Flam. Liq. 2, H225
 • Eye Irrit. 2A, H319
 9.5%

 • Flam. Liq. 2, H225
 • Eye Irrit. 2A, H319
 9.5%

 • Flam. Liq. 2, H225
 • Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331
 9.5%

 • Flam. Liq. 2, H225
 • Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331
 9.5%

 • Flam. Liq. 2, H225
 • Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331
 9.5%

### acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: November 12, 2018

Revision: November 12, 2018

### Trade name: Phenolphthalein Indicator (Cont'd. of page 2) 77-09-8 phenolphthalein 0.42% 🚯 Muta. 2, H341; Carc. 1B, H350; Repr. 2, H361 7732-18-5 Water 49.58% · Additional information: For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret. For the wording of the listed Hazard Statements, refer to section 16. **4 First-aid measures** Description of first aid measures · General information: Immediately remove any clothing soiled by the product. • After inhalation: Supply fresh air: consult doctor in case of complaints. · After skin contact: If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation continues, consult a doctor. · After eve contact: Remove contact lenses if worn. Rinse opened eye for several minutes under running water. Then consult a doctor. · After swallowing: Rinse out mouth and then drink plenty of water. Do not induce vomiting; immediately call for medical help. · Most important symptoms and effects, both acute and delayed: Dizziness Nausea in case of ingestion. Acidosis Blindness **Breathing difficulty** Coughing Causes eye irritation. Gastric or intestinal disorders when ingested. Disorientation · Danger: May be harmful if swallowed, in contact with skin or if inhaled. Vapors may cause drowsiness and dizziness. May cause cancer. May cause neurotoxic effects. Danger of impaired breathing. May cause damage to the central nervous system and optic nerve. Suspected of damaging fertility or the unborn child. - Indication of any immediate medical attention and special treatment needed: Medical supervision for at least 48 hours. If medical advice is needed, have product container or label at hand.

### **5** Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: Alcohol resistant foam

(Cont'd. on page 4)

### acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: November 12, 2018

Revision: November 12, 2018

Trade name: Phenolphthalein Indicator

(Cont'd. of page 3)

Water fog / haze Carbon dioxide Gaseous extinguishing agents Water spray Fire-extinguishing powder · For safety reasons unsuitable extinguishing agents: Water stream. · Special hazards arising from the substance or mixture Highly flammable liquid and vapor. Formation of toxic gases is possible during heating or in case of fire. · Advice for firefighters · Protective equipment: Wear self-contained respiratory protective device. Wear fully protective suit. · Additional information: Use large quantities of foam as it is partially destroyed by the product. Cool endangered product with water spray.

### 6 Accidental release measures

### · Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

Keep away from ignition sources.

Use respiratory protective device against the effects of fumes/dust/aerosol. Isolate area and prevent access.

· Environmental precautions

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· Methods and material for containment and cleaning up

Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders). Send for recovery or disposal in suitable receptacles.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### 7 Handling and storage

### · Handling

· Precautions for safe handling:

Use only in well ventilated areas.

Avoid splashes or spray in enclosed areas.

Prevent formation of aerosols.

• Information about protection against explosions and fires: Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Requirements to be met by storerooms and receptacles:

(Cont'd. on page 5)

### acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: November 12, 2018

Revision: November 12, 2018

Trade name: Phenolphthalein Indicator

(Cont'd. of page 4)

Store in a well-ventilated place. Keep cool.

Avoid storage near extreme heat, ignition sources or open flame.

- Information about storage in one common storage facility: Store away from foodstuffs. Store away from oxidizing agents.
- · Further information about storage conditions: Keep containers tightly sealed.
- · Specific end use(s) No relevant information available.

b Exposure co	ontrols/personal protection	
· Control parar		
•	rith limit values that require monitoring at the workplace:	
67-63-0 Propan	· · · · · · · · · · · · · · · · · · ·	
PEL (USA)	Long-term value: 980 mg/m <sup>3</sup> , 400 ppm	
REL (USA)	Short-term value: 1225 mg/m <sup>3</sup> , 500 ppm Long-term value: 980 mg/m <sup>3</sup> , 400 ppm	
TLV (USA)	Short-term value: 984 mg/m <sup>3</sup> , 400 ppm Long-term value: 492 mg/m <sup>3</sup> , 200 ppm BEI	
EL (Canada)	Short-term value: 400 ppm Long-term value: 200 ppm	
EV (Canada)	Short-term value: 400 ppm Long-term value: 200 ppm	
LMPE (Mexico)	Short-term value: 400 ppm Long-term value: 200 ppm A4, IBE	
64-17-5 Ethano		
PEL (USA)	Long-term value: 1900 mg/m <sup>3</sup> , 1000 ppm	
REL (USA)	Long-term value: 1900 mg/m <sup>3</sup> , 1000 ppm	
TLV (USA)	Short-term value: 1880 mg/m <sup>3</sup> , 1000 ppm	
EL (Canada)	Short-term value: 1000 ppm	
EV (Canada)	Long-term value: 1,900 mg/m <sup>3</sup> , 1,000 ppm	
LMPE (Mexico)	Long-term value: 1000 ppm A3	
67-56-1 Methar	ol	
PEL (USA)	Long-term value: 260 mg/m <sup>3</sup> , 200 ppm	
REL (USA)	Short-term value: 325 mg/m <sup>3</sup> , 250 ppm Long-term value: 260 mg/m <sup>3</sup> , 200 ppm Skin	
TLV (USA)	Short-term value: 328 mg/m³, 250 ppm Long-term value: 262 mg/m³, 200 ppm Skin; BEI	
EL (Canada)	Short-term value: 250 ppm Long-term value: 200 ppm Skin	
		(Cont'd. on page

## Safety Data Sheet acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: November 12, 2018

Revision: November 12, 2018

EV (Canada)	Short-term value: 325 mg/m <sup>3</sup> , 250 ppm	(Cont'd. of page 5)
	Long-term value: 260 mg/m <sup>3</sup> , 200 ppm	
	Skin	
LMPE (Mexico)	Short-term value: 250 ppm	
	Long-term value: 200 ppm	
	PIEL, IBE	
· Ingredients wit	th biological limit values:	
67-63-0 Propar	-	
BEI (USA) 40 n		
	lium: urine	
	e: end of shift at end of workweek	
	ameter: Acetone (background, nonspecific)	
67-56-1 Methar		
BEI (USA) 15 n		
	lium: urine	
	e: end of shift	
Para	ameter: Methanol (background, nonspecific)	
The usual preca Keep away from Immediately ren Wash hands be Do not inhale ga Engineering co Breathing equi Protection of h	etive and hygienic measures: autionary measures for handling chemicals should be followed. In foodstuffs, beverages and feed. In ove all soiled and contaminated clothing. If ore breaks and at the end of work. ases / fumes / aerosols. In the end of work. ases / fumes / aerosols. ases / fumes / aerosols. as	the preparation.
	glasses	
	national guidelines concerning the use of protective eyewear. n: Protective work clothing	
	d supervision of exposure into the environment	
	rmation available.	
	ment measures No relevant information available.	
		(Contid on page 7)

### acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: November 12, 2018

Revision: November 12, 2018

### Trade name: Phenolphthalein Indicator

(Cont'd. of page 6)

9 Physical and chemical properties		
· Information on basic physical ar	nd chemical properties	
· Appearance:		
Form:	Liquid	
Color:	Colorless	
· Odor:	Like alcohol	
· Odor threshold:	Not determined.	
· pH-value:	Not determined.	
<ul> <li>Melting point/Melting range:</li> </ul>	Not determined.	
<ul> <li>Boiling point/Boiling range:</li> </ul>	64.7 °C (148.5 °F)	
· Flash point:	13 °C (55.4 °F)	
· Flammability (solid, gaseous):	Not applicable.	
· Auto-ignition temperature:	425 °C (797 °F)	
· Decomposition temperature:	Not determined.	
· Danger of explosion:	Product is not explosive. However, formation of explosive air/ vapor mixtures are possible.	
· Explosion limits		
Lower:	2 Vol %	
Upper:	15 Vol %	
<ul> <li>Oxidizing properties:</li> </ul>	Not determined.	
· Vapor pressure at 20 °C (68 °F):	59 hPa (44.3 mm Hg)	
· Density at 20 °C (68 °F):	0.89 g/cm³ (7.43 lbs/gal)	
· Relative density:	0.85-0.96	
<ul> <li>Vapor density:</li> </ul>	Not determined.	
<ul> <li>Evaporation rate:</li> </ul>	Not determined.	
· Solubility in / Miscibility with		
Water:	Fully miscible.	
· Partition coefficient (n-octanol/wate	r): Not determined.	
· Viscosity		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
<ul> <li>Other information</li> </ul>	No relevant information available.	

### 10 Stability and reactivity

### · Reactivity:

Reacts with alkali (lyes).

Reacts with certain metals.

- · Chemical stability: Stable under normal temperatures and pressures.
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

(Cont'd. on page 8)

### acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: November 12, 2018

Revision: November 12, 2018

### Trade name: Phenolphthalein Indicator

(Cont'd. of page 7)

3

1

2B

R

Possibility of hazardous reactions
 Reacts violently with oxidizing agents.
 Reacts with strong acids.
 Toxic fumes may be released if heated above the decomposition point.

· Conditions to avoid Excessive heat.

- Incompatible materials Oxidizers
- Hazardous decomposition products
   Under fire conditions only:
   Carbon monoxide and carbon dioxide

11	Toxico	logical	information
----	--------	---------	-------------

- · Information on toxicological effects
- · Acute toxicity: Harmful if swallowed, in contact with skin or if inhaled.
- · LD/LC50 values that are relevant for classification: None.
- · Primary irritant effect:
- · On the skin: Based on available data, the classification criteria are not met.
- · On the eye: Irritating effect.
- Sensitization: Based on available data, the classification criteria are not met.

### · IARC (International Agency for Research on Cancer):

67-63-0 Propan-2-ol

64-17-5 Ethanol

77-09-8 phenolphthalein

### • NTP (National Toxicology Program):

77-09-8 phenolphthalein

### · OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

- · Probable route(s) of exposure:
- Ingestion. Inhalation.
- Eye contact. Skin contact.
- Acute effects (acute toxicity, irritation and corrosivity):
- Toxic if swallowed, in contact with skin or if inhaled.
- Causes serious eye irritation.
- **Repeated dose toxicity:** Possible risk of irreversible effects.
- Germ cell mutagenicity: Suspected of causing genetic defects.
- · Carcinogenicity: May cause cancer.
- Reproductive toxicity: Suspected of damaging fertility or the unborn child.
- STOT-single exposure: May cause damage to the central nervous system and optic nerve.
- · STOT-repeated exposure: Based on available data, the classification criteria are not met.
- · Aspiration hazard: Based on available data, the classification criteria are not met.

**12 Ecological information** 

(Cont'd. on page 9)

### acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: November 12, 2018

Revision: November 12, 2018

### Trade name: Phenolphthalein Indicator

(Cont'd. of page 8)

- · Toxicity
- · Aquatic toxicity No relevant information available.
- · Persistence and degradability No relevant information available.
- · Bioaccumulative potential: No relevant information available.
- Mobility in soil: No relevant information available.
- · Additional ecological information
- · General notes: Do not allow product to reach ground water, water course or sewage system.
- Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No relevant information available.

### 13 Disposal considerations

### · Waste treatment methods

· Recommendation:

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

### · Uncleaned packagings

- Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agent: Water, if necessary with cleansing agents.

4 Transport information	
· UN-Number · DOT, ADR/RID/ADN, IMDG, IATA	UN1987
<ul> <li>· UN proper shipping name</li> <li>· DOT</li> <li>· ADR/RID/ADN, IMDG, IATA</li> </ul>	Alcohols, n.o.s. (ISOPROPANOL, Ethanol, Methanol) ALCOHOLS, N.O.S. (ISOPROPANOL, ETHANOL METHANOL)
· Transport hazard class(es)	
· DOT	
· Class	3
· Label	3
	(Cont'd. on page 1

### acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: November 12, 2018

Revision: November 12, 2018

Trade name: Phenolphthalein Indicator	
	(Cont'd. of page 9)
· ADR/RID/ADN	
· Class	3 (F1)
· Label	3
· IMDG, IATA	
Class	3
· Label	3
<ul> <li>Packing group</li> <li>DOT, ADR/RID/ADN, IMDG, IATA</li> </ul>	II
<ul> <li>Environmental hazards</li> <li>Marine pollutant:</li> </ul>	No
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	33
· EMS Number:	F-E,S-D
Transport in bulk according to Annex II ( MARPOL73/78 and the IBC Code	
	Not applicable.
Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L

# 15 Regulatory information • Safety, health and environmental regulations/legislation specific for the substance or mixture • United States (USA) • SARA • Section 302 (extremely hazardous substances): None of the ingredients are listed. • Section 315 (extremely hazardous substances): None of the ingredients are listed. • Section 313 (Specific toxic chemical listings): 67-63-0 Propan-2-ol 67-56-1 Methanol

### acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: November 12, 2018

Revision: November 12, 2018

### Trade name: Phenolphthalein Indicator

	(Cont'd. of page
· TSCA (Toxic Substances Control Act)	
All ingredients are listed.	
· Proposition 65 (California)	
Chemicals known to cause cancer:	
Ethanol - listing refers specifically to alcoholic beverage consumption and is not a	applicable for product.
64-17-5 Ethanol	
77-09-8 phenolphthalein	
· Chemicals known to cause developmental toxicity for females:	
None of the ingredients are listed.	
· Chemicals known to cause developmental toxicity for males:	
None of the ingredients are listed.	
Chemicals known to cause developmental toxicity:	
Ethanol - listing refers specifically to alcoholic beverage consumption and is not a	applicable for product.
64-17-5 Ethanol	
67-56-1 Methanol	
EPA (Environmental Protection Agency):	
None of the ingredients are listed.	
· IARC (International Agency for Research on Cancer):	
67-63-0 Propan-2-ol	3
64-17-5 Ethanol	1
77-09-8 phenolphthalein	2
Canadian Domestic Substances List (DSL) (Substances not listed.):	

### **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistant, Bio-accumulable, Toxic vPvB: very Persistent and very Bioaccumulative OSHA: Occupational Safety & Health Administration Flam. Liq. 2: Flammable liquids - Category 2 Acute Tox. 3: Acute toxicity – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A Eye Irrit. 2B: Serious eye damage/eye irritation - Category 2B Muta. 2: Germ cell mutagenicity - Category 2 Carc. 1B: Carcinogenicity – Category 1B Carc. 2: Carcinogenicity – Category 2 Repr. 2: Reproductive toxicity - Category 2

(Cont'd. on page 12)

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: November 12, 2018

Revision: November 12, 2018

### Trade name: Phenolphthalein Indicator

(Cont'd. of page 11)

STOT SE 1: Specific target organ toxicity (single exposure) - Category 1 STOT SE 2: Specific target organ toxicity (single exposure) – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Sources Website, European Chemicals Agency (echa.europa.eu) Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/ overview/home.do) Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org) Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6 Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5. Safety Data Sheets, Individual Manufacturers SDS Prepared by: ChemTel Inc. 1305 North Florida Avenue Tampa, Florida USA 33602-2902 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573 Website: www.chemtelinc.com