Page: 1/10

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: November 28, 2018 Revision: November 28, 2018

1 Identification

· Product identifier

· Trade name: ORP Standard, 400mV

Product code: OR4400SS

· Recommended use and restriction on use

· Recommended use: Laboratory chemicals

· Restrictions on use: None

Details of the supplier of the Safety Data Sheet

· Manufacturer/Supplier:

AquaPhoenix Scientific, Inc.

860 Gitts Run Road Hanover, PA 17331 Phone: (717)632-1291 Toll-Free: (866)632-1291 info@aquaphoenixsci.com

Emergency telephone number:

ChemTel Inc.

(800)255-3924 (North America) +1 (813)248-0585 (International)

2 Hazard(s) identification

· Classification of the substance or mixture

Met. Corr.1 H290 May be corrosive to metals.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:



GHS05

· Signal word: Warning · Hazard statements:

H290 May be corrosive to metals.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

Precautionary statements:

P234 Keep only in original container. P264 Wash thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection.

P302+P352 If on skin: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing.

P332+P313 If skin irritation occurs: Get medical advice/attention.

(Cont'd. on page 2)

Page: 2/10

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: November 28, 2018 Revision: November 28, 2018

Trade name: ORP Standard, 400mV

(Cont'd. of page 1)

P362+P364 Take off contaminated clothing and wash it before reuse. If eye irritation persists: Get medical advice/attention. P337+P313

Absorb spillage to prevent material damage. P390

P406 Store in corrosive resistant container with a resistant inner liner.

· NFPA ratings (scale 0 - 4)



Health = 2 Fire = 0Instability = 0

· HMIS-ratings (scale 0 - 4)



*2 Health = *2 Fire = 0

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Components:				
7732-18-5	Water	85.45%		
7783-85-9	Ferrous ammonium sulfate Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	4.0%		
7783-83-7	Ferric Ammonium Sulfate	0.15%		
	Sulfuric acid Met. Corr.1, H290; Skin Corr. 1A, H314; Eye Dam. 1, H318	10.4%		

· Additional information: For the wording of the listed Hazard Statements, refer to section 16.

4 First-aid measures

- Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Immediately rinse with water.

If skin irritation continues, consult a doctor.

Seek immediate help for blistering or open wounds.

After eye contact:

Remove contact lenses if worn, if possible.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

Most important symptoms and effects, both acute and delayed:

Causes serious eye irritation.

Irritant to skin and mucous membranes.

Nausea in case of ingestion.

(Cont'd. on page 3)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: November 28, 2018 Revision: November 28, 2018

Trade name: ORP Standard, 400mV

(Cont'd. of page 2)

Gastric or intestinal disorders when ingested.

- · Danger: Danger of gastric perforation.
- · Indication of any immediate medical attention and special treatment needed:

If medical advice is needed, have product container or label at hand.

5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- For safety reasons unsuitable extinguishing agents: None.
- · Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information: No relevant information available.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

For large spills, use respiratory protective device against the effects of fumes/dust/aerosol.

- Environmental precautions Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up

Use calcium oxide as a neutralizing agent.

Clean the affected area carefully; suitable cleaners are:

Warm water

Dispose of the collected material according to regulations.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling
- · Precautions for safe handling:

Prevent formation of aerosols.

Avoid splashes or spray in enclosed areas.

Use only in well ventilated areas.

- · Information about protection against explosions and fires: No special measures required.
- Conditions for safe storage, including any incompatibilities
- Requirements to be met by storerooms and receptacles:

Store in a cool location.

(Cont'd. on page 4)

Page: 4/10

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: November 28, 2018 Revision: November 28, 2018

Trade name: ORP Standard, 400mV

(Cont'd. of page 3)

Store only in the original receptacle.

Unsuitable material for receptacle: aluminium. Unsuitable material for receptacle: steel.

· Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from metals.

Store away from oxidizing agents.

Do not store together with alkalis (caustic solutions).

· Specific end use(s) No relevant information available.

8 Exposure controls/personal protection

· Control parameters

	· Components with limit values that require monitoring at the workplace: 7664-93-9 Sulfuric acid		
ľ	PEL (USA)	Long-term value: 1 mg/m³	
	REL (USA)	Long-term value: 1 mg/m³	
	TLV (USA)	Long-term value: 0.2* mg/m³ *as thoracic fraction	
	EL (Canada)	Long-term value: 0.2 mg/m³ ACGIH A2; IARC 1	
	EV (Canada)	Long-term value: 0.2 mg/m³	
	LMPE (Mexico)	Long-term value: 0.2* mg/m³ A2;*fracción torácica	

· Exposure controls

General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- **Engineering controls:** Provide adequate ventilation.
- · Breathing equipment: Use suitable respiratory protective device when high concentrations are present.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

Nitrile rubber, NBR

Laminated film gloves.

Neoprene gloves

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to
(Cont'd. on page 5)

Page: 5/10

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: November 28, 2018 Revision: November 28, 2018

Trade name: ORP Standard, 400mV

(Cont'd. of page 4)

be observed.

· Eye protection:



Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear.

- · Body protection: Acid resistant protective clothing.
- · Limitation and supervision of exposure into the environment

No relevant information available.

· Risk management measures

See Section 7 for additional information.

No relevant information available.

Information on basic physical and chemical properties			
Appearance:			
Form:	Liquid		
Color:	Clear		
Odor:	Not determined.		
Odor threshold:	Not determined.		
pH-value at 20 °C (68 °F):	<2.0		
Melting point/Melting range:	Not determined.		
Boiling point/Boiling range:	Not determined.		
Flash point:	Not applicable.		
Flammability (solid, gaseous):	Not applicable.		
Auto-ignition temperature:	Not determined.		
Decomposition temperature:	Not determined.		
Danger of explosion:	Product does not present an explosion hazard.		
Explosion limits			
Lower:	Not determined.		
Upper:	Not determined.		
Oxidizing properties:	Not determined.		
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)		
Density:	Not determined.		
Relative density:	Not determined.		
Vapor density:	Not determined.		
Evaporation rate:	Not determined.		
Solubility in / Miscibility with			
Water:	Soluble.		

(Cont'd. on page 6)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: November 28, 2018 Revision: November 28, 2018

Trade name: ORP Standard, 400mV

(Cont'd. of page 5)

· Viscosity

Dynamic: Not determined. **Kinematic:** Not determined.

• Other information No relevant information available.

10 Stability and reactivity

- · Reactivity: No relevant information available.
- · Chemical stability: Stable under normal temperatures and pressures.
- · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

To avoid thermal decomposition, do not overheat.

Possibility of hazardous reactions

Toxic fumes may be released if heated above the decomposition point.

Reacts with alkali (lyes).

Reacts with strong oxidizing agents.

Reacts with certain metals.

- · Conditions to avoid No relevant information available.
- · Incompatible materials

Metals.

Alkalis

Strong oxidizers such as perchlorates, bromates, and nitrates; hydrofluoric acid.

· Hazardous decomposition products

Sulfur oxides (SOx)

Toxic metal oxide smoke

11 Toxicological information

- Information on toxicological effects
- · Acute toxicity: Based on available data, the classification criteria are not met.
- LD/LC50 values that are relevant for classification: None.
- · Primary irritant effect:
- · On the skin: Irritant to skin and mucous membranes.
- · On the eye: Causes eye irritation.
- Sensitization: No sensitizing effects known.
- · IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

· NTP (National Toxicology Program):

7664-93-9 Sulfuric acid

K

OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

Probable route(s) of exposure:

Ingestion.

Inhalation.

(Cont'd. on page 7)

Page: 7/10

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: November 28, 2018 Revision: November 28, 2018

Trade name: ORP Standard, 400mV

(Cont'd. of page 6)

Eye contact.

Skin contact.

- · Acute effects (acute toxicity, irritation and corrosivity): Irritating to eyes and skin.
- Repeated dose toxicity: No relevant information available.
- · Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- · Carcinogenicity: Based on available data, the classification criteria are not met.
- Reproductive toxicity: Based on available data, the classification criteria are not met.
- · STOT-single exposure: Based on available data, the classification criteria are not met.
- STOT-repeated exposure: Based on available data, the classification criteria are not met.
- Aspiration hazard: Based on available data, the classification criteria are not met.

12 Ecological information

- · Toxicity
- · Aquatic toxicity No relevant information available.
- Persistence and degradability No relevant information available.
- · Bioaccumulative potential: No relevant information available.
- Mobility in soil: No relevant information available.
- Additional ecological information
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. If the dilution of the use-level pH-value is considerably increased after use, the aqueous waste, emptied into drains, is only low water-dangerous.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB**: Not applicable.
- Other adverse effects No relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

- Uncleaned packagings
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

(Cont'd. on page 8)

Page: 8/10

Safety Data Sheet acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: November 28, 2018 Revision: November 28, 2018

Trade name: ORP Standard, 400mV

	(Cont'd. of page
· UN-Number · DOT, ADR/RID/ADN, IMDG, IATA	UN3264
· UN proper shipping name · DOT · ADR/RID/ADN, IMDG, IATA	Corrosive liquid, acidic, inorganic, n.o.s. (Sulfuric acid) CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S (SULPHURIC ACID)
· Transport hazard class(es)	
· DOT	
· Class · Label	8 8
· ADR/RID/ADN	
· Class	8 (C1)
IMDG, IATA	
· Class · Label	8 8
· Packing group · DOT, ADR/RID/ADN, IMDG, IATA	III
Environmental hazards Marine pollutant:	No
Special precautions for user Danger code (Kemler): EMS Number: Segregation groups	Warning: Corrosive substances 80 F-A,S-B Acids
Transport in bulk according to Annex l	II of Not applicable.
· Transport/Additional information:	
· Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L

Page: 9/10

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: November 28, 2018 Revision: November 28, 2018

Trade name: ORP Standard, 400mV

(Cont'd. of page 8)

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · United States (USA)
- ·SARA
- Section 302 (extremely hazardous substances):

None of the ingredients are listed.

· Section 355 (extremely hazardous substances):

7664-93-9 Sulfuric acid

· Section 313 (Specific toxic chemical listings):

7664-93-9 Sulfuric acid

TSCA (Toxic Substances Control Act)

All ingredients are listed.

- · Proposition 65 (California)
- · Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· EPA (Environmental Protection Agency):

None of the ingredients are listed.

· IARC (International Agency for Research on Cancer):

7664-93-9 Sulfuric acid

| 1

Canadian Domestic Substances List (DSL) (Substances not listed.):

All ingredients listed on DSL or NDSL.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Page: 10/10

Safety Data Sheet acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: November 28, 2018 Revision: November 28, 2018

Trade name: ORP Standard, 400mV

(Cont'd. of page 9)

PBT: Persistant, Bio-accumulable, Toxic vPvB: very Persistent and very Bioaccumulative OSHA: Occupational Safety & Health Administration Met. Corr.1: Corrosive to metals – Category 1
Skin Corr. 1A: Skin corrosion/irritation – Category 1A
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
STOT SE 3: Specific terrent corrent position (clinical propagation)

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3