Safety Data Sheet acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: January 25, 2019

Revision: November 27, 2018

1 Identification	
· Product identifier	
 Trade name: <u>Trace Hardness Buffer (Burette)</u> Product code: AR-1043-60 	
 Recommended use and restriction on use Recommended use: Laboratory chemicals Restrictions on use: No relevant information available. 	
 Details of the supplier of the Safety Data Sheet Manufacturer/Supplier: AquaPhoenix Scientific, Inc. 860 Gitts Run Road Hanover, PA 17331 Phone: (717)632-1291 Toll-Free: (866)632-1291 info@aquaphoenixsci.com Distributor: Aqua Analytics 245 Matheson Blvd East, Units 1 & 2 Mississauga, Ontario Canada L4Z 3C9 (888) 712-4000 	
 Emergency telephone number: ChemTel Inc. (800)255-3924 (North America) +1 (813)248-0585 (International) 	
2 Hazard(s) identification	
2 Hazard(s) identification • Classification of the substance or mixture Met. Corr.1 H290 May be corrosive to metals.	
2 Hazard(s) identification • Classification of the substance or mixture Met. Corr.1 H290 May be corrosive to metals. Skin Corr. 1B H314 Causes severe skin burns and eye damage.	
2 Hazard(s) identification Classification of the substance or mixture Met. Corr.1 H290 May be corrosive to metals. Skin Corr. 1B H314 Causes severe skin burns and eye damage. Eye Dam. 1 H318 Causes serious eye damage.	
2 Hazard(s) identification Classification of the substance or mixture Met. Corr.1 H290 May be corrosive to metals. Skin Corr. 1B H314 Causes severe skin burns and eye damage. Eye Dam. 1 H318 Causes serious eye damage. STOT SE 3 H335 May cause respiratory irritation.	
2 Hazard(s) identification Classification of the substance or mixture Met. Corr.1 H290 May be corrosive to metals. Skin Corr. 1B H314 Causes severe skin burns and eye damage. Eye Dam. 1 H318 Causes serious eye damage.	;).
 2 Hazard(s) identification Classification of the substance or mixture Met. Corr.1 H290 May be corrosive to metals. Skin Corr. 1B H314 Causes severe skin burns and eye damage. Eye Dam. 1 H318 Causes serious eye damage. STOT SE 3 H335 May cause respiratory irritation. Label elements GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS) Hazard pictograms: 	;).
 2 Hazard(s) identification Classification of the substance or mixture Met. Corr.1 H290 May be corrosive to metals. Skin Corr. 1B H314 Causes severe skin burns and eye damage. Eye Dam. 1 H318 Causes serious eye damage. STOT SE 3 H335 May cause respiratory irritation. Label elements GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS) 	 }).
 2 Hazard(s) identification Classification of the substance or mixture Met. Corr.1 H290 May be corrosive to metals. Skin Corr. 1B H314 Causes severe skin burns and eye damage. Eye Dam. 1 H318 Causes serious eye damage. STOT SE 3 H335 May cause respiratory irritation. Label elements The product is classified and labeled according to the Globally Harmonized System (GHS) Hazard pictograms: GHS05 GHS07 Signal word: Danger Hazard statements: H290 May be corrosive to metals.)).
 2 Hazard(s) identification Classification of the substance or mixture Met. Corr.1 H290 May be corrosive to metals. Skin Corr. 1B H314 Causes severe skin burns and eye damage. Eye Dam. 1 H318 Causes serious eye damage. STOT SE 3 H335 May cause respiratory irritation. Label elements GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS) Hazard pictograms: GHS05 GHS07 Signal word: Danger Hazard statements:	 }).
 2 Hazard(s) identification Classification of the substance or mixture Met. Corr.1 H290 May be corrosive to metals. Skin Corr. 1B H314 Causes severe skin burns and eye damage. Eye Dam. 1 H318 Causes serious eye damage. STOT SE 3 H335 May cause respiratory irritation. Label elements GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS Hazard pictograms: GHS05 GHS07 Signal word: Danger Hazard statements: H290 May be corrosive to metals. H314 Causes severe skin burns and eye damage. 	;).

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: January 25, 2019

Revision: November 27, 2018

Trade name: Trace Hardness Buffer (Burette)

	(Cont'd. of page 1)
P260	Do not breathe mist/vapors/spray.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection.
P301+P330+P331	If swallowed: Rinse mouth. Do NOT induce vomiting.
P302+P352	If on skin: Wash with plenty of water.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing.
P310	Immediately call a poison center/doctor.
P363	Wash contaminated clothing before reuse.
P390	Absorb spillage to prevent material damage.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P406	Store in corrosive resistant container with a resistant inner liner.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
· Other hazards There are no other hazards not otherwise classified that have been identified.	

3 Composition/information on ingredients

· Chemical characterization: Mixtures

•	Components:	
---	-------------	--

	components.		
	7732-18-5	Water	60-70%
-	141-43-5	 2-aminoethanol Skin Corr. 1B, H314 Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; STOT SE 3, H335 Flam. Liq. 4, H227 	25-30%
	2002-24-6	2-hydroxyethylammonium chloride	6-8%
	14402-88-1	Disodium [[N,N'-ethylenebis[N-(carboxymethyl)glycinato]](4-)-N,N',O,O',ON,ON'] magnesate(2-) Eye Irrit. 2B, H320	0.5-0.75%
	· Additional i		
	E a u tha a l'ata .		· · · · · · · ·

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret. For the wording of the listed Hazard Statements, refer to section 16.

4 First-aid measures

- [•] Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.

· After skin contact:

Immediately rinse with water.

If skin irritation continues, consult a doctor.

Seek immediate help for blistering or open wounds.

· After eye contact:

(Cont'd. on page 3)

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: January 25, 2019

Revision: November 27, 2018

Trade name: Trace Hardness Buffer (Burette)

(Cont'd. of page 2)

Protect unharmed eye. Remove contact lenses if worn. Rinse opened eye for several minutes under running water. Then consult a doctor. · After swallowing: Rinse out mouth and then drink plenty of water. Do not induce vomiting; immediately call for medical help. Most important symptoms and effects, both acute and delayed: Couahina Gastric or intestinal disorders when ingested. Nausea in case of ingestion. Strong caustic effect on skin and mucous membranes. May cause respiratory irritation. Danger: Danger of gastric perforation. Danger of disturbed cardiac rhythm. Causes serious eye damage. Danger of impaired breathing. Indication of any immediate medical attention and special treatment needed: Medical supervision for at least 48 hours. If medical advice is needed, have product container or label at hand.

5 Fire-fighting measures

[·] Extinguishing media

• Suitable extinguishing agents: Use fire fighting measures that suit the environment.

- · For safety reasons unsuitable extinguishing agents: No relevant information available.
- Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

· Additional information: Cool endangered receptacles with water in flooding quantities.

6 Accidental release measures

[•] Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Keep away from ignition sources.

Wear protective equipment. Keep unprotected persons away.

Use respiratory protective device against the effects of fumes/dust/aerosol.

- Environmental precautions Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Send for recovery or disposal in suitable receptacles.
- [•] Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Cont'd. on page 4)

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: January 25, 2019

Revision: November 27, 2018

Trade name: Trace Hardness Buffer (Burette)

(Cont'd. of page 3)

See Section 13 for disposal information.

7 Handling and storage

· Handling

- · Precautions for safe handling:
- Prevent formation of aerosols.

Avoid splashes or spray in enclosed areas.

Use only in well ventilated areas.

· Information about protection against explosions and fires: Combustible liquid.

- · Conditions for safe storage, including any incompatibilities
- · Requirements to be met by storerooms and receptacles: Store only in the original receptacle.

Unsuitable material for receptacle: aluminium.

Unsuitable material for receptacle: steel.

- Information about storage in one common storage facility: Store away from foodstuffs.
- Do not store together with oxidizing and acidic materials. • Further information about storage conditions: Keep containers tightly sealed.

· Specific end use(s) No relevant information available.

8 Exposure controls/personal protection			
Control parameters			
· Components w	rith limit values that require monitoring at the workplace:		
141-43-5 2-ami	noethanol		
PEL (USA)	Long-term value: 6 mg/m ³ , 3 ppm		
REL (USA)	JSA) Short-term value: 15 mg/m ³ , 6 ppm Long-term value: 8 mg/m ³ , 3 ppm		
TLV (USA)	TLV (USA) Short-term value: 15 mg/m ³ , 6 ppm Long-term value: 7.5 mg/m ³ , 3 ppm		
EL (Canada)	L (Canada) Short-term value: 6 ppm Long-term value: 3 ppm		
EV (Canada)	Short-term value: 15 mg/m³, 6 ppm Long-term value: 7.5 mg/m³, 3 ppm		
LMPE (Mexico)	Short-term value: 6 ppm Long-term value: 3 ppm		
7647-01-0 hydr	7647-01-0 hydrochloric acid		
PEL (USA)	Ceiling limit value: 7 mg/m ³ , 5 ppm		
REL (USA)			
TLV (USA)			
EL (Canada)	Ceiling limit value: 2 ppm		
EV (Canada)	Ceiling limit value: 2 ppm		
LMPE (Mexico)	Ceiling limit value: 2 ppm		
L	(Cont'd. on page 5)		

(Cont'd. on page 6)

٦

Safety Data Sheet acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: January 25, 2019

· Flammability (solid, gaseous):

Revision: November 27, 2018

Trade name: Trace Hardness Buffer (Burette)			
A4	(Cont'd. of page 4)		
Exposure controls			
General protective and hygienic mea			
	The usual precautionary measures for handling chemicals should be followed. Keep away from foodstuffs, beverages and feed.		
	Immediately remove all soiled and contaminated clothing.		
Wash hands before breaks and at the e	end of work.		
Avoid contact with the eyes and skin.			
 Engineering controls: Provide adequation Breathing equipment: Suitable respiration 			
· Protection of hands:	ably protective device recommended.		
Protective gloves			
The glove material has to be impermea	The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.		
· Material of gloves			
Butyl rubber, BR	Butyl rubber, BR		
Fluorocarbon rubber (Viton)			
Neoprene gloves Nitrile rubber, NBR Natural rubber, NR			
			Sensibilization by the components in the glove materials is possible.
· Eye protection:			
Safety glasses			
Follow relevant national guidelines cond	cerning the use of protective eyewear.		
	Body protection: Protective work clothing		
Limitation and supervision of exposure into the environment			
No relevant information available.			
9 Physical and chemical propert	ies		
· Information on basic physical and	d chemical properties		
· Appearance:			
Form:	Liquid		
Color:	Colorless		
· Odor:	Not determined.		
· Odor threshold:	Not determined.		
· pH-value:	Alkaline		
• Melting point/Melting range:	Not determined.		
· Boiling point/Boiling range: 100 °C (212 °F)			
· Flash point:	Not applicable.		

Not applicable.

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: January 25, 2019

Revision: November 27, 2018

Trade name: Trace Hardness Buffer (Burette)

		(Cont'd. of page
· Auto-ignition temperature:	Not determined.	
· Decomposition temperature:	Not determined.	
· Danger of explosion:	Not determined.	
· Explosion limits		
Lower:	Not determined.	
Upper:	Not determined.	
· Oxidizing properties:	Not determined.	
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
· Density:		
Relative density:	Not determined.	
Vapor density:	Not determined.	
Evaporation rate:	Not determined.	
· Solubility in / Miscibility with		
Water:	Fully miscible.	
· Partition coefficient (n-octanol/wat	er): Not determined.	
· Viscosity		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
[·] Other information	No relevant information available.	

10 Stability and reactivity

· Reactivity: Reacts with acids,	alkalis and oxidizing agents.
----------------------------------	-------------------------------

- Chemical stability: Stable under normal temperatures and pressures.
- Thermal decomposition / conditions to be avoided:
- Toxic fumes may be released if heated above the decomposition point.

Possibility of hazardous reactions Corrosive action on metals. Reacts with certain metals. Reacts with strong oxidizing agents. Exothermic reaction with acids. Toxic fumes may be released if heated above the decomposition point. Conditions to avoid Keep ignition sources away - Do not smoke. Excessive heat. Incompatible materials Metals.

- Strong acids Oxidizers
- [.] Hazardous decomposition products
- Under fire conditions only: Nitrogen oxides
- Carbon monoxide and carbon dioxide

(Cont'd. on page 7)

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: January 25, 2019

Revision: November 27, 2018

Trade name: Trace Hardness Buffer (Burette)

(Cont'd. of page 6)

3

Chlorine

11 Toxicological information

Information on toxicological effects

· Acute toxicity: Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:

141-43-5 2-aminoethanol

Oral LD50 2050 mg/kg (rat)

Dermal LD50 1000 mg/kg (rabbit)

Primary irritant effect:

- On the skin: Strong caustic effect on skin and mucous membranes.
- · On the eye: Strong caustic effect.
- Sensitization: Based on available data, the classification criteria are not met.

· IARC (International Agency for Research on Cancer):

7647-01-0 hydrochloric acid

· NTP (National Toxicology Program):

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

- · Probable route(s) of exposure:
- Ingestion. Inhalation.
- Eve contact.
- Skin contact.

· Acute effects (acute toxicity, irritation and corrosivity):

Causes severe skin burns and eye damage.

Irritating to respiratory system.

- · Repeated dose toxicity: No relevant information available.
- Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- · Carcinogenicity: Based on available data, the classification criteria are not met.
- Reproductive toxicity: Based on available data, the classification criteria are not met.

• STOT-single exposure: May cause respiratory irritation.

- STOT-repeated exposure: Based on available data, the classification criteria are not met.
- · Aspiration hazard: Based on available data, the classification criteria are not met.

12 Ecological information

· Toxicity

- · Aquatic toxicity No relevant information available.
- · Persistence and degradability No relevant information available.
- · Bioaccumulative potential: No relevant information available.
- Mobility in soil: No relevant information available.
- [•] Additional ecological information
- · General notes:

(Cont'd. on page 8)

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: January 25, 2019

Revision: November 27, 2018

Trade name: Trace Hardness Buffer (Burette)

(Cont'd. of page 7) Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· vPvB: Not applicable.

• Other adverse effects No relevant information available.

13 Disposal considerations

[·] Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

[·] Uncleaned packagings

• Recommendation: Disposal must be made according to official regulations.

4 Transport information	
[·] UN-Number · DOT, ADR/RID/ADN, IMDG, IATA	UN3267
 UN proper shipping name DOT 	Corrosive liquid, basic, organic, n.o.s. (Ethanolamine 2-hydroxyethylammonium chloride)
· ADR/RID/ADN, IMDG, IATA	CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S (ETHANOLAMINE, 2-hydroxyethylammonium chloride)
 Transport hazard class(es) 	
· Class	8
·Label	8
· ADR/RID/ADN	
Class	8 (C7)
· Label	8
	(Cont'd. on page

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: January 25, 2019

Revision: November 27, 2018

Trade name: Trace Hardness Buffer (Burette) (Cont'd. of page 8) · IMDG, IATA Class 8 · Label 8 Packing group · DOT, ADR/RID/ADN, IMDG, IATA Ш Environmental hazards Not applicable. Special precautions for user Warning: Corrosive substances Danger code (Kemler): 80 · EMS Number: F-A,S-B · Segregation groups Alkalis [•] Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. **15 Regulatory information** · Safety, health and environmental regulations/legislation specific for the substance or mixture · United States (USA)

· SARA

· Section 302 (extremely hazardous substances):

None of the ingredients are listed.

· Section 355 (extremely hazardous substances):

7647-01-0 hydrochloric acid

· Section 313 (Specific toxic chemical listings):

7647-01-0 hydrochloric acid

· TSCA (Toxic Substances Control Act)

All ingredients are listed.

· Proposition 65 (California)

· Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

(Cont'd. on page 10)

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: January 25, 2019

Revision: November 27, 2018

Trade name: Trace Hardness Buffer (Burette)

(Cont'd. of page 9)

· EPA (Environmental Protection Agency):

None of the ingredients are listed.

· IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

· Canadian Domestic Substances List (DSL) (Substances not listed.):

All ingredients are listed.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistant, Bio-accumulable, Toxic vPvB: very Persistent and very Bioaccumulative OSHA: Occupational Safety & Health Administration Flam. Liq. 4: Flammable liquids - Category 4 Met. Corr.1: Corrosive to metals - Category 1 Acute Tox. 4: Acute toxicity - Category 4 Skin Corr. 1B: Skin corrosion/irritation - Category 1B Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2B: Serious eye damage/eye irritation - Category 2B STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 Sources Website, European Chemicals Agency (echa.europa.eu) Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/ overview/home.do) Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org) Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6 Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5. Safety Data Sheets, Individual Manufacturers SDS Prepared by: ChemTel Inc. 1305 North Florida Avenue Tampa, Florida USA 33602-2902 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com