Safety Data Sheet acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 04, 2019

Revision: February 26, 2019

 Product identifier Trade name: <u>Victoria Blue B Indicator with Xylenes</u> Product code: VB2000SS Recommended use and restriction on use Recommended use: Laboratory chemicals Restrictions on use: No relevant information available. Details of the supplier of the Safety Data Sheet Manufacturer/Supplier: AquaPhoemk Scientific, Inc. 800 Gitts Soft Association of the Safety Data Sheet Manufacturer/Supplier: AquaPhoemk Scientific, Inc. 800 Gitts Run Road Hanover, PA 17331 Phone: (7/17632-1291 Toll-Free: (866)632-1291 Toll-Free: (866)632-1291 Toll-Free: (866)632-1291 Toll-Free: (866)632-1291 Toll-Free: (866)632-53924 (North America) +1 (813)248-0585 (International) 2 Hazard(s) identification Classification of the substance or mixture Fiam. Liq. 2 H225 Highly flammable liquid and vapor. Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2A H319 Causes serious eye irritation. STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness. Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. Labol elements The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard plotograms: Cifls Jabel elements The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard statements: H225 Highly flammable liquid and vapor. H335 Causes skin irritation. H335 H338 May cause respiratory irritation. May cause drowsiness or dizziness. H304 May be fatal if swallowed and enters airways. Precautionary statements: Proceutionary statements: 	1 Identification
 Product code: VB2000SS Recommended use and restriction on use Recommended use: Laboratory chemicals Restrictions on use: No relevant information available. Details of the supplier of the Safety Data Sheet Manufacturer/Supplier: AquaPhoenix Scientific, Inc. 800 Gitts Run Road Hanover, PA 17331 Phone: (717)632-1291 Info@aquaphoenixsci.com Emergency telephone number: Chem Tel Inc. (800)255-3924 (North America) +1 (813)248-0685 (International) 2 Hazard(s) identification 3 Classification of the substance or mixture Flam. Liq. 2 H225 Highly flammable liquid and vapor. Acute Tox. 4 H332 Harmful if inhaled. Skin Irit. 2 H315 Causes seinious eye irritation. Eye Irrit. 2A H319 Causes serious eye irritation. May cause drowsiness or dizziness. Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. 4 Label elements The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms: Action Barton, Causes serious eye irritation. Hazard pictograms: Auson of the Substance or May cause drowsiness or dizziness. Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. Asp. Tox. 1 H304 Any be fatal if swallowed and enters airways. Hazard pictograms: Auson of the Substance or Harmonized System (GHS). Hazard pictograms: Auson of Causes serious eye irritation. H315 Causes serious eye irritation. H315 Causes serious eye irritation. H316 May cause respiratory irritation. May cause drowsiness or dizziness. H317 Causes serious eye irritation. H318 Causes serious eye irritation. H318 Causes erepiratory irritation. H319 Causes serious eye irritation. H319 Causes serious eye irritation. H319 Causes serious eye irritation. H319 Causes erepirato	· Product identifier
 Recommended use: Laboratory chemicals Restrictions on use: No relevant information available. Details of the supplier of the Safety Data Sheet Manufacturer/Supplier: AquaPhoenix Scientific, Inc. 800 Gitts Run Road Hanover, PA 17331 Phone: (717)632-1291 Toll-Free: (866)632-1291 info@aquaphoenixsci.com Emergency telephone number: Chem Tel Inc. (800)255-3924 (North America) +1 (813)248-0585 (International) Z Hazard(s) identification Classification of the substance or mixture Flam. Liq. 2 H225 Highly flammable liquid and vapor. Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2A H315 Causes serious eye irritation. STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness. Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. Label elements OHS abeled elements OHS abeled is a stress of the Substance or the Globally Harmonized System (GHS). Hazard statements: H225 Highly flammable liquid and vapor. H326 August of the Substance or the Globally Harmonized System (GHS). Hazard statements: H225 Highly flammable liquid and vapor. H336 H316 Causes serious eye irritation. H335-H336 May cause respiratory to the Globally Harmonized System (GHS). Hazard pictograms: W25 H316 Causes serious eye irritation. H335 Causes serious eye irritation. H335 Causes serious eye irritation. H335 Causes serious eye irritation. H335 H336 May cause respiratory inflation. H335 Causes serious eye irritation. H336 May cause respiratory irritation. H336 May be fatal if swallowed and enters airways. Precautionary statements: H240 M May be fatal if swallowed and enters airways. 	
$ \begin{array}{llllllllllllllllllllllllllllllllllll$	Recommended use: Laboratory chemicals
ChemTel Inc. (800)255-3924 (North America) +1 (813)248-0585 (International) 2 Hazard(s) identification classification of the substance or mixture Flam. Liq. 2 H225 Highly flammable liquid and vapor. Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2A H319 Causes serious eye irritation. STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness. Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. - Label elements GHS 1 abel elements The product is classified and labeled according to the Globally Harmonized System (GHS). - Hazard pictograms: * Signal word: Danger + Hazard statements: H225 Highly flammable liquid and vapor. H332 Harmful if inhaled. H315 Causes skin irritation. H335-H336 May cause respiratory irritation. H336-H336 May cause respiratory irritation. H336-H336 May cause respiratory irritation. H336-H336 May cause respiratory irritation. H336-H341 if swallowed and enters airways. * Precautionary statements:	Manufacturer/Supplier: AquaPhoenix Scientific, Inc. 860 Gitts Run Road Hanover, PA 17331 Phone: (717)632-1291 Toll-Free: (866)632-1291
• Classification of the substance or mixture Flam. Liq. 2 H225 Highly flammable liquid and vapor. Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2A H319 Causes serious eye irritation. STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness. Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. • Label elements • • GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). • Hazard pictograms: • • GHS02 GHS07 GHS08 • • Signal word: Danger • • Hazard statements: H225 H225 Highly flammable liquid and vapor. H332 Harmful if inhaled. H315 Causes serious eye irritation. H335 Causes serious eye irritation. H335 Causes serious eye irritation. H319 Causes serious eye irritation. H335 Causes serious eye irritation. H336 May be fatal if swallowed and enters airways. H304	ChemTel Inc. (800)255-3924 (North America)
Flam. Liq. 2H225Highly flammable liquid and vapor.Acute Tox. 4H332Harmful if inhaled.Skin Irrit. 2H315Causes skin irritation.Eye Irrit. 2AH319Causes serious eye irritation. May cause drowsiness or dizziness.Asp. Tox. 1H304May be fatal if swallowed and enters airways.•Label elements•GHS label elementsThe product is classified and labeled according to the Globally Harmonized System (GHS).•Hazard pictograms: $\widetilde{\psi}$ $\widetilde{\psi}$ $\widetilde{\psi}$ $\widetilde{\psi}$ $\widetilde{GHS02}$ GHS07 $\widetilde{GHS08}$ •Signal word: Danger•Hazard statements:H225Highly flammable liquid and vapor.H335Causes skin irritation.H315Causes serious eye irritation.H316Causes serious eye irritation.H317Causes serious eye irritation.H318Causes eserious eye irritation.H335-H336May cause respiratory irritation.H335-H336May cause respiratory irritation.H304May be fatal if swallowed and enters airways.•Precautionary statements:	2 Hazard(s) identification
Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2A H319 Causes serious eye irritation. STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness. Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. • Label elements • GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). • Hazard pictograms: • • With State elements • GHS02 GHS07 GHS08 • • Signal word: Danger • • Hazard statements: • H225 Highly flammable liquid and vapor. H335 Causes skin irritation. H319 Causes serious eye irritation. H315 Causes serious eye irritation. H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness. H304 May be fatal if swallowed and enters airways. • Precautionary statements: •	· Classification of the substance or mixture
Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2A H319 Causes serious eye irritation. STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness. Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. • Label elements • GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). • Hazard pictograms: $\widetilde{\psi}$ $\widetilde{\psi}$ GHS02 GHS07 GHS08 • Signal word: Danger • Hazard statements: H225 Highly flammable liquid and vapor. H332 Harmful if inhaled. H315 Causes skin irritation. H319 Causes serious eye irritation. H334 May cause respiratory irritation. H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness. H304 May be fatal if swallowed and enters airways. • Precautionary statements: •	Flam. Liq. 2 H225 Highly flammable liquid and vapor.
Eye Irrit. 2A H319 Causes serious eye irritation. STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness. Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. • Label elements • GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). • Hazard pictograms: Image: Comparison of the terminal statements: H225 Highly flammable liquid and vapor. H322 Harmful if inhaled. H315 Causes serious eye irritation. H319 Causes serious eye irritation. H319 Causes serious eye irritation. H336 May cause respiratory irritation. May cause drowsiness or dizziness. H304 May be fatal if swallowed and enters airways.	
 STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness. Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. Label elements GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms: Output <	
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. • Label elements GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). • Hazard pictograms: Image: Construct of the Globally Harmonized System (GHS). • Hazard pictograms: Image: Construct of the Globally Harmonized System (GHS). • Hazard pictograms: Image: Construct of the Globally Harmonized System (GHS). • Hazard pictograms: Image: Construct of the Globally Harmonized System (GHS). • Hazard pictograms: Image: Construct of the Globally Harmonized System (GHS). • Hazard pictograms: Image: Construct of the Globally Harmonized System (GHS). • Hazard pictograms: • GHS02 GHS07 GHS08 • Signal word: Danger • Hazard statements: H225 Highly flammable liquid and vapor. H322 Harmful if inhaled. H315 Causes skin irritation. H319 Causes serious eye irritation. H336-H336 May cause respiratory irritation. May cause drowsiness or dizziness. H304 May be fatal if swallowed and enters airways. • Precautionary statemen	·
 Label elements GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms: Image and Image and Image according to the Globally Harmonized System (GHS). GHS02 GHS07 GHS08 Signal word: Danger Hazard statements: H225 Highly flammable liquid and vapor. H332 Harmful if inhaled. H315 Causes skin irritation. H319 Causes serious eye irritation. H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness. H304 May be fatal if swallowed and enters airways. Precautionary statements: 	
 GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms: Image: Image: Im	
 Signal word: Danger Hazard statements: H225 Highly flammable liquid and vapor. H332 Harmful if inhaled. H315 Causes skin irritation. H319 Causes serious eye irritation. H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness. H304 May be fatal if swallowed and enters airways. Precautionary statements: 	 • GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). • Hazard pictograms:
 H225 Highly flammable liquid and vapor. H332 Harmful if inhaled. H315 Causes skin irritation. H319 Causes serious eye irritation. H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness. H304 May be fatal if swallowed and enters airways. • Precautionary statements: 	
 H332 Harmful if inhaled. H315 Causes skin irritation. H319 Causes serious eye irritation. H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness. H304 May be fatal if swallowed and enters airways. • Precautionary statements: 	
 H315 Causes skin irritation. H319 Causes serious eye irritation. H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness. H304 May be fatal if swallowed and enters airways. • Precautionary statements: 	
H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness. H304 May be fatal if swallowed and enters airways. • Precautionary statements:	H315 Causes skin irritation.
H304 May be fatal if swallowed and enters airways. • Precautionary statements:	
Precautionary statements:	
(Cont'd. on page 2	Precautionary statements:
、	(Cont'd. on page 2

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 04, 2019

Revision: February 26, 2019

Trade name: Victoria Blue B Indicator with Xylenes (Cont'd. of page 1) P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ventilating/lighting/equipment. P242 Use only non-sparking tools. Take precautionary measures against static discharge. P243 P261 Avoid breathing mist, vapors, or spray. Wash thoroughly after handling. P264 Use only outdoors or in a well-ventilated area. P271 Wear protective gloves/protective clothing/eye protection/face protection. P280 P301+P310 If swallowed: Immediately call a poison center/doctor. P331 Do NOT induce vomiting. P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 Call a poison center/doctor if you feel unwell. P332+P313 If skin irritation occurs: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse. P337+P313 If eve irritation persists: Get medical advice/attention. P370+P378 In case of fire: Use for extinction: Alcohol resistant foam. Store in a well-ventilated place. Keep cool. P403+P235 Store locked up. P405 P501 Dispose of contents/container in accordance with local/regional/national/international regulations. · Other hazards There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Compone	· Components:		
1330-20-7	Xylene Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	44.24%	
67-63-0	Propan-2-ol Flam. Liq. 2, H225 Eye Irrit. 2A, H319; STOT SE 3, H336	26.92%	
64-17-5	Ethanol Flam. Liq. 2, H225 Eye Irrit. 2A, H319	25.97%	
67-56-1	Methanol Flam. Liq. 2, H225 Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331 STOT SE 1, H370 Eye Irrit. 2B, H320	1.47%	
	(Cont [*]	d. on page 3)	

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 04, 2019

Revision: February 26, 2019

Trade name: Victoria Blue B Indicator with Xylenes

	(Cont'd. of page 2)
7732-18-5 Water	1.37%
2580-56-5 [4-[[4-anilino-1-naphthyl][4-(dimethylamino)phenyl]methylene]cyclohexa-2,5 ylidene]dimethylammonium chloride	5-dien-1- 0.03%
Acute Tox. 4, H302; Eye Irrit. 2A, H319	
· Additional information:	
For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as	s a trade secret.

For the wording of the listed Hazard Statements, refer to section 16.

4 First-aid measures

Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Take affected persons out into the fresh air.

· After inhalation:

Supply fresh air.

Provide oxygen treatment if affected person has difficulty breathing.

If experiencing respiratory symptoms: Call a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation continues, consult a doctor.

· After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

A person vomiting while lying on their back should be turned onto their side.

· Most important symptoms and effects, both acute and delayed:

Breathing difficulty Dizziness Coughing Gastric or intestinal disorders when ingested. Nausea in case of ingestion. Vomiting. Headache Irritating to eyes, respiratory system and skin. Disorientation **Danger:** Harmful if inhaled. May be harmful if swallowed. May be harmful in contact with skin.

Danger of impaired breathing.

Danger of disturbed cardiac rhythm.

May be fatal if swallowed and enters airways.

May cause drowsiness or dizziness.

May cause neurotoxic effects.

Condition may deteriorate with alcohol consumption.

(Cont'd. on page 4)

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 04, 2019

Revision: February 26, 2019

Trade name: Victoria Blue B Indicator with Xylenes

(Cont'd. of page 3)

· Indication of any immediate medical attention and special treatment needed:

If swallowed or in case of vomiting, danger of entering the lungs.

If swallowed, gastric irrigation with added, activated carbon.

Medical supervision for at least 48 hours.

If necessary oxygen respiration treatment.

Later observation for pneumonia and pulmonary edema.

If medical advice is needed, have product container or label at hand.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: Alcohol resistant foam Carbon dioxide Gaseous extinguishing agents Water fog / haze Fire-extinguishing powder
- For safety reasons unsuitable extinguishing agents: Water stream. Water spray
- Special hazards arising from the substance or mixture Highly flammable liquid and vapor. Formation of toxic gases is possible during heating or in case of fire.
- Advice for firefighters
 Protective equipment: Wear self-contained respiratory protective device. Wear fully protective suit.
- Additional information: Eliminate all ignition sources if safe to do so. Use large quantities of foam as it is partially destroyed by the product. Cool endangered containers with water fog.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures
 Isolate area and prevent access.
 Wear protective equipment. Keep unprotected persons away.
 Use respiratory protective device against the effects of fumes/dust/aerosol.
 Ensure adequate ventilation.
 Keep away from ignition sources.
 Take precautionary measures against static discharge.
 Protect from heat.

 Environmental precautions Do not allow to enter sewers/ surface or ground water.

 Methods and material for containment and cleaning up
 Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).
 Send for recovery or disposal in suitable receptacles.

See Section 7 for information on safe handling.

(Cont'd. on page 5)

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 04, 2019

Revision: February 26, 2019

Trade name: Victoria Blue B Indicator with Xylenes

(Cont'd. of page 4)

See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

· Handling

Precautions for safe handling: Avoid splashes or spray in enclosed areas. Prevent formation of aerosols. Use only in well ventilated areas. Information about protection against explosions and fires:

Highly flammable liquid and vapor. Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Flammable gas-air mixtures may be formed in empty containers/receptacles.

 Conditions for safe storage, including any incompatibilities
 Requirements to be met by storerooms and receptacles: Store in a cool location.
 Avoid storage near extreme heat, ignition sources or open flame.

 Information about storage in one common storage facility: Store away from foodstuffs.
 Store away from oxidizing agents.

• Further information about storage conditions: Keep containers tightly sealed.

· Specific end use(s) No relevant information available.

8 Exposure controls/personal protection

· Control parameters

· Components w	vith limit values that require monitoring at the workplace:	
1330-20-7 Xyle	ne	
PEL (USA)	Long-term value: 435 mg/m ³ , 100 ppm	
REL (USA)	Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm	
TLV (USA)	Short-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm BEI	
EL (Canada)	Short-term value: 150 ppm Long-term value: 100 ppm	
EV (Canada)	Short-term value: 650 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm	
LMPE (Mexico)	Short-term value: 150 ppm Long-term value: 100 ppm A4, IBE	
67-63-0 Propan	n-2-ol	
PEL (USA)	Long-term value: 980 mg/m ³ , 400 ppm	
		Cont'd. on page

Safety Data Sheet acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 04, 2019

Trade name: Victoria Blue B Indicator with Xylenes

Revision: February 26, 2019

		(Cont'd. of page 5)
REL (USA)	Short-term value: 1225 mg/m ³ , 500 ppm	(00000000000000000000000000000000000000
	Long-term value: 980 mg/m ³ , 400 ppm	
TLV (USA)	Short-term value: 984 mg/m ³ , 400 ppm	
	Long-term value: 492 mg/m ³ , 200 ppm BEI	
EL (Canada)	Short-term value: 400 ppm	
	Long-term value: 200 ppm	
EV (Canada)	Short-term value: 400 ppm	
· · · ·	Long-term value: 200 ppm	
LMPE (Mexico)	Short-term value: 400 ppm	
	Long-term value: 200 ppm	
	A4, IBE	
64-17-5 Ethano		
PEL (USA)	Long-term value: 1900 mg/m ³ , 1000 ppm	
REL (USA)	Long-term value: 1900 mg/m ³ , 1000 ppm	
TLV (USA)	Short-term value: 1880 mg/m ³ , 1000 ppm	
EL (Canada)	Short-term value: 1000 ppm	
EV (Canada)	Long-term value: 1,900 mg/m ³ , 1,000 ppm	
LMPE (Mexico)	Long-term value: 1000 ppm	
67-56-1 Methan	A3	
PEL (USA)	Long-term value: 260 mg/m ³ , 200 ppm	
REL (USA)	Short-term value: 325 mg/m ³ , 250 ppm Long-term value: 260 mg/m ³ , 200 ppm	
	Skin	
TLV (USA)	Short-term value: 328 mg/m ³ , 250 ppm	
	Long-term value: 262 mg/m ³ , 200 ppm	
	Skin; BEI	
EL (Canada)	Short-term value: 250 ppm	
	Long-term value: 200 ppm Skin	
EV (Canada)	Short-term value: 325 mg/m ³ , 250 ppm	
	Long-term value: 260 mg/m ³ , 200 ppm	
	Skin	
LMPE (Mexico)	Short-term value: 250 ppm	
	Long-term value: 200 ppm	
	PIEL, IBE	
Ingredients with biological limit values:		
1330-20-7 Xylene		
BEI (USA) 1.5 g/g creatinine Medium: urine		
Time: end of shift		
Parameter: Methylhippuric acids		
67-63-0 Propan		
BEI (USA) 40 mg/L		
BEI (USA) 40 m	IG/L	

Safety Data Sheet acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 04, 2019

Revision: February 26, 2019

lue name.	Victoria Blue B Indicator with Xylenes
	(Cont'd. of pa
	Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)
67-56-1 M	ethanol
BEI (USA)	15 mg/L Medium: urine Time: end of shift Parameter: Methanol (background, nonspecific)
The usual Keep away Immediate Wash han Do not inha Avoid cont Engineeri Breathing Use suitab NIOSH or	rotective and hygienic measures: precautionary measures for handling chemicals should be followed. / from foodstuffs, beverages and feed. ly remove all soiled and contaminated clothing. ds before breaks and at the end of work. ale gases / fumes / aerosols. act with the eyes and skin. ng controls: Provide adequate ventilation. equipment: le respiratory protective device when high concentrations are present. EN approved organic vapor respirator equipped with a dust/mist prefilter should be used. n of hands:
Material o Laminated	film gloves.
	ble are gloves made of the following materials: materials listed above should be used.
Sa	afety glasses
Body prot	evant national guidelines concerning the use of protective eyewear. ection: Solvent resistant protective clothing n and supervision of exposure into the environment at information available.
Dia	
Physica	l and chemical properties

- · Appearance: Form:
- Color:
- · Odor:

Liquid Colorless Characteristic

(Cont'd. on page 8)

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 04, 2019

Revision: February 26, 2019

Trade name: Victoria Blue B Indicator with Xylenes

	(Cont'd. of page
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Melting point/Melting range:	Not determined.
 Boiling point/Boiling range: 	78 °C (172.4 °F)
· Flash point:	10-15 °C (50-59 °F)
· Flammability (solid, gaseous):	Not applicable.
· Auto-ignition temperature:	>260 °C (>500 °F)
· Decomposition temperature:	Not determined.
· Danger of explosion:	Product is not explosive. However, formation of explosive a vapor mixtures are possible.
· Explosion limits	
Lower:	Not determined.
Upper:	Not determined.
 Oxidizing properties: 	Non-oxidizing.
· Vapor pressure:	Not determined.
· Density at 20 °C (68 °F):	0.83 g/cm ³ (6.93 lbs/gal)
· Relative density:	Not determined.
 Vapor density: 	Not determined.
· Evaporation rate:	Not determined.
\cdot Solubility in / Miscibility with	
Water:	Partly miscible.
· Alcohols:	Fully miscible.
· Partition coefficient (n-octanol/wa	ter): Not determined.
· Viscosity	
Dynamic:	Not determined.
Kinematic:	Not determined.
 Other information 	No relevant information available.

10 Stability and reactivity

- · Reactivity: No relevant information available.
- Chemical stability: Stable under normal temperatures and pressures.
- Thermal decomposition / conditions to be avoided:
- No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions** Reacts violently with oxidizing agents.
- Reacts violently with oxidizing agents.
- Used empty containers may contain product gases which form explosive mixtures with air.
- Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized. Highly flammable liquid and vapor.

Reacts with strong acids and alkali.

Conditions to avoid

Keep ignition sources away - Do not smoke.

(Cont'd. on page 9)

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 04, 2019

Γ

Revision: February 26, 2019

Trade name: Victoria Blue B Indicator with Xylenes

(Cont'd. of page 8)

Store away from oxidizing agents.

- Incompatible materials Oxidizing agents
- Hazardous decomposition products Under fire conditions only: Carbon monoxide and carbon dioxide

11	11 Toxicological information			
	Information on toxicological effects Acute toxicity: Harmful if inhaled. LD/LC50 values that are relevant for classification:			
	ATE (Acu	te Toxicit	y Estimate)	
	Oral	LD50	4004 mg/kg	
	Dermal	LD50	3702 mg/kg	
	Inhalative	LC50/4h	18.5 mg/l	
	1330-20-7	Xylene		
	Oral	LD50	4300 mg/kg (rat)	
	Dermal	LD50	2000 mg/kg (rabbit)	
	· On the ey	in: Irritant e: Causes	ect: t to skin and mucous membranes. s eye irritation. ed on available data, the classification criteria are not met.	
	•		I Agency for Research on Cancer):	
	1330-20-7	-		3
		Propan-2	2-ol	3
	64-17-5	Ethanol		1
	•		icology Program):	
	None of th	e ingredie	ents are listed.	
	· OSHA-Ca	(Occupa	tional Safety & Health Administration):	
	None of th	e ingredie	ents are listed.	
		route(s) o	of exposure:	
	Ingestion. Inhalation.			
	Eve conta			
	Skin contact.			
			e toxicity, irritation and corrosivity):	
			owed and enters airways.	
	Irritating to eyes, respiratory system and skin. Harmful if inhaled.			
	Vapors ha		ic effect	
			vallowed or in contact with skin.	
			icity: No relevant information available.	
	· Germ cell mutagenicity: Based on available data, the classification criteria are not met.			
	· Carcinoge	enicity: B	ased on available data, the classification criteria are not met.	(Cont'd. on page 10)

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 04, 2019

Revision: February 26, 2019

Trade name: Victoria Blue B Indicator with Xylenes

(Cont'd. of page 9)

• Reproductive toxicity: Based on available data, the classification criteria are not met.

· STOT-single exposure:

May cause respiratory irritation.

May cause drowsiness or dizziness.

- STOT-repeated exposure: Based on available data, the classification criteria are not met.
- · Aspiration hazard: May be fatal if swallowed and enters airways.

12 Ecological information

· Toxicity

· Aquatic toxicity

1330-20-7 Xylene

LC50 13.4 mg/l (pimephales promelas)

· Persistence and degradability No relevant information available.

- · Bioaccumulative potential: No relevant information available.
- Mobility in soil: No relevant information available.
- · Additional ecological information

· General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No relevant information available.

13 Disposal considerations

Waste treatment methods

· Recommendation:

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

Uncleaned packagings

- **Recommendation:** Disposal must be made according to official regulations.
- Recommended cleansing agent: Water, if necessary with cleansing agents.

4 Transport information	
· UN-Number · DOT, ADR/RID/ADN, IMDG, IATA	UN1993
 • UN proper shipping name • DOT 	Flammable liquids, n.o.s. (Xylenes, Ethanol, ISOPROPANOL)
	(Cont'd. on page 11

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 04, 2019

Revision: February 26, 2019

Trade name: Victoria Blue B Indicator with Xylenes (Cont'd. of page 10) FLAMMABLE LIQUID, N.O.S. (XYLENES, ETHANOL · ADR/RID/ADN, IMDG (ETHYL ALCOHOL), ISOPROPANOL) · IATA FLAMMABLE LIQUID, N.O.S. (XYLENES, ETHANOL, **ISOPROPANOL**) · Transport hazard class(es) · DOT 3 · Class · Label 3 · ADR/RID/ADN · Class 3 (F1) · Label 3 · IMDG, IATA 3 Class · Label 3 · Packing group · DOT, ADR/RID/ADN, IMDG, IATA Ш · Environmental hazards Not applicable. Special precautions for user Warning: Flammable liquids · Danger code (Kemler): 33 · EMS Number: F-E,S-E Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: · DOT · Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture

(Cont'd. on page 12)

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 04, 2019

Revision: February 26, 2019

Trade name: Victoria Blue B Indicator with Xylenes
(Cont'd. of page 11)
·SARA
Section 302 (extremely hazardous substances):
None of the ingredients are listed.
· Section 355 (extremely hazardous substances):
None of the ingredients are listed.
Section 313 (Specific toxic chemical listings):
1330-20-7 Xylene
67-63-0 Propan-2-ol
67-56-1 Methanol
• TSCA (Toxic Substances Control Act)
All ingredients are listed.
Chemicals known to cause cancer: Ethanol - listing refers specifically to alcoholic beverage consumption and is not applicable for product. 64-17-5 Ethanol
Chemicals known to cause developmental toxicity for females:
None of the ingredients are listed.
Chemicals known to cause developmental toxicity for males:
None of the ingredients are listed.
Chemicals known to cause developmental toxicity: Ethanol - listing refers specifically to alcoholic beverage consumption and is not applicable for product.
64-17-5 Ethanol
67-56-1 Methanol
• EPA (Environmental Protection Agency):
1330-20-7 Xylene
IARC (International Agency for Research on Cancer):
1330-20-7 Xylene 3
67-63-0 Propan-2-ol 3
64-17-5 Ethanol 1
Canadian Domestic Substances List (DSL) (Substances not listed.):
All ingredients are listed.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road IMDG: International Maritime Code for Dangerous Goods

- DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 04, 2019

Revision: February 26, 2019

Trade name: Victoria Blue B Indicator with Xylenes

(Cont'd. of page 12) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistant, Bio-accumulable, Toxic vPvB: very Persistent and very Bioaccumulative OSHA: Occupational Safety & Health Administration Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 3: Acute toxicity – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A Eye Irrit. 2B: Serious eye damage/eye irritation - Category 2B STOT SE 1: Specific target organ toxicity (single exposure) - Category 1 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 Asp. Tox. 1: Aspiration hazard - Category 1 Sources Website, European Chemicals Agency (echa.europa.eu) Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/ overview/home.do) Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org) Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6 Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5. Safety Data Sheets, Individual Manufacturers SDS Prepared by: ChemTel Inc. 1305 North Florida Avenue Tampa, Florida USA 33602-2902 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573 Website: www.chemtelinc.com