according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: February 14, 2020

1 Identification

· Product identifier

· Trade name: Aluminum Metal Granular

· Product code: AL7200

· **CAS Number:** 7429-90-5

· Recommended use and restriction on use

· Recommended use: Laboratory chemicals

Restrictions on use: No relevant information available.

Details of the supplier of the Safety Data Sheet

· Manufacturer/Supplier:

AquaPhoenix Scientific, Inc.

860 Gitts Run Road

Hanover, PA 17331 USA

Tel +1 (717)632-1291

Toll-Free: (866)632-1291

info@aquaphoenixsci.com

Distributor:

AquaPhoenix Scientific

860 Gitts Run Road,

Hanover, PA 17331

(717) 632-1291

· Emergency telephone number:

ChemTel Inc.

(800)255-3924 (North America)

+1 (813)248-0585 (International)

2 Hazard(s) identification

· Classification of the substance or mixture

Pyr. Sol. 1 H250 Catches fire spontaneously if exposed to air.

Water-react. 2 H261 In contact with water releases flammable gas.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms:



GHS02

· Signal word: Danger

· Hazard statements:

H250 Catches fire spontaneously if exposed to air.

H261 In contact with water releases flammable gas.

· Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P223 Do not allow contact with water.

(Cont'd. on page 2)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: February 14, 2020

Trade name: Aluminum Metal Granular

(Cont'd. of page 1)

P231+P232 Handle under inert gas. Protect from moisture.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment. P280 Wear protective gloves/protective clothing/eye protection.

P335+P334 Brush off loose particles from skin. Immerse in cool water/wrap in wet bandages.

P370+P378 In case of fire: Use for extinction: Dry sand, graphite powder, or special powder for metal fires.

P402+P404 Store in a dry place. Store in a closed container.

P422 Store contents under inert gas.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· NFPA ratings (scale 0 - 4) The substance demonstrates unusual reactivity with water.

Other hazards There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

- Chemical characterization: Substances
- · CAS No. Description 7429-90-5 Aluminium

4 First-aid measures

- Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

· After skin contact:

In case of contact with burning product:

Brush off loose particles from skin. Immerse in cool water/wrap in wet bandages.

Immediate medical treatment necessary. Failure to treat burns can prevent wounds from healing.

· After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

· Most important symptoms and effects, both acute and delayed:

Breathing difficulty

Dizziness

Nausea in case of ingestion.

Gastric or intestinal disorders when ingested.

- · Danger: Danger of impaired breathing.
- Indication of any immediate medical attention and special treatment needed:

If medical advice is needed, have product container or label at hand.

5 Fire-fighting measures

(Cont'd. on page 3)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: February 14, 2020

Trade name: Aluminum Metal Granular

(Cont'd. of page 2)

Extinguishing media

Suitable extinguishing agents:

Dry sand.

Graphite powder.

Special powder for metal fires. Do not use water.

- · For safety reasons unsuitable extinguishing agents: Water
- · Special hazards arising from the substance or mixture

Flammable solid.

In contact with water releases flammable gas.

Formation of toxic gases is possible during heating or in case of fire.

- Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

· Additional information: Eliminate all ignition sources if safe to do so.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

For large spills, use respiratory protective device against the effects of fumes/dust/aerosol.

Ensure adequate ventilation.

Protect from heat.

Do not allow contact with water.

Keep away from ignition sources.

Environmental precautions

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

Methods and material for containment and cleaning up

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Send for recovery or disposal in suitable receptacles.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Handling

· Precautions for safe handling:

Prevent formation of dust.

Any deposit of dust which cannot be avoided must be regularly removed.

Use only in well ventilated areas.

Information about protection against explosions and fires:

Protect against electrostatic charges.

Flammable solid.

In contact with water releases flammable gas.

(Cont'd. on page 4)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: February 14, 2020

Trade name: Aluminum Metal Granular

(Cont'd. of page 3)

- Conditions for safe storage, including any incompatibilities
- Requirements to be met by storerooms and receptacles:

Store in a cool location.

Avoid storage near extreme heat, ignition sources or open flame.

· Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidizing agents.

Do not store together with acids.

Protect from humidity and water.

· Further information about storage conditions:

Keep containers tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No relevant information available.

8 Exposure controls/personal protection

· Control parameters

· Components with limit values that require monitoring at the workplace:					
7429-90-5 aluminium powder (stabilised)					
PEL (USA)	Long-term value: 15*; 5** mg/m³ *Total dust; ** Respirable fraction				
REL (USA)	Long-term value: 10* 5** mg/m³ as Al*Total dust**Respirable/pyro powd./welding f.				
TLV (USA)	Long-term value: 1* mg/m³ as Al; *as respirable fraction				
EL (Canada)	Long-term value: 1.0 mg/m³ respirable, as Al				
EV (Canada)	Long-term value: 5 mg/m³ aluminium-containing (as aluminium)				
LMPE (Mexico)	Long-term value: 1* mg/m³ A4, *fracciòn respirable				

Exposure controls

· General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Do not breathe dust/fume/gas/mist/vapors/spray.

- · Engineering controls: Provide adequate ventilation.
- · Breathing equipment: Not required under normal conditions of use.
- · Protection of hands:



Thermally-protective gloves.

· Eye protection:

(Cont'd. on page 5)

Safety Data Sheet according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: February 14, 2020

Trade name: Aluminum Metal Granular

(Cont'd. of page 4)



Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear.

- · Body protection: Protective work clothing
- Limitation and supervision of exposure into the environment

No relevant information available.

9 Physical and chemical properties					
· Information on basic physical and chemical properties · Appearance:					
Form:	Solid				
Color:	Silver-colored				
· Odor:	Odorless				
· Odor threshold:	Not determined.				
· pH-value:	Not applicable.				
· Melting point/Melting range:	660 °C (1220 °F)				
· Boiling point/Boiling range:	2500 °C (4532 °F)				
· Flash point:	Not applicable.				
· Flammability (solid, gaseous):	Flammable solid.				
· Auto-ignition temperature:	Not determined.				
· Decomposition temperature:	Not determined.				
· Danger of explosion:	Not determined.				
· Explosion limits					
Lower:	Not determined.				
Upper:	Not determined.				
· Oxidizing properties:	Not determined.				
· Vapor pressure:	Not determined.				
· Density at 20 °C (68 °F):	2.7 g/cm³ (22.53 lbs/gal)				
· Relative density:	Not determined.				
· Vapor density:	Not applicable.				
· Evaporation rate:	Not applicable.				
· Solubility in / Miscibility with					
Water:	Insoluble.				
· Partition coefficient (n-octanol/water): Not determined.					
· Viscosity					
Dynamic:	Not applicable.				
Kinematic:	Not applicable.				
· Other information	No relevant information available.				

(Cont'd. on page 6)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: February 14, 2020

Trade name: Aluminum Metal Granular

(Cont'd. of page 5)

10 Stability and reactivity

- · Reactivity: No relevant information available.
- · Chemical stability: Stable under normal temperatures and pressures.
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

· Possibility of hazardous reactions

Reacts with oxidizing agents.

Flammable solid.

Toxic fumes may be released if heated above the decomposition point.

· Conditions to avoid

Store away from oxidizing agents.

Keep ignition sources away - Do not smoke.

- · Incompatible materials No relevant information available.
- · Hazardous decomposition products

Under fire conditions only:

Aluminium oxide smoke

11 Toxicological information

- Information on toxicological effects
- Acute toxicity: Based on available data, the classification criteria are not met.
- · LD/LC50 values that are relevant for classification: None.
- · Primary irritant effect:
- · On the skin: Based on available data, the classification criteria are not met.
- · On the eye: Based on available data, the classification criteria are not met.
- · Sensitization: Based on available data, the classification criteria are not met.
- IARC (International Agency for Research on Cancer):

Substance is not listed.

· NTP (National Toxicology Program):

Substance is not listed.

· OSHA-Ca (Occupational Safety & Health Administration):

Substance is not listed.

· Probable route(s) of exposure:

Ingestion.

Inhalation.

Eye contact.

Skin contact.

- · Acute effects (acute toxicity, irritation and corrosivity): No relevant information available.
- · Repeated dose toxicity: No relevant information available.
- · Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- · Carcinogenicity: Based on available data, the classification criteria are not met.
- · Reproductive toxicity: Based on available data, the classification criteria are not met.
- · STOT-single exposure: Based on available data, the classification criteria are not met.
- · STOT-repeated exposure: Based on available data, the classification criteria are not met.
- · Aspiration hazard: Based on available data, the classification criteria are not met.

Page: 7/9

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: February 14, 2020

Trade name: Aluminum Metal Granular

(Cont'd. of page 6)

12 Ecological information

- · Toxicity
- · Aquatic toxicity No relevant information available.
- · Persistence and degradability No relevant information available.
- · Bioaccumulative potential: No relevant information available.
- Mobility in soil: No relevant information available.
- · Other adverse effects No relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

- Uncleaned packagings
- · Recommendation: Disposal must be made according to official regulations.

14	Transi	nort	infor	mation

· UN-Number

· DOT, ADR/RID/ADN, IMDG, IATA UN1396

UN proper shipping name

Aluminum powder, uncoated

· ADR/RID/ADN, IMDG, IATA ALUMINIUM POWDER, UNCOATED

- Transport hazard class(es)
- · DOT



4.3 · Class · Label 4.3

ADR/RID/ADN



· Class 4.3 (W2) 4.3

Label

(Cont'd. on page 8)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: February 14, 2020

Trade name: Aluminum Metal Granular

(Cont'd. of page 7)

· IMDG, IATA



• Class 4.3 • Label 4.3

· Packing group

· DOT, ADR/RID/ADN, IMDG, IATA

• Environmental hazards Not applicable.

· Special precautions for user Warning: Substances which, in contact with water, emit

flammable gases

· Hazard identification number (Kemler code): 423

EMS Number: F-G,S-O

· Segregation groups Powdered metals

Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · United States (USA)
- ·SARA
- Section 302 (extremely hazardous substances):

Substance is not listed.

Section 313 (Specific toxic chemical listings):

Substance is listed.

· TSCA (Toxic Substances Control Act)

7429-90-5 aluminium powder (stabilised)

- · Proposition 65 (California)
- · Chemicals known to cause cancer:

Substance is not listed.

Chemicals known to cause developmental toxicity for females:

Substance is not listed.

Chemicals known to cause developmental toxicity for males:

Substance is not listed.

· Chemicals known to cause developmental toxicity:

Substance is not listed.

EPA (Environmental Protection Agency):

(Cont'd. on page 9)

Page: 9/9

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: February 14, 2020

Trade name: Aluminum Metal Granular

(Cont'd. of page 8)

Substance is not listed.

· IARC (International Agency for Research on Cancer):

Substance is not listed.

· Canadian Domestic Substances List (DSL):

Substance is not listed.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

OSHA: Occupational Safety & Health Administration

Pyr. Sol. 1: Pyrophoric solids - Category 1

Water-react. 2: Substances and mixtures which in contact with water emit flammable gases - Category 2

· Sources

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtel.com