DC3100SS

Version number: 1.0 Date of compilation: 2025-11-13

SECTION 1: Identification

1.1 Product identifier

Trade name Dichlorofluorescein, 0.1% w/v in 50% Ethanol

SDS Identifier DC3100SS

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses laboratory and analytical use

1.3 Details of the supplier of the safety data sheet

AquaPhoenix Scientific 860 Gitts Run Road Hanover PA 17331 United States

Telephone: (866) 632-1291

e-mail: info@aquaphoenixsci.com

Website: https://www.aquaphoenixsci.com/

1.4 Emergency telephone number

Emergency information service ChemTel Inc.: 1-800-255-3924, +01-813-248-0585

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200, Rev. 2024)

Hazard class	Category	Hazard class and category	Hazard statement
flammable liquid	2	Flam. Liq. 2	H225
acute toxicity (oral)	5	Acute Tox. 5	H303
serious eye damage/eye irritation	2	Eye Irrit. 2	H319
carcinogenicity	1A	Carc. 1A	H350

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200, Rev. 2024)

- Signal word danger

- Pictograms

GHS02, GHS07, GHS08



United States: en Page: 1 / 17

DC3100SS

Version number: 1.0 Date of compilation: 2025-11-13

- Hazard statements

H225 Highly flammable liquid and vapour.
 H303 May be harmful if swallowed.
 H319 Causes serious eye irritation.

H350 May cause cancer.

- Precautionary statements

P203 Obtain, read and follow all safety instructions before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P264+P265 Wash hands thoroughly after handling. Do not touch eyes.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P301+P317 IF SWALLOWED: Get medical help.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse affected areas with

water or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P318 IF exposed or concerned, get medical advice. P337+P317 If eye irritation persists: Get medical help.

P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regula-

tions.

- Hazardous ingredients for labelling

Ethanol, methyl alcohol

2.3 Other hazards

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of $\geq 0.1\%$.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of \geq 0.1%.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
Water	CAS No 7732-18-5	49.9		
Ethanol	CAS No 64-17-5	42.9	Flam. Liq. 2 / H225 Eye Irrit. 2 / H319 Carc. 1A / H350	

United States: en Page: 2 / 17

DC3100SS

Version number: 1.0 Date of compilation: 2025-11-13

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
Isopropanol	CAS No 67-63-0	4.505	Flam. Liq. 2 / H225 Eye Irrit. 2 / H319 STOT SE 3 / H336	
methyl alcohol	CAS No 67-56-1	2.145	Flam. Liq. 2 / H225 Acute Tox. 3 / H301 Acute Tox. 3 / H311 Acute Tox. 3 / H331 STOT SE 1 / H370	
Methyl isobutyl ketone	CAS No 108-10-1	0.45	Flam. Liq. 2 / H225 Acute Tox. 5 / H303 Acute Tox. 4 / H332 Eye Irrit. 2 / H319 Carc. 2 / H351 STOT SE 3 / H335 STOT SE 3 / H336	
2,7-Dichlorofluorescein	CAS No 76-54-0	0.1	Skin Irrit. 2 / H315 Eye Irrit. 2A / H319 STOT SE 3 / H335	1

Remarks

For full text of abbreviations: see SECTION 16

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, Alcohol resistant foam, BC-powder, Carbon dioxide (CO2)

Unsuitable extinguishing media

Water jet

United States: en Page: 3 / 17

Version number: 1.0 Date of compilation: 2025-11-13

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO2)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

Wear impact- and splash-resistant eyewear.

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

Advice on general occupational hygiene

United States: en Page: 4 / 17

Version number: 1.0 Date of compilation: 2025-11-13

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

Control of the effects

Protect against external exposure, such as

heat, high temperatures, light, UV-radiation/sunlight

- Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)

Coun- try	Name of agent	CAS No	Identi- fier	TWA [ppm]	TWA [mg/m³]	STEL [ppm]	STEL [mg/m³]	Ceiling-C [ppm]	Ceiling-C [mg/m³]	Nota- tion	Source
US	hexone	108-10-1	REL	50 (10 h)	205 (10 h)	75	300				NIOSH REL
US	hexone (methyl isobutyl ketone)	108-10-1	PEL	100	410						29 CFR 1910.10 00
US	methyl isobutyl ketone	108-10-1	TLV®	20	82	75	307				ACGIH® 2025
US	methyl isobutyl ketone (hexone)	108-10-1	PEL (CA)	50	205	75	300				Cal/OSH A PEL
US	ethanol	64-17-5	TLV®			1,000	1,880				ACGIH® 2025
US	ethyl alcohol	64-17-5	REL	1,000 (10 h)	1,900 (10 h)						NIOSH REL
US	ethyl alcohol (eth- anol)	64-17-5	PEL (CA)	1,000	1,900						Cal/OSH A PEL
US	ethyl alcohol (eth- anol)	64-17-5	PEL	1,000	1,900						29 CFR 1910.10 00
US	methanol	67-56-1	TLV®	200	262	250	328			Н	ACGIH® 2025
US	methyl alcohol	67-56-1	PEL	200	260						29 CFR 1910.10 00

United States: en Page: 5 / 17

Version number: 1.0 Date of compilation: 2025-11-13

Occupational exposure limit values (Workplace Exposure Limits) CAS No Name of agent Identi-**TWA TWA STEL STEL** Ceiling-C Ceiling-C Source Coun-Nota-[mg/m³] [mg/m³] [ppm] [ppm] [mg/m³] [ppm] try fier tion US methyl alcohol 67-56-1 REL 200 260 250 325 Н NIOSH (10 h) (10 h)REL US methyl alcohol 67-56-1 PEL 200 260 250 325 1,000 Н Cal/OSH (methanol) (CA) A PEL US 67-63-0 TLV® 491 984 **ACGIH®** 2-propanol 200 400 2025 US isopropyl alcohol 67-63-0 **PEL** 400 980 500 1,225 Cal/OSH A PEL (CA) US 67-63-0 400 980 NIOSH isopropyl alcohol **REL** 500 1,225 REL (10 h) (10 h)US isopropyl alcohol 67-63-0 PEL 400 980 29 CFR 1910.10

Notation

Ceiling-C ceiling value is a limit value above which exposure should not occur

H absorbed through the skin

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period

00

(unless otherwise specified)

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-

weighted average (unless otherwise specified

Biological limit values Country Name of agent **Notation Identifier Value** Source **Parameter** US methyl isobutyl ketone methyl isobutyl ketone **BEI®** 1 mg/l ACGIH® 2025 US methanol methanol **BEI®** 15 mg/l ACGIH® 2025 US 2-propanol acetone **BEI®** 40 mg/l ACGIH® 2025

Relevant DNELs of components							
Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time	
methyl alcohol	67-56-1	DNEL	130 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic ef- fects	
methyl alcohol	67-56-1	DNEL	130 mg/m ³	human, inhalatory	worker (industry)	acute - systemic ef- fects	
methyl alcohol	67-56-1	DNEL	130 mg/m³	human, inhalatory	worker (industry)	chronic - local effects	
methyl alcohol	67-56-1	DNEL	130 mg/m ³	human, inhalatory	worker (industry)	acute - local effects	
methyl alcohol	67-56-1	DNEL	20 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic ef- fects	
methyl alcohol	67-56-1	DNEL	20 mg/kg bw/day	human, dermal	worker (industry)	acute - systemic ef- fects	
Methyl isobutyl ketone	108-10-1	DNEL	83 mg/m³	human, inhalatory	worker (industry)	chronic - systemic ef- fects	

United States: en Page: 6 / 17

Version number: 1.0 Date of compilation: 2025-11-13

Relevant DNELs of components Name of substance **Endpoint Threshold CAS No** Protection goal, **Used in Exposure time** level route of exposure Methyl isobutyl ketone 108-10-1 DNEL 208 mg/m³ human, inhalatory worker (industry) acute - systemic effects Methyl isobutyl ketone 108-10-1 DNEL 83 mg/m³ human, inhalatory worker (industry) chronic - local effects 208 mg/m³ acute - local effects Methyl isobutyl ketone 108-10-1 **DNEL** human, inhalatory worker (industry) Methyl isobutyl ketone 108-10-1 DNEL 11.8 mg/kg human, dermal worker (industry) chronic - systemic efbw/day fects

Relevant PNECs of components							
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time	
Methyl isobutyl ketone	108-10-1	PNEC	0.6 ^{mg} / _l	aquatic organisms	freshwater	short-term (single instance)	
Methyl isobutyl ketone	108-10-1	PNEC	0.06 ^{mg} / _l	aquatic organisms	marine water	short-term (single instance)	
Methyl isobutyl ketone	108-10-1	PNEC	27.5 ^{mg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)	
Methyl isobutyl ketone	108-10-1	PNEC	8.27 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single instance)	
Methyl isobutyl ketone	108-10-1	PNEC	0.83 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single instance)	
Methyl isobutyl ketone	108-10-1	PNEC	1.3 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)	

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

United States: en Page: 7 / 17

Version number: 1.0 Date of compilation: 2025-11-13

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Product description: See website or catalog for details.

Physical state	liquid
Color	yellow
Odor	characteristic
Melting point/freezing point	-98 °C
Boiling point or initial boiling point and boiling range	64.7 °C at 1,013 hPa
Evaporation rate	not determined
Flammability	flammable liquid in accordance with GHS criteria
Lower and upper explosion limit	not determined
Flash point	9.7 °C at 1,013 hPa
Auto-ignition temperature	>260 °C (auto-ignition temperature (liquids and gases))
Decomposition temperature	not relevant
pH (value)	not determined
Kinematic viscosity	not determined

Solubility(ies)

Water solubility	miscible in any proportion
------------------	----------------------------

Partition coefficient

Partition coefficient n-octanol/water (log value)	this information is not available
---	-----------------------------------

Vapor pressure	169.3 hPa at 25 °C
----------------	--------------------

Density and/or relative density

Density	not determined
Relative vapour density	information on this property is not available

Particle characteristics	not relevant (liquid)
--------------------------	-----------------------

United States: en Page: 8 / 17

Version number: 1.0 Date of compilation: 2025-11-13

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200, Rev. 2024)

Acute toxicity

May be harmful if swallowed.

- Acute toxicity estimate (ATE)

Oral 4,662 ^{mg}/_{kg}

Acute toxicity estimate (ATE) of components

Name of substance	CAS No	Exposure route	ATE
methyl alcohol	67-56-1	oral	100 ^{mg} / _{kg}
methyl alcohol	67-56-1	dermal	300 ^{mg} / _{kg}
methyl alcohol	67-56-1	inhalation: vapor	3 ^{mg} / _l /4h
Methyl isobutyl ketone	108-10-1	oral	4,570 ^{mg} / _{kg}
Methyl isobutyl ketone	108-10-1	inhalation: vapor	11.6 ^{mg} / _l /4h

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

United States: en Page: 9 / 17

DC3100SS

Version number: 1.0 Date of compilation: 2025-11-13

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

May cause cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans

Name of substance	CAS No	Classification	Number
Isopropanol	67-63-0	3	
Ethanol	64-17-5	1	
Methyl isobutyl ketone	108-10-1	2B	

Legend

Carcinogenic to humansPossibly carcinogenic to humans

Not classifiable as to carcinogenicity in humans

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

11.2 Information on other hazards

There is no additional information.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of \geq 0.1%.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of \geq 0.1%.

12.7 Other adverse effects

Data are not available.

United States: en Page: 10 / 17

Version number: 1.0 Date of compilation: 2025-11-13

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Please consider the relevant national or regional provisions.

SECTION 14: Transport information

14.1 UN number

DOT UN 1987
IMDG-Code UN 1987
ICAO-TI UN 1987

14.2 UN proper shipping name

DOT Alcohols, n.o.s.

IMDG-Code ALCOHOLS, N.O.S.

ICAO-TI Alcohols, n.o.s.

14.3 Transport hazard class(es)

DOT 3
IMDG-Code 3
ICAO-TI 3

14.4 Packing group

DOT II IMDG-Code II ICAO-TI II

14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations

14.6 Other relevant information

Shipping container markings and labels, received from AquaPhoenix, may vary from the above information. Products that are regulated for transport will be packaged by AquaPhoenix as Dangerous Goods in Excepted Quantities according to IATA, US DOT, and IMDG regulations. AquaPhoenix may also elect to ship certain products as UN 3316 Chemical Kit, Hazard Class 9, Packing Group II or III. In case of reshipment, it is the responsibility of the shipper to determine appropriate labels and markings in accordance with applicable transportation regulations.

14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

<u>Information for each of the UN Model Regulations</u>

Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Particulars in the shipper's declaration UN1987, Alcohols, n.o.s., 3, II

Reportable quantity (RQ) 233,100 lbs (105,828 kg) (methyl alcohol) (Methyl isobutyl

ketone)

Danger label(s) 3

United States: en Page: 11 / 17

Version number: 1.0 Date of compilation: 2025-11-13



Special provisions (SP) 172, IB2, T7, TP1, TP8, TP28

ERG No 127

International Maritime Dangerous Goods Code (IMDG) - Additional information

Marine pollutant - Danger label(s) 3



Special provisions (SP) 274

Excepted quantities (EQ) E2

Limited quantities (LQ) 1 L

EmS F-E, S-D

Stowage category B

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Danger label(s) 3



Special provisions (SP) A3, A180

Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question National regulations (United States)

Toxic Substance Control Act (TSCA) all ingredients are listed (ACTIVE) or exempt from

listing

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings

Name of substance	CAS No	Remarks	Effective date
Isopropanol	67-63-0	only persons who manufacture by the strong acid process are subject, supplier notification not required	1986-12-31

United States: en Page: 12 / 17

Version number: 1.0 Date of compilation: 2025-11-13

Toxics Release Inventory: Specific	Toxic Chemical Lis	tings	
Name of substance	CAS No	Remarks	Effective date
methyl alcohol	67-56-1		1986-12-31
Methyl isobutyl ketone	108-10-1		1986-12-31

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
methyl alcohol	67-56-1		3 4	5000 (2270)
Methyl isobutyl ketone	108-10-1		3 4	5000 (2270)

Legend

- 3 "3" indicates that the source is section 112 of the Clean Air Act
- 4 "4" indicates that the source is section 3001 of the Resource Conservation and Recovery Act (RCRA)

Clean Air Act

none of the ingredients are listed

Right to Know Hazardous Substance List

- Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
Isopropanol	67-63-0		F3
methyl alcohol	67-56-1		TE F3
Ethanol	64-17-5		CA MU TE F3
Methyl isobutyl ketone	108-10-1		F3 R1

<u>Legend</u>

CA Carcinogenic

F3 Flammable - Third Degree

MU Mutagenic

R1 Reactive - First Degree

TE Teratogenic

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals			
Name acc. to inventory CAS No Remarks Type of the toxicity			
methanol	67-56-1		developmental

United States: en Page: 13 / 17

Version number: 1.0 Date of compilation: 2025-11-13

Proposition 65 List of chemicals			
Name acc. to inventory	CAS No	Remarks	Type of the toxicity
ethanol (ethyl alcohol)	64-17-5	in alcoholic beverages	developmental
methyl isobutyl ketone	108-10-1		cancer
methyl isobutyl ketone (MIBK)	108-10-1		developmental

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	2	temporary or minor injury may occur
Flammability	3	material that can be ignited under almost all ambient temperature conditions
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	3	material that can be ignited under almost all ambient temperature conditions
Health	0	material that, under emergency conditions, would offer no hazard beyond that of ordinary combustible material
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
AU	AIIC	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	all ingredients are listed

United States: en Page: 14 / 17

Version number: 1.0 Date of compilation: 2025-11-13

Country	Inventory	Status
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed (ACTIVE)

<u>Legend</u>

AIIC Australian Inventory of Industrial Chemicals
CICR Chemical Inventory and Control Regulation

CSCL-ENCS List of Existing and New Chemical Substances (CSCL-ENCS)

DSL Domestic Substances List (DSL)

ECSI EC Substance Inventory (EINECS, ELINCS, NLP)

IECSC Inventory of Existing Chemical Substances Produced or Imported in China

INSQ National Inventory of Chemical Substances

ISHA-ENCS Inventory of Existing and New Chemical Substances (ISHA-ENCS)

KECI Korea Existing Chemicals Inventory NZIOC New Zealand Inventory of Chemicals

PICCS Philippine Inventory of Chemicals and Chemical Substances (PICCS)

 ${\sf REACH\ Reg.}\quad {\sf REACH\ registered\ substances}$

TCSI Taiwan Chemical Substance Inventory

TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH® 2025	From ACGIH®, 2025 TLVs® and BEIs® Book. Copyright 2025. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement
Acute Tox.	Acute toxicity
ATE	Acute Toxicity Estimate
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
Carc.	Carcinogenicity
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
DOT	Department of Transportation (USA)

United States: en Page: 15 / 17

DC3100SS

Version number: 1.0 Date of compilation: 2025-11-13

Abbr.	Descriptions of used abbreviations
ED	Endocrine disruptor
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ERG No	Emergency Response Guidebook - Number
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NLP	No-Longer Polymer
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TLV®	Threshold Limit Values
TWA	Time-weighted average
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

Globally Harmonized System of Classification and Labelling of Chemicals ("Purple book").

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

United States: en Page: 16 / 17

DC3100SS

Version number: 1.0 Date of compilation: 2025-11-13

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H303	May be harmful if swallowed.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H350	May cause cancer.
H351	Suspected of causing cancer.
H370	Causes damage to organs.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

United States: en Page: 17 / 17