Revision: August 04, 2020

Product ic	lontifior			
Trade name Product co	e: <u>Lead Pb</u>			
Recommer	ded use: L	nd restriction on use aboratory chemicals No relevant information		
Details of Manufactur AquaPhoen 860 Gitts Re Hanover, PA Tel +1 (717 Toll-Free: (8 info@aquap Distributor AquaPhoen 860 Gitts Re Hanover, F (717) 632-	rer/Supplie ix Scientific un Road A 17331 US 6632-1291 666)632-129 bhoenixsci.c : ix Scientific un Road, PA 17331	, Inc. SA 91 com	ata Sheet	
Emergency ChemTel In (800)255-3 +1 (813)24	c. 924 (North	America)		
Hazard(s	idontifi	ation		

Carc. 1A	H350	May cause cancer. Route of exposure: Inhalation.
Repr. 1A	H360-H362	May damage fertility or the unborn child. May cause harm to breast-fed children.
STOT RE 1		Causes damage to the central nervous system, the kidneys and the nervous system through prolonged or repeated exposure. Route of exposure: Oral, Inhalation.

_ _ _ _

[•] Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms:



· Signal word: Danger

Hazard statements:

H302 Harmful if swallowed. H350 May cause cancer. Route of exposure: Inhalation.

(Cont'd. on page 2)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: August 04, 2020

Trade name: Lead Pb

- -

H360-H3 H372	(Cont'd. of page 1) 62 May damage fertility or the unborn child. May cause harm to breast-fed children. Causes damage to the central nervous system, the kidneys and the nervous system through prolonged or repeated exposure. Route of exposure: Oral, Inhalation.
· Precauti	onary statements:
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P263	Avoid contact during pregnancy/while nursing.
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P3	312 If swallowed: Call a poison center/doctor if you feel unwell.
P330	Rinse mouth.
P308+P3	313 IF exposed or concerned: Get medical advice/attention.
P314	Get medical advice/attention if you feel unwell.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
[.] Other h	azards There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Componei	nts:	
7439-92-1	lead (mass metal form)	80-100%
	🗞 Carc. 2, H351; Repr. 1A, H360-H362; STOT RE 1, H372	
7440-36-0		1-10%
	🗞 Carc. 2, H351; STOT RE 2, H373	
7440-38-2		0.1-2.0%
	 Acute Tox. 3, H301; Acute Tox. 3, H331 Carc. 1A, H350 	

· Additional information:

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret. For the wording of the listed Hazard Statements, refer to section 16.

4 First-aid measures

[•] Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation:

Supply fresh air.

Seek immediate medical advice.

Provide oxygen treatment if affected person has difficulty breathing.

If experiencing respiratory symptoms: Call a poison center/doctor.

After skin contact:

(Cont'd. on page 3)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: August 04, 2020

Trade name: Lead Pb

(Cont'd. of page 2) Wash with soap and water. After contact with the molten product, cool rapidly with cold water. In case of thermal burns, seek medical help. · After eye contact: Remove contact lenses if worn. Rinse opened eye for 15 minutes under running water. If symptoms persist, consult a doctor. · After swallowing: Rinse out mouth and then drink plenty of water. Do not induce vomiting; immediately call for medical help. Most important symptoms and effects, both acute and delayed: Mechanical irritation to eyes and skin. Gastric or intestinal disorders when ingested. Danger: Harmful if swallowed. May damage fertility or the unborn child. May cause harm to breast-fed children. Causes damage to the central nervous system, the kidneys and the nervous system through prolonged or repeated exposure. Route of exposure: Oral, Inhalation. May cause cancer. Route of exposure: Inhalation. Indication of any immediate medical attention and special treatment needed: Medical supervision for at least 48 hours. If medical advice is needed, have product container or label at hand. 5 Fire-fighting measures

• Extinguishing media

• Suitable extinguishing agents: Use fire fighting measures that suit the environment.

- For safety reasons unsuitable extinguishing agents: No relevant information available.
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

Advice for firefighters

Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

6 Accidental release measures

[•] Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

For large spills, use respiratory protective device against the effects of fumes/dust/aerosol.

• Environmental precautions

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

Methods and material for containment and cleaning up

Pick up mechanically.

Send for recovery or disposal in suitable receptacles.

Reference to other sections

See Section 7 for information on safe handling.

(Cont'd. on page 4)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: August 04, 2020

Trade name: Lead Pb

(Cont'd. of page 3)

See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

[·] Handling

· Precautions for safe handling:

- Prevent formation of dust.
- Use only in well ventilated areas.
- · Information about protection against explosions and fires: No special measures required.

· Conditions for safe storage, including any incompatibilities

- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidizers, strong acids, strong bases.

- Further information about storage conditions: Keep containers tightly sealed.
- Specific end use(s) No relevant information available.

8 Exposure controls/personal protection

· Control parameters

Components w	Components with limit values that require monitoring at the workplace:		
7439-92-1 lead	(mass metal form)		
PEL (USA)	Long-term value: 0.05* mg/m³ *see 29 CFR 1910.1025		
REL (USA)	Long-term value: 0.05* mg/m³ *8-hr TWA ;See PocketGuide App.C		
TLV (USA)	Long-term value: 0.05* mg/m³ *and inorganic compounds, as Pb; BEI		
EL (Canada)	Long-term value: 0.05 mg/m³ R; IARC 2B		
EV (Canada)	Long-term value: 0.05 mg/m³ as Pb, Skin (organic compounds)		
LMPE (Mexico)	Long-term value: 0.05 mg/m³ A3, IBE		
7440-36-0 antin	nony		
PEL (USA)	Long-term value: 0.5 mg/m³ as Sb		
REL (USA)	Long-term value: 0.5 mg/m³ as Sb		
TLV (USA)	Long-term value: 0.5 mg/m³ as Sb		
EL (Canada)	Long-term value: 0.5 mg/m³ as Sb		
<u> </u>	(Cont'd. on page 5)		

Revision: August 04, 2020

Trade nam	e: Lead	Pb
-----------	---------	----

			(Cont'd. of page 4)
EV (Canad	la)	Long-term value: 0.5 mg/m³	
LMPE (Me)	xico)	Long-term value: 0.5 mg/m³ como Sb	
7440-38-2		nic	
PEL (USA)		Long-term value: 0.5* 0.01** mg/m³ as As; *organic**inorg. compds.; 29 CFR 1910.1018	
REL (USA))	Ceiling limit value: 0.002 mg/m³ as As; 15min; See Pocket Guide App. A	
TLV (USA)		Long-term value: 0.01 mg/m³ as As; BEI	
EL (Canada	a)	Long-term value: 0.01 mg/m³ as As; ACGIH A1, IARC1	
EV (Canad	a)	Short-term value: 0.05 mg/m³ Long-term value: 0.01 mg/m³ as As	
LMPE (Me	xico)	Long-term value: 0.01 mg/m³ A1, IBE; como As	
· Ingredient	s wit	h biological limit values:	
7439-92-1 BEI (USA)		(mass metal form)	
	Med Time Para 10 µ Med Time Para	ium: blood e: not critical imeter: Lead g/100 ml ium: blood e: not critical imeter: Lead (women of child bearing potential)	
7440-38-2			
BEI (USA)	Med Time	g As/L ium: urine e: end of workweek imeter: Inorganic arsenic plus methylated metabolites (background)	
The usual p Keep away Wash hand • Engineerir • Breathing • Protection Wear glove • Material of A recomme	rotec preca from ds bei ng co equi of h es for f glov endat of any	tive and hygienic measures: utionary measures for handling chemicals should be followed. foodstuffs, beverages and feed. fore breaks and at the end of work. introls: Provide adequate ventilation. pment: Not required under normal conditions of use. ands: protection against thermal and mechanical hazards according to OSHA a ves ion for a suitable glove material is not available. Testing will be required potential glove materials.	
			(Cont d. on page 6)

Revision: August 04, 2020

Trade name: Lead Pb

(Cont'd. of page 5)

Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear. · Body protection: Protective work clothing

Limitation and supervision of exposure into the environment No relevant information available.

· Risk management measures No relevant information available.

Information on basic physical and	d chemical properties	
· Appearance:	a chemical properties	
Form:	Solid material	
Color:	Light blue	
· Odor:	Odorless	
Odor threshold:	Not determined.	
· pH-value:	Not applicable.	
 Melting point/Melting range: 	327.4 °C (621.3 °F)	
· Boiling point/Boiling range:	1740 °C (3164 °F)	
· Flash point:	Not applicable.	
· Flammability (solid, gaseous):	Not determined.	
Auto-ignition temperature:	Not determined.	
· Decomposition temperature:	Not determined.	
[·] Danger of explosion:	Product does not present an explosion hazard.	
· Explosion limits		
Lower:	Not determined.	
Upper:	Not determined.	
· Oxidizing properties:	Non-oxidizing.	
· Vapor pressure at 970 °C (1778 °F):	1.3 mm Hg	
· Density at 20 °C (68 °F):	11.3 g/cm³ (94.3 lbs/gal)	
· Relative density:	Not determined.	
· Vapor density:	Not applicable.	
· Evaporation rate:	Not applicable.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
	Insoluble.	
Partition coefficient (n-octanol/water)	: Not determined.	
Viscosity		
Dynamic:	Not applicable.	
Kinematic:	Not applicable.	

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: August 04, 2020

Trade name: Lead Pb

(Cont'd. of page 6)

[•] Other information

No relevant information available.

10 Stability and reactivity

· Reactivity: No relevant information available.

• Chemical stability: Stable under normal temperatures and pressures.

Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

• Possibility of hazardous reactions No dangerous reactions known.

· Conditions to avoid No relevant information available.

· Incompatible materials No relevant information available.

· Hazardous decomposition products Leadoxide vapor

11 Toxicological information

· Information on toxicological effects

· Acute toxicity: Harmful if swallowed.

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate) Oral LD50 >1920-2216 mg/kg (rat) Inhalative LC50/4h 25-500 mg/l 7439-92-1 lead (mass metal form) Oral LD50 >2000 mg/kg (rat) 7440-36-0 antimony Oral LD50 7000 mg/kg (rat) 7440-38-2 arsenic Oral LD50 763 mg/kg (rat) · Primary irritant effect: • On the skin: Based on available data, the classification criteria are not met. · On the eye: Based on available data, the classification criteria are not met. • Sensitization: Based on available data, the classification criteria are not met. · IARC (International Agency for Research on Cancer): 7439-92-1 lead (mass metal form) 2B 7440-38-2 arsenic 1 • NTP (National Toxicology Program): 7439-92-1 lead (mass metal form) R Κ 7440-38-2 arsenic **OSHA-Ca** (Occupational Safety & Health Administration): 7440-38-2 arsenic Probable route(s) of exposure: Ingestion. Inhalation. (Cont'd. on page 8)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: August 04, 2020

Trade name: Lead Pb

(Cont'd. of page 7)

Eye contact. Skin contact.

- Acute effects (acute toxicity, irritation and corrosivity): No relevant information available.
- Repeated dose toxicity: Danger of serious damage to health by prolonged exposure.
- · Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- · Carcinogenicity: May cause cancer. Route of exposure: Inhalation.
- Reproductive toxicity: May damage fertility or the unborn child. May cause harm to breast-fed children.
- STOT-single exposure: Based on available data, the classification criteria are not met.

STOT-repeated exposure:

Causes damage to the central nervous system, the kidneys and the nervous system through prolonged or repeated exposure. Route of exposure: Oral, Inhalation.

· Aspiration hazard: Based on available data, the classification criteria are not met.

12 Ecological information

[·] Toxicity

- · Aquatic toxicity No relevant information available.
- · Persistence and degradability No relevant information available.
- · Bioaccumulative potential: May be accumulated in organism
- **Mobility in soil:** No relevant information available.
- Additional ecological information
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

The product contains heavy metals. Avoid transfer into the environment. Specific preliminary treatments are necessary.

Other adverse effects No relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

[·] Uncleaned packagings

· Recommendation: Disposal must be made according to official regulations.

14 Transport information		
· UN-Number · DOT, ADR/RID/ADN, IMDG, IATA	Not regulated.	
 UN proper shipping name DOT, ADR/RID/ADN, IMDG, IATA 	Not regulated.	
· Transport hazard class(es)		
		(Cont'd. on page 9)

Revision: August 04, 2020

Trade name: Lead Pb

		(Cont'd. of page 8
· DOT, ADR/RID/ADN, IMDG, IATA		
· Class	Not regulated.	
· Packing group		
DOT, ADR/RID/ADN, IMDG, IATA	Not regulated.	
· Environmental hazards	Not applicable.	
· Special precautions for user	Not applicable.	
[•] Transport in bulk according to Annex	(II of	
MARPOL73/78 and the IBC Code	Not applicable.	

15 Regulatory information

· SARA	
· Section 302 (extremely hazardous subst	ances):
None of the ingredients are listed.	
· Section 313 (Specific toxic chemical list	ngs):
All ingredients are listed.	
· TSCA (Toxic Substances Control Act)	
All ingredients are listed or exempt.	
[·] Proposition 65 (California)	
Chemicals known to cause cancer:	
7439-92-1 lead (mass metal form)	
7440-38-2 arsenic	
· Chemicals known to cause development	tal toxicity for females:
7439-92-1 lead (mass metal form)	
· Chemicals known to cause development	tal toxicity for males:
7439-92-1 lead (mass metal form)	
Chemicals known to cause development	tal toxicity:
7439-92-1 lead (mass metal form)	
EPA (Environmental Protection Agency)	
7439-92-1 lead (mass metal form)	E
7440-38-2 arsenic	Α
· IARC (International Agency for Research	on Cancer):
7439-92-1 lead (mass metal form)	2
7440-38-2 arsenic	1

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: August 04, 2020

Trade name: Lead Pb

(Cont'd. of page 9)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• Abbreviations and acronyms: ADR: European Agreement concerning the

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent OSHA: Occupational Safety & Health Administration Acute Tox. 3: Acute toxicity – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Carc. 1A: Carcinogenicity – Category 1A Carc. 2: Carcinogenicity – Category 2 Repr. 1A: Reproductive toxicity - Category 1A STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2 Sources Website, European Chemicals Agency (echa.europa.eu) Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/ overview/home.do) Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org) Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6 Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5. Safety Data Sheets, Individual Manufacturers SDS Prepared by: ChemTel 1305 North Florida Avenue Tampa, Florida USA 33602-2902 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtel.com