1 Identification
· Product identifier
 Trade name: Molybdenum Indicator Solvent Product code: MO1591SS
 Recommended use and restriction on use Recommended use: Laboratory chemicals Restrictions on use: No relevant information available.
 Details of the supplier of the Safety Data Sheet Manufacturer/Supplier: AquaPhoenix Scientific, Inc. 860 Gitts Run Road Hanover, PA 17331 USA Tel +1 (717)632-1291 Toll-Free: (866)632-1291 info@aquaphoenixsci.com Distributor: AquaPhoenix Scientific 860 Gitts Run Road, Hanover, PA 17331 (717) 632-1291
• Emergency telephone number: ChemTel Inc. (800)255-3924 (North America) +1 (813)248-0585 (International)
2 Hazard(s) identification
2 Hazard(s) identification Classification of the substance or mixture
Classification of the substance or mixture Flam. Liq. 2 H225 Highly flammable liquid and vapor.
• Classification of the substance or mixture Flam. Liq. 2 H225 Highly flammable liquid and vapor. Acute Tox. 3 H301 Toxic if swallowed.
Classification of the substance or mixture Flam. Liq. 2 H225 Highly flammable liquid and vapor. Acute Tox. 3 H301 Toxic if swallowed. Acute Tox. 3 H311 Toxic in contact with skin.
Classification of the substance or mixture Flam. Liq. 2 H225 Highly flammable liquid and vapor. Acute Tox. 3 H301 Toxic if swallowed. Acute Tox. 3 H311 Toxic in contact with skin. Acute Tox. 3 H331 Toxic if inhaled.
Classification of the substance or mixtureFlam. Liq. 2H225Highly flammable liquid and vapor.Acute Tox. 3H301Toxic if swallowed.Acute Tox. 3H311Toxic in contact with skin.Acute Tox. 3H331Toxic if inhaled.Eye Irrit. 2AH319Causes serious eye irritation.
Classification of the substance or mixtureFlam. Liq. 2H225Highly flammable liquid and vapor.Acute Tox. 3H301Toxic if swallowed.Acute Tox. 3H311Toxic in contact with skin.Acute Tox. 3H331Toxic if inhaled.Eye Irrit. 2AH319Causes serious eye irritation.STOT SE 1H370Causes damage to the central nervous system and optic nerve.
Classification of the substance or mixtureFlam. Liq. 2H225Highly flammable liquid and vapor.Acute Tox. 3H301Toxic if swallowed.Acute Tox. 3H311Toxic in contact with skin.Acute Tox. 3H331Toxic if inhaled.Eye Irrit. 2AH319Causes serious eye irritation.
 Classification of the substance or mixture Flam. Liq. 2 H225 Highly flammable liquid and vapor. Acute Tox. 3 H301 Toxic if swallowed. Acute Tox. 3 H311 Toxic in contact with skin. Acute Tox. 3 H311 Toxic if inhaled. Eye Irrit. 2A H319 Causes serious eye irritation. STOT SE 1 H370 Causes damage to the central nervous system and optic nerve. Label elements GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
Classification of the substance or mixture Flam. Liq. 2 H225 Highly flammable liquid and vapor. Acute Tox. 3 H301 Toxic if swallowed. Acute Tox. 3 H311 Toxic in contact with skin. Acute Tox. 3 H311 Toxic if inhaled. Eye Irrit. 2A H319 Causes serious eye irritation. STOT SE 1 H370 Causes damage to the central nervous system and optic nerve. Label elements The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms: Image: CHS06 GHS07 GHS08 Signal word: Danger Hazard statements: H225 Highly flammable liquid and vapor.
 Classification of the substance or mixture Flam. Liq. 2 H225 Highly flammable liquid and vapor. Acute Tox. 3 H301 Toxic if swallowed. Acute Tox. 3 H311 Toxic in contact with skin. Acute Tox. 3 H311 Toxic if inhaled. Eye Irrit. 2A H319 Causes serious eye irritation. STOT SE 1 H370 Causes damage to the central nervous system and optic nerve. Label elements GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms: GHS02 GHS06 GHS07 GHS08 Signal word: Danger Hazard statements:

Revision: June 04, 2020

Trade name: Molybdenum Indicator Solvent

	(Cont'd. of page 1)
H370	Causes damage to the central nervous system and optic nerve.
 Precautionary s 	
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe mist/vapors/spray.
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	If swallowed: Immediately call a poison center/doctor.
P330	Rinse mouth.
P303+P361+P3	53 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P3	38 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing.
P308+P311	IF exposed or concerned: Call a poison center/doctor.
P337+P313	If eye irritation persists: Get medical advice/attention.
P361+P364	Take off immediately all contaminated clothing and wash it before reuse.
P370+P378	In case of fire: Use for extinction: Alcohol resistant foam or water spray.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
[.] Other hazards	s There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Components:			
67-56-1 methanol	40-60%		
 Flam. Liq. 2, H225 Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331 STOT SE 1, H370 Eye Irrit. 2B, H320 			
64-17-5 Ethanol	20-40%		
Flam. Liq. 2, H225 Eye Irrit. 2A, H319			
· Additional information:			

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret. For the wording of the listed Hazard Statements, refer to section 16.

4 First-aid measures

(Cont'd. on page 3)

Revision: June 04, 2020

	(Cont'd. of pa
Description of first aid measures	
General information: Immediately remove any clothing soiled by the prod	duct.
After inhalation:	
Supply fresh air.	
Provide oxygen treatment if affected person has difficulty breathing.	
If experiencing respiratory symptoms: Call a doctor.	
In case of unconsciousness place patient stably in side position for transp	ortation.
After skin contact:	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse s	skin with water/shower.
If skin irritation is experienced, consult a doctor.	
After eye contact:	
Remove contact lenses if worn.	
Rinse opened eye for several minutes under running water. Then consult	a doctor.
After swallowing:	
Rinse out mouth and then drink plenty of water.	
Do not induce vomiting; immediately call for medical help.	
Most important symptoms and effects, both acute and delayed:	
Breathing difficulty	
Coughing	
Causes eye irritation.	
Causes mild skin irritation.	
Gastric or intestinal disorders when ingested.	
Nausea in case of ingestion.	
Dizziness	
Acidosis	
Blindness	
Disorientation	
Unconsciousness	
Danger:	
May cause neurotoxic effects.	
Danger of impaired breathing. Toxic if swallowed, in contact with skin or if inhaled.	
Causes damage to the central nervous system and optic nerve.	
Indication of any immediate medical attention and special treatment	noodod:
Contains ethanediol. Consult literature for specific antidotes.	needed.
Medical supervision for at least 48 hours.	
If necessary oxygen respiration treatment.	
Later observation for pneumonia and pulmonary edema.	
If medical advice is needed, have product container or label at hand.	

- Extinguishing media
 Suitable extinguishing agents: Alcohol resistant foam Carbon dioxide
- Gaseous extinguishing agents Water fog / haze Water spray

(Cont'd. on page 4)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: June 04, 2020

ade name: Molybdenum Indicator Solvent	
	(Cont'd. of page
Fire-extinguishing powder	
For safety reasons unsuitable extinguishing agents: Water st	ream.
Special hazards arising from the substance or mixture	
Highly flammable liquid and vapor.	
Formation of toxic gases is possible during heating or in case of fi	re.
· Advice for firefighters	
· Protective equipment:	
Wear self-contained respiratory protective device.	
Wear fully protective suit.	
Additional information:	
Eliminate all ignition sources if safe to do so.	
Use large quantities of foam as it is partially destroyed by the proc	luct.
Cool endangered receptacles with water in flooding quantities.	
6 Accidental release measures	
Personal precautions, protective equipment and emerg	ency procedures
Isolate area and prevent access.	ency procedures
Isolate area and prevent access. Wear protective equipment. Keep unprotected persons away.	ency procedures
Isolate area and prevent access. Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation.	ency procedures
Isolate area and prevent access. Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation. Keep away from ignition sources.	
Isolate area and prevent access. Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation. Keep away from ignition sources. Use respiratory protective device against the effects of fumes/dus	
Isolate area and prevent access. Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation. Keep away from ignition sources. Use respiratory protective device against the effects of fumes/dus Protect from heat.	
Isolate area and prevent access. Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation. Keep away from ignition sources. Use respiratory protective device against the effects of fumes/dus Protect from heat. Environmental precautions	
Isolate area and prevent access. Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation. Keep away from ignition sources. Use respiratory protective device against the effects of fumes/dus Protect from heat. Environmental precautions Do not allow to enter sewers/ surface or ground water.	t/aerosol.
Isolate area and prevent access. Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation. Keep away from ignition sources. Use respiratory protective device against the effects of fumes/dus Protect from heat. Environmental precautions Do not allow to enter sewers/ surface or ground water. Inform respective authorities in case of seepage into water course	t/aerosol.
 Isolate area and prevent access. Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation. Keep away from ignition sources. Use respiratory protective device against the effects of fumes/dus Protect from heat. Environmental precautions Do not allow to enter sewers/ surface or ground water. Inform respective authorities in case of seepage into water course Methods and material for containment and cleaning up 	t/aerosol. e or sewage system.
 Isolate area and prevent access. Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation. Keep away from ignition sources. Use respiratory protective device against the effects of fumes/dus Protect from heat. Environmental precautions Do not allow to enter sewers/ surface or ground water. Inform respective authorities in case of seepage into water course Methods and material for containment and cleaning up Absorb with non-combustible liquid-binding material (sand, diatom) 	t/aerosol. e or sewage system.
 Isolate area and prevent access. Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation. Keep away from ignition sources. Use respiratory protective device against the effects of fumes/dus Protect from heat. Environmental precautions Do not allow to enter sewers/ surface or ground water. Inform respective authorities in case of seepage into water course Methods and material for containment and cleaning up Absorb with non-combustible liquid-binding material (sand, diatom Send for recovery or disposal in suitable receptacles. 	t/aerosol. e or sewage system.
 Isolate area and prevent access. Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation. Keep away from ignition sources. Use respiratory protective device against the effects of fumes/dus Protect from heat. Environmental precautions Do not allow to enter sewers/ surface or ground water. Inform respective authorities in case of seepage into water course Methods and material for containment and cleaning up Absorb with non-combustible liquid-binding material (sand, diatom Send for recovery or disposal in suitable receptacles. Reference to other sections 	t/aerosol. e or sewage system.
 Isolate area and prevent access. Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation. Keep away from ignition sources. Use respiratory protective device against the effects of fumes/dus Protect from heat. Environmental precautions Do not allow to enter sewers/ surface or ground water. Inform respective authorities in case of seepage into water course Methods and material for containment and cleaning up Absorb with non-combustible liquid-binding material (sand, diatom Send for recovery or disposal in suitable receptacles. Reference to other sections See Section 7 for information on safe handling. 	t/aerosol. e or sewage system.
 Isolate area and prevent access. Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation. Keep away from ignition sources. Use respiratory protective device against the effects of fumes/dus Protect from heat. Environmental precautions Do not allow to enter sewers/ surface or ground water. Inform respective authorities in case of seepage into water course Methods and material for containment and cleaning up Absorb with non-combustible liquid-binding material (sand, diatom Send for recovery or disposal in suitable receptacles. Reference to other sections 	t/aerosol. e or sewage system.

[.] Handling


Precautions for safe handling: Prevent formation of aerosols. Avoid splashes or spray in enclosed areas. Use only in well ventilated areas.
Information about protection against explosions and fires: Highly flammable liquid and vapor. Keep ignition sources away - Do not smoke. Protect from heat. Protect against electrostatic charges. Flammable gas-air mixtures may be formed in empty containers/receptacles.

[•] Conditions for safe storage, including any incompatibilities

(Cont'd. on page 5)

		(Cont'd. of pag
Information a	s to be met by storerooms and receptacles: Store in a cool location. bout storage in one common storage facility:	Contra. of pag
Store away fro		
	m oxidizing agents. nation about storage conditions:	
	rs tightly sealed.	
This product is		
[·] Specific end	luse(s) No relevant information available.	
BExposure o	controls/personal protection	
· Control para	ameters	
· Components	with limit values that require monitoring at the workplace:	
67-56-1 meth	anol	
PEL (USA)	Long-term value: 260 mg/m³, 200 ppm	
REL (USA)	Short-term value: 325 mg/m³, 250 ppm	
	Long-term value: 260 mg/m³, 200 ppm Skin	
TLV (USA)	Short-term value: 328 mg/m³, 250 ppm	
	Long-term value: 262 mg/m³, 200 ppm Skin; BEI	
EL (Canada)	Short-term value: 250 ppm	
	Long-term value: 200 ppm Skin	
EV (Canada)	Short-term value: 325 mg/m³, 250 ppm Long-term value: 260 mg/m³, 200 ppm	
	Skin	
LMPE (Mexico) Short-term value: 250 ppm Long-term value: 200 ppm	
	PIEL, IBE	
64-17-5 Ethar		
PEL (USA)	Long-term value: 1900 mg/m³, 1000 ppm	
REL (USA)	Long-term value: 1900 mg/m³, 1000 ppm	
TLV (USA)	Short-term value: 1880 mg/m³, 1000 ppm	
EL (Canada)	Short-term value: 1000 ppm	
EV (Canada)	Long-term value: 1,900 mg/m³, 1,000 ppm	
· · /) Long-term value: 1000 ppm	
	A3	
-	ith biological limit values:	
67-56-1 meth		
BEI (USA) 15		
	edium: urine	
	ne: end of shift rameter: Methanol (background, nonspecific)	
· Exposure co	ontrols	(Cont'd. on pag

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations



Form:	Liquid	
Color:	Colorless	
Odor:	Alcohol-like	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Melting point/Melting range:	Not determined.	
Boiling point/Boiling range:	<100 °C (<212 °F)	
Flash point:	11-13 °C (51.88.6 °F)	
Flammability (solid, gaseous):	Not applicable.	
Auto-ignition temperature:	>260 °C (>500 °F)	

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: June 04, 2020

Trade name: Molybdenum Indicator Solvent

	(Cont'd. of page
· Decomposition temperature:	Not determined.
[.] Danger of explosion:	Product is not explosive. However, formation of explosive air vapor mixtures are possible.
· Explosion limits	
Lower:	3 Vol %
Upper:	15 Vol %
Oxidizing properties:	Not determined.
· Vapor pressure at 20 °C (68 °F):	>50 hPa (>37.5 mm Hg)
· Density:	
Relative density:	Not determined.
Vapor density:	Not determined.
Evaporation rate:	Not determined.
· Solubility in / Miscibility with	
Water:	Fully miscible.
· Partition coefficient (n-octanol/wat	er): Not determined.
· Viscosity	
Dynamic:	Not determined.
Kinematic:	Not determined.
[·] Other information	No relevant information available.

10 Stability and reactivity · Reactivity: No relevant information available. · Chemical stability: Stable under normal temperatures and pressures. Thermal decomposition / conditions to be avoided: No decomposition if used and stored according to specifications. Possibility of hazardous reactions Highly flammable liquid and vapor. Reacts violently with oxidizing agents. Reacts with strong acids. Toxic fumes may be released if heated above the decomposition point. Used empty containers may contain product gases which form explosive mixtures with air. Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized. Conditions to avoid Keep ignition sources away - Do not smoke. Store away from oxidizing agents. · Incompatible materials No relevant information available. · Hazardous decomposition products Under fire conditions only:

Carbon monoxide and carbon dioxide

11 Toxicological information

(Cont'd. on page 8)

Revision: June 04, 2020

			(Cont'd. of page
· Informati	on on te	oxicological effects	
· Acute toxi			
· LD/LC50 v	alues th	at are relevant for classification:	
ATE (Acut	e Toxicit	ty Estimate)	
Oral	LD50	100-200 mg/kg	
Dermal	LD50	400-600 mg/kg	
Inhalative	LC50/4h	3.5-6.5 mg/l	
Primary in		ect:	
On the ski		14 - 41	
Causes mi Based on a		data, the classification criteria are not met.	
· On the eye			
		ed on available data, the classification criteria are not met.	
· IARC (Inte	rnationa	I Agency for Research on Cancer):	
64-17-5 Et	thanol		
NTP (Natio	onal Tox	icology Program):	
None of the	e ingredie	ents are listed.	
· OSHA-Ca	(Occupa	tional Safety & Health Administration):	
None of the	e ingredie	ents are listed.	
	oute(s)	of exposure:	
Ingestion.			
Inhalation. Eye contac	٠t		
Skin conta			
		te toxicity, irritation and corrosivity):	
		in contact with skin or if inhaled.	
		the central nervous system and optic nerve.	
Irritating to Causes mi		itation	
-		kicity: No relevant information available.	
		icity: Based on available data, the classification criteria are not met.	
		ased on available data, the classification criteria are not met.	
		city: Based on available data, the classification criteria are not met.	
		sure: Causes damage to the central nervous system and optic nerve.	
		posure: Based on available data, the classification criteria are not met.	
• Aspiration	nazaro:	Based on available data, the classification criteria are not met.	

· Aquatic toxicity No relevant information available.

· Persistence and degradability No relevant information available.

- · Bioaccumulative potential: No relevant information available.
- Mobility in soil: No relevant information available.
- [•] Additional ecological information

(Cont'd. on page 9)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: June 04, 2020

Trade name: Molybdenum Indicator Solvent

(Cont'd. of page 8)

• General notes: Do not allow product to reach ground water, water course or sewage system. • Other adverse effects No relevant information available.

13 Disposal considerations

[•] Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Incinerate in accordance with local, state and federal regulations.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

[·] Uncleaned packagings

• Recommendation: Disposal must be made according to official regulations.

Transport information	
UN-Number DOT, ADR/RID/ADN, IMDG, IATA	UN1986
UN proper shipping name DOT, ADR/RID/ADN, IMDG, IATA	ALCOHOLS, FLAMMABLE, TOXIC, N.O. (ETHANOL (ETHYL ALCOHOL), METHANOL)
Transport hazard class(es)	
DOT	
Class	3
Label	3, 6.1
ADR/RID/ADN	
Class	3 (FT1)
Label	3, 6.1
IMDG	
Class	3
Label	3/6.1

Trade name: Molybdenum Indicator Solvent		
	(Cont'd. of page 9)	
· Class · Label	3 3 (6.1)	
 Packing group DOT, ADR/RID/ADN, IMDG, IATA 	II	
· Environmental hazards	Not applicable.	
 Special precautions for user Hazard identification number (Kemler code): EMS Number: 	Warning: Flammable liquids 336 F-E,S-D	
 Transport in bulk according to Annex II o MARPOL73/78 and the IBC Code 	f Not applicable.	
 Safety, health and environmental regula mixture United States (USA) SARA 	ations/legislation specific for the substance or	
Section 302 (extremely hazardous substances None of the ingredients are listed.	s):	
Section 313 (Specific toxic chemical listings):		
67-56-1 methanol		
• TSCA (Toxic Substances Control Act)		
67-56-1 methanol		
64-17-5 Ethanol		
 Proposition 65 (California) Chemicals known to cause cancer: Ethanol - listing refers specifically to alcoholic bet 	verage consumption and is not applicable for product.	
64-17-5 Ethanol		
Chemicals known to cause developmental to:	xicity for females:	
None of the ingredients are listed.		
Chemicals known to cause developmental to:	xicity for males:	
None of the ingredients are listed. Chemicals known to cause developmental to:	xicity	
Ethanol - listing refers specifically to alcoholic be	verage consumption and is not applicable for product.	
67-56-1 methanol		
64-17-5 Ethanol	(Cont'd. on page 11)	

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: June 04, 2020

Trade name: Molybdenum Indicator Solvent

(Cont'd. of page 10)

1

· EPA (Environmental Protection Agency):

None of the ingredients are listed.

IARC (International Agency for Research on Cancer):

64-17-5 Ethanol

Canadian Domestic Substances List (DSL):

None of the ingredients are listed.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent OSHA: Occupational Safety & Health Administration Flam. Liq. 2: Flammable liquids – Category 2 Acute Tox. 3: Acute toxicity - Category 3 Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A Eye Irrit. 2B: Serious eye damage/eye irritation - Category 2B STOT SE 1: Specific target organ toxicity (single exposure) - Category 1 Sources Website, European Chemicals Agency (echa.europa.eu) Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/ overview/home.do) Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org) Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6 Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5. Safety Data Sheets, Individual Manufacturers SDS Prepared by: ChemTel 1305 North Florida Avenue Tampa, Florida USA 33602-2902 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573 Website: www.chemtel.com