

Safety Data Sheet

PY1815SS

Version number: 1.4

Date of compilation: 2026-01-06

SECTION 1: Identification

1.1 Product identifier

Trade name

Polymer Buffer

SDS Identifier

PY1815SS

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

laboratory and analytical use

1.3 Details of the supplier of the safety data sheet

AquaPhoenix Scientific
860 Gitts Run Road
Hanover PA 17331
United States

Telephone: (866) 632-1291
e-mail: info@aquaphoenixsci.com
Website: <https://www.aquaphoenixsci.com/>

1.4 Emergency telephone number

Emergency information service

ChemTel Inc.: 1-800-255-3924, +01-813-248-0585

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200, Rev. 2024)

Hazard class	Category	Hazard class and category	Hazard statement
substance or mixture corrosive to metals	1	Met. Corr. 1	H290
skin corrosion/irritation	1B	Skin Corr. 1B	H314
serious eye damage/eye irritation	1	Eye Dam. 1	H318
specific target organ toxicity - repeated exposure	2	STOT RE 2	H373
hazardous to the aquatic environment - acute hazard	3	Aquatic Acute 3	H402

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Skin corrosion produces an irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis. Delayed or immediate effects can be expected after short or long-term exposure. Spillage and fire water can cause pollution of watercourses.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200, Rev. 2024)

- Signal word danger

- Pictograms

GHS05, GHS08



Safety Data Sheet

PY1815SS

Version number: 1.4

Date of compilation: 2026-01-06

- Hazard statements

H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H373	May cause damage to organs through prolonged or repeated exposure.
H402	Harmful to aquatic life.

- Precautionary statements

P234	Keep only in original packaging.
P260	Do not breathe dusts or mists.
P264+P265	Wash hands thoroughly after handling. Do not touch eyes.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P302+P361+P354	IF ON SKIN: Take off immediately all contaminated clothing. Immediately rinse with water for several minutes.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P354+P338	IF IN EYES: Immediately rinse with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P316	Get emergency medical help immediately.
P321	Specific treatment (see on this label).
P363	Wash contaminated clothing before reuse.
P390	Absorb spillage to prevent material-damage.
P405	Store locked up.
P406	Store in a corrosion resistant container with a resistant inner liner.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

- Hazardous ingredients for labelling

EDTA, Disodium Salt, Dihydrate, sodium hydroxide, Ethanolamine, 1L

2.3 Other hazards

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of $\geq 0.1\%$.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0.1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
Water	CAS No 7732-18-5	74.34		
EDTA, Disodium Salt, Dihydrate	CAS No 6381-92-6	13.96	Acute Tox. 5 / H303 Acute Tox. 4 / H332 STOT RE 2 / H373 Aquatic Acute 3 / H402	 
sodium citrate dihydrate	CAS No 6132-04-3	7.5	Acute Tox. 5 / H313	

Safety Data Sheet

PY1815SS

Version number: 1.4

Date of compilation: 2026-01-06

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
sodium hydroxide	CAS No 1310-73-2	2.7	Met. Corr. 1 / H290 Acute Tox. 4 / H302 Skin Corr. 1A / H314 Eye Dam. 1 / H318 Aquatic Acute 3 / H402	 
Ethanolamine, 1L	CAS No 141-43-5	1.5	Flam. Liq. 4 / H227 Acute Tox. 4 / H302 Acute Tox. 4 / H312 Acute Tox. 4 / H332 Skin Corr. 1B / H314 Eye Dam. 1 / H318 STOT SE 3 / H335 Aquatic Acute 2 / H401 Aquatic Chronic 3 / H412	 

Remarks

For full text of abbreviations: see SECTION 16

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

Medical attention may be necessary if the product gets into the eyes or on the skin.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO₂)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Substance or mixture corrosive to metals.

Safety Data Sheet

PY1815SS

Version number: 1.4

Date of compilation: 2026-01-06

Hazardous combustion products

Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

Wear impact- and splash-resistant eyewear.

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Corrosive conditions

Store in corrosive resistant container with a resistant inner liner.

Control of the effects

Safety Data Sheet

PY1815SS

Version number: 1.4

Date of compilation: 2026-01-06

Protect against external exposure, such as
heat, high temperatures, light, UV-radiation/sunlight

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m³]	STEL [ppm]	STEL [mg/m³]	Ceiling-C [ppm]	Ceiling-C [mg/m³]	Notation	Source
US	sodium hydroxide	1310-73-2	REL						2		NIOSH REL
US	sodium hydroxide	1310-73-2	TLV®						2		ACGIH® 2024
US	sodium hydroxide	1310-73-2	PEL		2						29 CFR 1910.10 00
US	sodium hydroxide (caustic soda)	1310-73-2	PEL (CA)						2		Cal/OSHA PEL
US	ethanolamine	141-43-5	REL	3 (10 h)	8 (10 h)	6	15				NIOSH REL
US	ethanolamine	141-43-5	TLV®	3		6					ACGIH® 2024
US	ethanolamine	141-43-5	PEL	3	6						29 CFR 1910.10 00
US	ethanolamine (2-aminoethanol)	141-43-5	PEL (CA)	3	8	6	15				Cal/OSHA PEL

Notation

Ceiling-C ceiling value is a limit value above which exposure should not occur

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Relevant DNELs of components						
Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
EDTA, Disodium Salt, Dihydrate	6381-92-6	DNEL	1.5 mg/m³	human, inhalatory	worker (industry)	chronic - systemic effects
EDTA, Disodium Salt, Dihydrate	6381-92-6	DNEL	3 mg/m³	human, inhalatory	worker (industry)	acute - systemic effects
EDTA, Disodium Salt, Dihydrate	6381-92-6	DNEL	1.5 mg/m³	human, inhalatory	worker (industry)	chronic - local effects
EDTA, Disodium Salt, Dihydrate	6381-92-6	DNEL	3 mg/m³	human, inhalatory	worker (industry)	acute - local effects
Ethanolamine, 1L	141-43-5	DNEL	1 mg/m³	human, inhalatory	worker (industry)	chronic - systemic effects

Safety Data Sheet

PY1815SS

Version number: 1.4

Date of compilation: 2026-01-06

Relevant DNELs of components						
Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
						facts
Ethanolamine, 1L	141-43-5	DNEL	0.51 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
Ethanolamine, 1L	141-43-5	DNEL	3 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Relevant PNECs of components						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
EDTA, Disodium Salt, Dihydrate	6381-92-6	PNEC	2.5 mg/l	aquatic organisms	freshwater	short-term (single instance)
EDTA, Disodium Salt, Dihydrate	6381-92-6	PNEC	0.25 mg/l	aquatic organisms	marine water	short-term (single instance)
EDTA, Disodium Salt, Dihydrate	6381-92-6	PNEC	50 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
EDTA, Disodium Salt, Dihydrate	6381-92-6	PNEC	1.1 mg/kg	terrestrial organisms	soil	short-term (single instance)
Ethanolamine, 1L	141-43-5	PNEC	0.07 mg/l	aquatic organisms	freshwater	short-term (single instance)
Ethanolamine, 1L	141-43-5	PNEC	0.007 mg/l	aquatic organisms	marine water	short-term (single instance)
Ethanolamine, 1L	141-43-5	PNEC	100 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Ethanolamine, 1L	141-43-5	PNEC	0.357 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Ethanolamine, 1L	141-43-5	PNEC	0.036 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Ethanolamine, 1L	141-43-5	PNEC	1.29 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Recommended: Disposable neoprene gloves, 0.1 - 0.2 mm thick, 15-120 minute breakthrough times. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Wash hands thoroughly after handling.

Safety Data Sheet

PY1815SS

Version number: 1.4

Date of compilation: 2026-01-06

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Product description: See website or catalog for details.

Physical state	liquid
Color	colorless - clear
Odor	odorless
Melting point/freezing point	0 °C at 1 atm
Boiling point or initial boiling point and boiling range	100 °C at 1 atm
Evaporation rate	not determined
Flammability	this material is combustible, but will not ignite readily
Lower and upper explosion limit	not determined
Flash point	not determined
Auto-ignition temperature	424 °C (auto-ignition temperature (liquids and gases))
Decomposition temperature	not relevant
pH (value)	10.8
Kinematic viscosity	not determined
Solubility(ies)	not determined

Partition coefficient

Partition coefficient n-octanol/water (log value)	this information is not available
---	-----------------------------------

Vapor pressure	23 hPa at 20 °C
----------------	-----------------

Density and/or relative density

Density	not determined
Relative vapour density	information on this property is not available

Safety Data Sheet

PY1815SS

Version number: 1.4

Date of compilation: 2026-01-06

Particle characteristics

not relevant (liquid)

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". Substance or mixture corrosive to metals.

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200, Rev. 2024)

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components

Name of substance	CAS No	Exposure route	ATE
EDTA, Disodium Salt, Dihydrate	6381-92-6	oral	2,800 mg/kg
EDTA, Disodium Salt, Dihydrate	6381-92-6	inhalation: dust/mist	1.5 mg/l/4h
sodium citrate dihydrate	6132-04-3	dermal	>2,000 mg/kg
sodium hydroxide	1310-73-2	oral	325 mg/kg
Ethanolamine, 1L	141-43-5	oral	1,089 mg/kg
Ethanolamine, 1L	141-43-5	dermal	1,100 mg/kg
Ethanolamine, 1L	141-43-5	inhalation: vapor	11 mg/l/4h

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Safety Data Sheet

PY1815SS

Version number: 1.4

Date of compilation: 2026-01-06

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

11.2 Information on other hazards

There is no additional information.

SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life.

Aquatic toxicity (acute) of components

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
EDTA, Disodium Salt, Dihydrate	6381-92-6	LC50	>116 mg/l	fish	96 h
EDTA, Disodium Salt, Dihydrate	6381-92-6	EC50	>114 mg/l	aquatic invertebrates	48 h
EDTA, Disodium Salt, Dihydrate	6381-92-6	ErC50	>60 mg/l	algae	72 h
sodium citrate dihydrate	6132-04-3	LC50	18,000 – 32,000 mg/l	guppy (Poecilia reticulata)	96 h
sodium citrate dihydrate	6132-04-3	EC50	5,600 – 10,000 mg/l	water flea (Daphnia)	48 h
sodium hydroxide	1310-73-2	LC50	<180 mg/l	fish	96 h
sodium hydroxide	1310-73-2	EC50	40.4 mg/l	aquatic invertebrates	48 h
Ethanolamine, 1L	141-43-5	LC50	349 mg/l	fish	96 h
Ethanolamine, 1L	141-43-5	EC50	27.04 mg/l	aquatic invertebrates	48 h
Ethanolamine, 1L	141-43-5	ErC50	2.8 mg/l	algae	72 h

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

Safety Data Sheet

PY1815SS

Version number: 1.4

Date of compilation: 2026-01-06

12.5 Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of $\geq 0.1\%$.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0.1\%$.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Please consider the relevant national or regional provisions.

SECTION 14: Transport information

14.1 UN number

DOT	UN 1760
IMDG-Code	UN 1760
ICAO-TI	UN 1760

14.2 UN proper shipping name

DOT	Corrosive liquid, n.o.s.
IMDG-Code	CORROSIVE LIQUID, N.O.S.
ICAO-TI	Corrosive liquid, n.o.s.
Technical name (hazardous ingredients)	sodium hydroxide, Ethanolamine, 1L

14.3 Transport hazard class(es)

DOT	8
IMDG-Code	8
ICAO-TI	8

14.4 Packing group

DOT	III
IMDG-Code	III
ICAO-TI	III

14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations

14.6 Other relevant information

Shipping container markings and labels, received from AquaPhoenix, may vary from the above information. Products that are regulated for transport will be packaged by AquaPhoenix as Dangerous Goods in Excepted Quantities according to IATA, US DOT, and IMDG regulations. AquaPhoenix may also elect to ship certain products as UN 3316 Chemical Kit, Hazard Class 9, Packing Group II or III. In case of reshipment, it is the responsibility of the shipper to determine appropriate labels and markings in accordance with applicable transportation regulations.

14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Safety Data Sheet

PY1815SS

Version number: 1.4

Date of compilation: 2026-01-06

Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Particulars in the shipper's declaration	UN1760, Corrosive liquid, n.o.s., (sodium hydroxide, Ethanolamine, 1L, mixture), 8, III
Reportable quantity (RQ)	37,037 lbs (16,815 kg) (sodium hydroxide)
Danger label(s)	8



Special provisions (SP)	IB3, T7, TP1, TP28
ERG No	154

International Maritime Dangerous Goods Code (IMDG) - Additional information

Marine pollutant	-
Danger label(s)	8



Special provisions (SP)	223, 274
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
EmS	F-A, S-B
Stowage category	A

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Danger label(s)	8
-----------------	---



Special provisions (SP)	A3
Excepted quantities (EQ)	E1
Limited quantities (LQ)	1 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Toxic Substance Control Act (TSCA) not all ingredients are listed (ACTIVE)

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

- Specific Toxic Chemical Listings (EPCRA Section 313)

none of the ingredients are listed

Safety Data Sheet

PY1815SS

Version number: 1.4

Date of compilation: 2026-01-06

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
sodium hydroxide	1310-73-2		1	1000 (454)

Legend

1 "1" indicates that the statutory source is section 311(b)(2) of the Clean Water Act

Clean Air Act

none of the ingredients are listed

Right to Know Hazardous Substance List

- Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
sodium hydroxide	1310-73-2		CO R1
Ethanolamine, 1L	141-43-5		CO F2

Legend

CO Corrosive
F2 Flammable - Second Degree
R1 Reactive - First Degree

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

none of the ingredients are listed

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	3	major injury likely unless prompt action is taken and medical treatment is given
Flammability	1	material that must be preheated before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	1	material that must be preheated before ignition can occur

Safety Data Sheet

PY1815SS

Version number: 1.4

Date of compilation: 2026-01-06

Category	Degree of hazard	Description
Health	3	material that, under emergency conditions, can cause serious or permanent injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
AU	AIIC	all ingredients are listed
CA	DSL	not all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	not all ingredients are listed
EU	REACH Reg.	all ingredients are listed
JP	CSCL-ENCS	all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	not all ingredients are listed

Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

Safety Data Sheet

PY1815SS

Version number: 1.4

Date of compilation: 2026-01-06

SECTION 16: Other information, including date of preparation or last revision

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH® 2024	From ACGIH®, 2024 TLVs® and BEIs® Book. Copyright 2024. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement
Acute Tox.	Acute toxicity
Aquatic Acute	Hazardous to the aquatic environment - acute hazard
Aquatic Chronic	Hazardous to the aquatic environment - chronic hazard
ATE	Acute Toxicity Estimate
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
DOT	Department of Transportation (USA)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
ED	Endocrine disruptor
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
ERG No	Emergency Response Guidebook - Number
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval

Safety Data Sheet

PY1815SS

Version number: 1.4

Date of compilation: 2026-01-06

Abbr.	Descriptions of used abbreviations
Met. Corr.	Substance or mixture corrosive to metals
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NLP	No-Longer Polymer
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure
TLV®	Threshold Limit Values
TWA	Time-weighted average
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

Globally Harmonized System of Classification and Labelling of Chemicals ("Purple book").
 Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG).
 Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.
 Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H227	Combustible liquid.
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H303	May be harmful if swallowed.
H312	Harmful in contact with skin.
H313	May be harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.

Safety Data Sheet

PY1815SS

Version number: 1.4

Date of compilation: 2026-01-06

Code	Text
H373	May cause damage to organs through prolonged or repeated exposure.
H401	Toxic to aquatic life.
H402	Harmful to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.