

# Safety Data Sheet


according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: February 14, 2020

## 1 Identification

- **Product identifier**
- **Trade name:** Salting Out Density
- **Product code:** FEDSC1161-Q
- **Recommended use and restriction on use**
- **Recommended use:** Laboratory chemicals
- **Restrictions on use:** No relevant information available.
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**  
AquaPhoenix Scientific, Inc.  
860 Gitts Run Road  
Hanover, PA 17331  
Phone: (717)632-1291  
Toll-Free: (866)632-1291  
info@aquaphoenixsci.com
- **Distributor:**  
Fisher Science Education  
6771 Silver Crest Road,  
Nazareth, PA 18064  
(800) 955-1177
- **Emergency telephone number:**  
ChemTel Inc.  
(800)255-3924 (North America)  
+1 (813)248-0585 (International)

## 2 Hazard(s) identification

- **Classification of the substance or mixture**  
Flam. Liq. 2 H225 Highly flammable liquid and vapor.  
Eye Irrit. 2A H319 Causes serious eye irritation.  
STOT SE 3 H336 May cause drowsiness or dizziness.
- **Label elements**
- **GHS label elements**  
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms:**  

  
GHS02 GHS07
- **Signal word:** Danger
- **Hazard statements:**  
H225 Highly flammable liquid and vapor.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.
- **Precautionary statements:**  
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P233 Keep container tightly closed.

(Cont'd. on page 2)

# Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: February 14, 2020

**Trade name: Salting Out Density**

(Cont'd. of page 1)



P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing mist, vapors, or spray.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a poison center/doctor if you feel unwell.
P337+P313	If eye irritation persists: Get medical advice/attention.
P370+P378	In case of fire: Use for extinction: Alcohol resistant foam or water spray.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Other hazards** There are no other hazards not otherwise classified that have been identified.

## 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Components:**

67-63-0	Propan-2-ol  Flam. Liq. 2, H225  Eye Irrit. 2A, H319; STOT SE 3, H336	50%
7647-14-5	Sodium chloride	11.25%
7732-18-5	Water	38.75%

· **Additional information:**

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret.  
 For the wording of the listed Hazard Statements, refer to section 16.

## 4 First-aid measures

· **Description of first aid measures**

· **General information:** Immediately remove any clothing soiled by the product.

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:**

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 If skin irritation continues, consult a doctor.

· **After eye contact:**

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:**

(Cont'd. on page 3)

# Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: February 14, 2020

**Trade name: Salting Out Density**

(Cont'd. of page 2)

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

· **Most important symptoms and effects, both acute and delayed:**

Dizziness

Coughing

Causes eye irritation.

Gastric or intestinal disorders when ingested.

Nausea in case of ingestion.

Acidosis

· **Danger:** May cause drowsiness or dizziness.

· **Indication of any immediate medical attention and special treatment needed:**

If necessary oxygen respiration treatment.

If medical advice is needed, have product container or label at hand.

## 5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

Alcohol resistant foam

Carbon dioxide

Gaseous extinguishing agents

Water fog / haze

Fire-extinguishing powder

· **For safety reasons unsuitable extinguishing agents:** Water stream.

· **Special hazards arising from the substance or mixture**

Highly flammable liquid and vapor.

Formation of toxic gases is possible during heating or in case of fire.

· **Advice for firefighters**

· **Protective equipment:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

· **Additional information:**

Eliminate all ignition sources if safe to do so.

Use large quantities of foam as it is partially destroyed by the product.

## 6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Isolate area and prevent access.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

Keep away from ignition sources.

Protect from heat.

For large spills, use respiratory protective device against the effects of fumes/dust/aerosol.

· **Environmental precautions**

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· **Methods and material for containment and cleaning up**

(Cont'd. on page 4)

# Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: February 14, 2020

**Trade name: Salting Out Density**

(Cont'd. of page 3)

Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).  
Send for recovery or disposal in suitable receptacles.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and storage

· **Handling**

· **Precautions for safe handling:**

Prevent formation of aerosols.

Avoid splashes or spray in enclosed areas.

Use only in well ventilated areas.

· **Information about protection against explosions and fires:**

Highly flammable liquid and vapor.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Flammable gas-air mixtures may be formed in empty containers/receptacles.

· **Conditions for safe storage, including any incompatibilities**

· **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Avoid storage near extreme heat, ignition sources or open flame.

· **Information about storage in one common storage facility:**

Store away from foodstuffs.

Store away from oxidizing agents.

· **Further information about storage conditions:**

Keep containers tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· **Specific end use(s)** No relevant information available.

## 8 Exposure controls/personal protection

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

**67-63-0 Propan-2-ol**

PEL (USA)	Long-term value: 980 mg/m <sup>3</sup> , 400 ppm
REL (USA)	Short-term value: 1225 mg/m <sup>3</sup> , 500 ppm Long-term value: 980 mg/m <sup>3</sup> , 400 ppm
TLV (USA)	Short-term value: 984 mg/m <sup>3</sup> , 400 ppm Long-term value: 492 mg/m <sup>3</sup> , 200 ppm BEI
EL (Canada)	Short-term value: 400 ppm Long-term value: 200 ppm

(Cont'd. on page 5)

# Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: February 14, 2020

**Trade name: Salting Out Density**

(Cont'd. of page 4)

EV (Canada)	Short-term value: 400 ppm Long-term value: 200 ppm
LMPE (Mexico)	Short-term value: 400 ppm Long-term value: 200 ppm A4, IBE

· **Ingredients with biological limit values:**

**67-63-0 Propan-2-ol**

BEI (USA)	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)
-----------	---

· **Exposure controls**

· **General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.

· **Engineering controls:** Provide adequate ventilation.

· **Breathing equipment:** Suitable respiratory protective device recommended.

· **Protection of hands:**



Protective gloves

· **Material of gloves**

Nitrile rubber, NBR

Neoprene gloves

Butyl rubber, BR

Natural rubber, NR

Sensibilization by the components in the glove materials is possible.

· **Not suitable are gloves made of the following materials:** PVA gloves

· **Eye protection:**



Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear.

· **Body protection:** Protective work clothing

· **Limitation and supervision of exposure into the environment**

No relevant information available.

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **Appearance:**

<b>Form:</b>	Liquid
<b>Color:</b>	Colorless

(Cont'd. on page 6)

# Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: February 14, 2020

Trade name: Salting Out Density

(Cont'd. of page 5)

· <b>Odor:</b>	Alcohol-like
· <b>Odor threshold:</b>	Not determined.
· <b>pH-value:</b>	Not determined.
· <b>Melting point/Melting range:</b>	-19 °C (-66.2 °F)
· <b>Boiling point/Boiling range:</b>	>78 °C (>172.4 °F)
· <b>Flash point:</b>	17-19 °C (62.6-66.2 °F)
· <b>Flammability (solid, gaseous):</b>	Not applicable.
· <b>Auto-ignition temperature:</b>	>260 °C (>500 °F)
· <b>Decomposition temperature:</b>	Not determined.
· <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· <b>Explosion limits</b>	
<b>Lower:</b>	2 Vol %
<b>Upper:</b>	12 Vol %
· <b>Oxidizing properties:</b>	Non-oxidizing.
· <b>Vapor pressure:</b>	Not determined.
· <b>Density at 20 °C (68 °F):</b>	0.90-1.00 g/cm <sup>3</sup> (7.51-8.35 lbs/gal)
· <b>Relative density:</b>	Not determined.
· <b>Vapor density:</b>	Not determined.
· <b>Evaporation rate:</b>	Not determined.
· <b>Solubility in / Miscibility with Water:</b>	Fully miscible.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Other information</b>	No relevant information available.

## 10 Stability and reactivity

- **Reactivity:** No relevant information available.
- **Chemical stability:** Stable under normal temperatures and pressures.
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions**  
Reacts with oxidizing agents.  
Used empty containers may contain product gases which form explosive mixtures with air.  
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.  
Highly flammable liquid and vapor.  
Toxic fumes may be released if heated above the decomposition point.
- **Conditions to avoid**  
Keep ignition sources away - Do not smoke.

(Cont'd. on page 7)

# Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: February 14, 2020

**Trade name: Salting Out Density**

(Cont'd. of page 6)

Store away from oxidizing agents.

· **Incompatible materials** Oxidizing agents.

· **Hazardous decomposition products**

Under fire conditions only:

Carbon monoxide and carbon dioxide

## 11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity:** Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

**ATE (Acute Toxicity Estimate)**

Inhalative	LC50/4h	60 mg/l (rat)
------------	---------	---------------

**67-63-0 Propan-2-ol**

Oral	LD50	5045 mg/kg (rat)
------	------	------------------

Dermal	LD50	12800 mg/kg (rabbit)
--------	------	----------------------

Inhalative	LC50/4h	30 mg/l (rat)
------------	---------	---------------

· **Primary irritant effect:**

· **On the skin:** Based on available data, the classification criteria are not met.

· **On the eye:** Causes eye irritation.

· **Sensitization:** Based on available data, the classification criteria are not met.

· **IARC (International Agency for Research on Cancer):**

67-63-0	Propan-2-ol	3
---------	-------------	---

· **NTP (National Toxicology Program):**

None of the ingredients are listed.

· **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

· **Probable route(s) of exposure:**

Ingestion.

Inhalation.

Eye contact.

Skin contact.

· **Acute effects (acute toxicity, irritation and corrosivity):**

Causes eye irritation.

Vapors have narcotic effect.

· **Repeated dose toxicity:** No relevant information available.

· **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.

· **Carcinogenicity:** Based on available data, the classification criteria are not met.

· **Reproductive toxicity:** Based on available data, the classification criteria are not met.

· **STOT-single exposure:** May cause drowsiness or dizziness.

· **STOT-repeated exposure:** Based on available data, the classification criteria are not met.

· **Aspiration hazard:** Based on available data, the classification criteria are not met.

## 12 Ecological information

(Cont'd. on page 8)

# Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: February 14, 2020

Trade name: Salting Out Density



(Cont'd. of page 7)

- **Toxicity**
- **Aquatic toxicity** No relevant information available.
- **Persistence and degradability** No relevant information available.
- **Bioaccumulative potential:** No relevant information available.
- **Mobility in soil:** No relevant information available.
- **Additional ecological information**
- **General notes:**  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Other adverse effects** No relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.
- **Uncleaned packagings**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

## 14 Transport information

- |   |  |
|---|--|
| · <b>UN-Number</b>  |  |
| · <b>DOT, ADR/RID/ADN, IMDG, IATA</b>   | UN1219                                   |
| · <b>UN proper shipping name</b>  |  |
| · <b>DOT</b>  | Isopropanol solution                     |
| · <b>ADR/RID/ADN, IMDG, IATA</b>  | ISOPROPANOL (ISOPROPYL ALCOHOL) solution |
| · <b>Transport hazard class(es)</b>   |  |
| · <b>DOT</b>  |  |
|  |  |
| · <b>Class</b>  | 3  |
| · <b>Label</b>  | 3  |
| -----   |  |
| · <b>ADR/RID/ADN</b>  |  |
|  |  |
| · <b>Class</b>  | 3 (F1)                                   |
| · <b>Label</b>  | 3  |

(Cont'd. on page 9)



# Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: February 14, 2020

Trade name: Salting Out Density

(Cont'd. of page 8)

· **IMDG, IATA**



· **Class** 3  
· **Label** 3

· **Packing group**  
· **DOT, ADR/RID/ADN, IMDG, IATA** II

· **Environmental hazards** Not applicable.

· **Special precautions for user** Warning: Flammable liquids  
· **Hazard identification number (Kemler code):** 33  
· **EMS Number:** F-E,S-D

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

## 15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**  
· **United States (USA)**  
· **SARA**

· **Section 302 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

67-63-0 | Propan-2-ol

· **TSCA (Toxic Substances Control Act)**

All ingredients are listed or exempt.

· **Proposition 65 (California)**

· **Chemicals known to cause cancer:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity for females:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity for males:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

· **EPA (Environmental Protection Agency):**

None of the ingredients are listed.

· **IARC (International Agency for Research on Cancer):**

(Cont'd. on page 10)

# Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: February 14, 2020

**Trade name: Salting Out Density**

(Cont'd. of page 9)

67-63-0 Propan-2-ol

3

**Canadian Domestic Substances List (DSL):**

All ingredients listed on DSL or NDSL.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Abbreviations and acronyms:**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

OSHA: Occupational Safety & Health Administration

Flam. Liq. 2: Flammable liquids – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

**Sources**

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com