

SAFETY DATA SHEET

1. Identification

| Product identifier | WATERMARK® KARL FISCHER COULOMETRIC GENERATOR SOLUTION, UNIVERSAL |
|---------------------------------|---|
| Other means of identification | |
| Product code | 2321 |
| Recommended use | Laboratory reagent for water determination using the Karl Fischer method. |
| Recommended restrictions | None known. |
| Manufacturer/Importer/Supp | blier/Distributor information |
| Manufacturer | |

| Company name Address | GFS Chemicals, Inc. P.O. Box 245 Powell, OH 43065 United States | |
|---------------------------|--|--|
| Telephone | Phone Toll Free Fax | 740-881-5501 800-858-9682 740-881-5989 |
| Website E-mail | www.gfschemicals.com service@gfschemicals.com | |
| Emergency phone number | Emergency Assistance | Chemtrec 800-424-9300 |

2. Hazard(s) identification

| Physical hazards | Flammable liquids | Category 3 |
|-----------------------|---|------------|
| Health hazards | Acute toxicity, dermal | Category 4 |
| | Skin corrosion/irritation | Category 2 |
| | Serious eye damage/eye irritation | Category 2 |
| | Sensitization, skin | Category 1 |
| | Carcinogenicity | Category 2 |
| | Reproductive toxicity | Category 1 |
| | Specific target organ toxicity, repeated exposure | Category 1 |
| Environmental hazards | Hazardous to the aquatic environment, acute hazard | Category 3 |
| | Hazardous to the aquatic environment, long-term hazard | Category 3 |
| OSHA defined hazards | Not classified. | |

Label elements



Danger

Hazard statement

Signal word

Flammable liquid and vapor. Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Suspected of causing cancer. May damage fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects.

Precautionary statement Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Avoid release to the environment. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.

| Response | IF ON SKIN: Wash with plenty of soap and water. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a POISON CENTER/doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish. | | | |
|--|--|--|--|--|
| Storage | Keep container tightly closed. Store in a well-ventilated place. Keep cool. | | | |
| Disposal | Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal. | | | |
| Hazard(s) not otherwise classified (HNOC) | None known. | | | |
| Supplemental information | 1-3% of the mixture consists of component(s) of unknown acute oral toxicity. 10-20% of the mixture consists of component(s) of unknown acute dermal toxicity. 10-20% of the mixture consists of component(s) of unknown acute inhalation toxicity. 80-90% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 80-90% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment. | | | |

3. Composition/information on ingredients

| Chemical name | Common name and synonyms | CAS number | % |
|-----------------------------------|---|------------|------------|
| ETHYLENEGLYCOLMONOMETHYL ETHER | Methyl Cellosolve Ethylene Glycol Monomethyl Ether 2-Methoxyethanol | 109-86-4 | 80 - < 90* |
| DIETHANOLAMINE | BIS(2-HYDROXYETHYL)AMINE | 111-42-2 | 10 - < 20* |
| IODINE | | 7553-56-2 | 1 - < 3* |
| SULFUR DIOXIDE | | 7446-09-5 | 1 - < 3* |

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

| 4. First-aid measures | | | | |
|--|--|--|--|--|
| Inhalation | Move to fresh air. Call a physician if symptoms develop or persist. | | | |
| Skin contact | Remove contaminated clothing immediately and wash skin with soap and water. Get medical advice/attention if you feel unwell. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse. | | | |
| Eye contact | Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. | | | |
| Ingestion | Rinse mouth. Get medical advice/attention if you feel unwell. | | | |
| Most important symptoms/effects, acute and delayed | Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects. | | | |
| Indication of immediate medical attention and special treatment needed | Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed. | | | |
| General information | Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse. | | | |
| 5. Fire-fighting measures | | | | |
| Suitable extinguishing media | Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2). | | | |
| Uncuitable extinguishing | Do not use water let as an extinguisher, as this will spread the fire | | | |

| Suitable extinguishing media | Water rog. Alcohol resistant roam. Dry chemical powder. Carbon dioxide (CO2). |
|---|--|
| Unsuitable extinguishing media | Do not use water jet as an extinguisher, as this will spread the fire. |
| Specific hazards arising from the chemical | Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed. |
| Special protective equipment and precautions for firefighters | Self-contained breathing apparatus and full protective clothing must be worn in case of fire. |
| Fire fighting equipment/instructions | In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. |
| Specific methods | Use standard firefighting procedures and consider the hazards of other involved materials. |
| | |

General fire hazards Flammable liquid and vapor.

6. Accidental release measures

| Personal precautions, protective equipment and emergency procedures | Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. |
|---|--|
| Methods and materials for containment and cleaning up | Use water spray to reduce vapors or divert vapor cloud drift. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. This product is miscible in water. Prevent product from entering drains. |
| | Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water. |
| | Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. |
| | Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS. |
| Environmental precautions | Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. |
| 7. Handling and storage | |
| Precautions for safe handling | Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices. |
| Conditions for safe storage, including any incompatibilities | Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS). |

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

| US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) | | | | | |
|---|---------|----------|-------------------------------|--|--|
| Components | Туре | Value | Value | | |
| ETHYLENEGLYCOLMONOME THYL ETHER (CAS 109-86-4) | PEL | 80 mg/m3 | | | |
| | | 25 ppm | | | |
| IODINE (CAS 7553-56-2) | Ceiling | 1 mg/m3 | | | |
| | | 0.1 ppm | | | |
| SULFUR DIOXIDE (CAS 7446-09-5) | PEL | 13 mg/m3 | | | |
| | | 5 ppm | | | |
| US. ACGIH Threshold Limit Value | S | | | | |
| Components | Туре | Value | Form | | |
| DIETHANOLAMINE (CAS 111-42-2) | TWA | 1 mg/m3 | Inhalable fraction and vapor. | | |
| ETHYLENEGLYCOLMONOME THYL ETHER (CAS 109-86-4) | TWA | 0.1 ppm | | | |
| SULFUR DIOXIDE (CAS 7446-09-5) | STEL | 0.25 ppm | | | |

US. NIOSH: Pocket Guide to Chemical Hazards Components Type

| Components | Туре | Value |
|----------------------------------|---------|-----------|
| DIETHANOLAMINE (CAS 111-42-2) | TWA | 15 mg/m3 |
| | | 3 ppm |
| ETHYLENEGLYCOLMONOME | TWA | 0.3 mg/m3 |
| THYL ETHER (CAS 109-86-4) | | - |
| | | 0.1 ppm |
| IODINE (CAS 7553-56-2) | Ceiling | 1 mg/m3 |
| | - | 0.1 ppm |
| SULFUR DIOXIDE (CAS | STEL | 13 mg/m3 |
| 7446-09-5) | | 5. |
| | | 5 ppm |
| | TWA | 5 mg/m3 |
| | | 2 ppm |

Biological limit values

| US. ACGIH. BEIs. Biologic Components | al Exposure Indices /alue | Determinant | Specimen | Sampling Time | |
|---|---|---|--|--|--|
| ETHYLENEGLYCOLMONOME THYL ETHER (CAS 109-86-4) | 1 mg/g | 2-Methoxyaceti c acid | Creatinine in urine | * | |
| * - For sampling details, plea | se see the source docu | ument. | | | |
| Exposure guidelines | | | | | |
| US - Tennessee OELs: Ski ETHYLENEGLYCOLMONO US ACGIH Threshold Limi | n designation)METHYL ETHER (CAS t Values: Skin desig | 109-86-4) Can be nation | absorbed throug | gh the skin. | |
| DIETHANOLAMINE (CAS ETHYLENEGLYCOLMONO US. California Code of Re g | 111-42-2) METHYL ETHER (CAS gulations, Title 8, Se | Can be 109-86-4) Can be ection 5155. Airbo | absorbed throug absorbed throug | gh the skin. gh the skin. ants | |
| DIETHANOLAMINE (CAS ETHYLENEGLYCOLMONO US. Minnesota Hazardous | 111-42-2) METHYL ETHER (CAS Substances List (M | Can be 109-86-4) Can be inn. Rules 5206.0 | absorbed throug absorbed throug 400). | gh the skin. gh the skin. | |
| ETHYLENEGLYCOLMONC US. NIOSH: Pocket Guide | METHYL ETHER (CAS to Chemical Hazard | 109-86-4) Skin de s | signation applies | 5. | |
| ETHYLENEGLYCOLMONC US. OSHA Table Z-1 Limit | METHYL ETHER (CAS s for Air Contaminar | 109-86-4) Can be nts (29 CFR 1910 | absorbed throug 1000) | gh the skin. | |
| ETHYLENEGLYCOLMONC | METHYL ETHER (CAS | 109-86-4) Can be | absorbed throug | gh the skin. | |
| Appropriate engineering controls | Explosion-proof gen changes per hour) s use process enclosu levels below recomm airborne levels to an showers are recomm | ieral and local exha should be used. Ver ires, local exhaust v mended exposure lii n acceptable level. F mended. | ust ventilation. G ntilation rates sho rentilation, or oth mits. If exposure Provide eyewash | Good general ventilation (typically 10 air buld be matched to conditions. If applicable, her engineering controls to maintain airborne e limits have not been established, maintain station. Eye wash fountain and emergency | |
| Individual protection measure Eye/face protection | es, such as personal Wear safety glasses | protective equip with side shields (o | ment or goggles). Eye | wash fountains are required. | |
| Skin protection | | | | | |
| Hand protection | Wear appropriate cl | nemical resistant glo | oves. | | |
| Other | Wear appropriate cl | Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. | | | |
| Respiratory protection | If engineering contr limits (where applic been established), a cartridge. | ols do not maintain able) or to an accer an approved respira | airborne concer otable level (in co tor must be wor | ntrations below recommended exposure buntries where exposure limits have not n. Chemical respirator with organic vapor | |
| Thermal hazards | Wear appropriate th | nermal protective clo | othing, when ne | cessary. | |
| General hygiene considerations | Observe any medica personal hygiene m drinking, and/or sm contaminants. Cont | al surveillance requi easures, such as wa oking. Routinely wa aminated work cloth | rements. When ashing after han ash work clothin ning should not l | using do not smoke. Always observe good dling the material and before eating, g and protective equipment to remove be allowed out of the workplace. | |
| 9. Physical and chemica | l properties | | | | |
| Appearance | Clear. | | | | |

| Form | Liquid |
|--|---------------------------|
| Folm | Liquiu. |
| Color | Light yellow. |
| Odor Odor | Strong. |
| Udor threshold | Not available. |
| pH | 6 |
| Melting point/freezing point | -42 °F (-41 °C) estimated |
| Initial boiling point and boiling range | 255 °F (124 °C) estimated |
| Flash point | 115 - 140 °F (46 - 60 °C) |
| Evaporation rate | Not available. |
| Flammability (solid, gas) | Not applicable. |
| Upper/lower flammability or e | xplosive limits |
| Flammability limit - lower (%) | 2.4 % estimated |
| Flammability limit - upper (%) | Not available. |
| Explosive limit - lower (%) | Not available. |
| Explosive limit - upper (%) | Not available. |
| Vapor pressure | 374 hPa estimated |
| Vapor density | Not available. |
| Relative density | Not available. |
| Solubility(ies) | |
| Solubility (water) | Miscible |
| Partition coefficient (n-octanol/water) | Not available. |
| Auto-ignition temperature | 640 °F (338 °C) estimated |
| Decomposition temperature | Not available. |
| Viscosity | Not available. |
| Other information | |
| Density | 1.10 g/cm3 |
| Explosive properties | Not explosive. |
| Flammability class | Combustible II estimated |
| Flash point class | Combustible II |
| Oxidizing properties | Not oxidizing. |
| Percent volatile | 83.2 % estimated |
| Specific gravity | 1.1 |
| VOC | 83.2 % estimated |
| 100 | |

10. Stability and reactivity

| Reactivity | The product is stable and non-reactive under normal conditions of use, storage and transport. |
|---------------------------------------|--|
| Chemical stability | Material is stable under normal conditions. |
| Possibility of hazardous reactions | Hazardous polymerization does not occur. |
| Conditions to avoid | Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials. |
| Incompatible materials | Strong acids. Strong oxidizing agents. Caustics. |
| Hazardous decomposition products | Upon decomposition, this product emits oxides of sulfur, carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. |
| | |

11. Toxicological information

Information on likely routes of exposure

| Inhalation | May cause damage to organs through prolonged or repeated exposure by inhalation |
|--------------------------|--|
| Skin contact | Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction. |
| Eye contact | Causes serious eye irritation. |
| Ingestion | Expected to be a low ingestion hazard. |
| Material name: WATERMARK | R KARL FISCHER COULOMETRIC GENERATOR SOLUTION, UNIVERSAL |

Information on toxicological effects

| cute toxicity | Harmful in contact with skin. |
|---------------|-------------------------------|
| | |

| Acute toxicity | Harmful in contact with skin. | |
|------------------|---|---------------------|
| Product | Species | Test Results |
| WATERMARK® KAR | L FISCHER COULOMETRIC GENERATOR SOLUTION, | , UNIVERSAL |
| <u>Acute</u> | | |
| Inhalatio | n | |
| LC50 | Guinea pig | 6278 mg/l |
| | Mouse | 6389 mg/l |
| | Rat | 2308 mg/l |
| Oral | | |
| LD50 | Mouse | 99999 mg/kg |
| | Rabbit | 99999 mg/kg |
| Components | Species | Test Results |
| DIETHANOLAMINE (| CAS 111-42-2) | |
| <u>Acute</u> | | |
| Dermal | | |
| LD50 | Rabbit | 11.9 ml/kg |
| Oral | | 4000 <i>I</i> |
| LD50 | Rat | 1820 mg/kg |
| | | 710 mg/kg |
| Other | Manage | 2200 |
| | | 2300 mg/kg |
| ETHYLENEGLYCOLM | ONOMETHYL ETHER (CAS 109-86-4) | |
| <u>Acute</u> | | |
| LD50 | Rabbit | 1280 ma/ka |
| Inhalatio | | 1200 mg/kg |
| | Rat | 1500 mg/l 7 hours |
| Oral | | 2000 |
| LD50 | Guinea pig | 950 mg/kg |
| | Mouse | 2560 mg/kg |
| | Rabbit | 890 mg/kg |
| | Pat | 2370 mg/kg |
| Other | Nat | 2370 119/kg |
| | Mouse | 2147 ma/ka |
| 2000 | Bat | 2140 mg/kg |
| | | 2110 119/19 |
| | J0-2) | |
| Oral | | |
| LD50 | Mouse | 22 g/kg |
| | Rabbit | 10 g/kg |
| | Rat | 14 a/ka |
| | °AS 7446-09-5) | - 37.53 |
| | | |
| Inhalatio | n | |
| LC50 | Guinea pig | 1000 ppm, 20 Hours |
| | | 1000 mg/l, 20 Hours |
| | | 130 ppm, 154 Hours |

130 mg/l, 154 Hours

| Components | Species | Test Results |
|---|--|--|
| | Mouse | 1000 ppm, 4 Hours |
| | | 1000 mg/l, 4 Hours |
| | | 150 ppm, 847 Hours |
| | | 150 mg/l, 847 Hours |
| | | |
| * Estimates for product may b | e based on additional componen | t data not shown. |
| Skin corrosion/irritation | Causes skin irritation. | |
| irritation | Causes serious eye irritation. | |
| Respiratory or skin sensitizatio | on | |
| Respiratory sensitization | Not a respiratory sensitizer. | |
| Skin sensitization | May cause an allergic skin read | tion. |
| Germ cell mutagenicity | mutagenic or genotoxic. | oduct or any components present at greater than 0.1% are |
| Carcinogenicity | Suspected of causing cancer. | |
| IARC Monographs. Overall | Evaluation of Carcinogenicit | у |
| DIETHANOLAMINE (CAS : SULFUR DIOXIDE (CAS 74 | 111-42-2) 446-09-5) | 2B Possibly carcinogenic to humans. 3 Not classifiable as to carcinogenicity to humans. |
| US OSHA Hazard Categorie | es (1) | |
| Not regulated. | . (10) | |
| US USHA Hazard Categorie | es (10) | |
| US OSHA Hazard Categorie | es (2) | |
| Not regulated. US OSHA Hazard Categorie | es (3) | |
| Not regulated. US OSHA Hazard Categorie | es (4) | |
| Not regulated. US OSHA Hazard Categorie | es (5) | |
| Not regulated. US OSHA Hazard Categorie | es (6) | |
| Not regulated. US OSHA Hazard Categorie | es (7) | |
| Not regulated. | | |
| US OSHA Hazard Categorie | es (8) | |
| Not regulated. US OSHA Hazard Categorie | es (9) | |
| Not regulated. | | |
| US. National Toxicology Pr Not listed. | ogram (NTP) Report on Carc | inogens |
| Reproductive toxicity | May damage fertility or the unl | porn child. |
| Specific target organ toxicity - single exposure | Not classified. | |
| Specific target organ toxicity - repeated exposure | Causes damage to organs thro | ugh prolonged or repeated exposure. |
| Aspiration hazard | Not an aspiration hazard. | |
| Chronic effects | Causes damage to organs thro harmful. Prolonged exposure n | ugh prolonged or repeated exposure. Prolonged inhalation may be nay cause chronic effects. |
| 12. Ecological informatio | n | |
| Ecotoxicity | Harmful to aquatic life with lon | a lasting effects. |
| | | |

| Product | | Species | Test Results |
|-----------------|-----------------|--------------------|-----------------------------------|
| WATERMARK® KARL | FISCHER COULOME | TRIC GENERATOR SOL | UTION, UNIVERSAL |
| Aquatic | | | |
| Crustacea | EC50 | Daphnia | 468.1818 mg/l, 48 hours estimated |
| | LC50 | Daphnia | 15385 mg/l, 24 hours |

| Product | | Species | Test Results |
|---------------------------|------------------------|--|-------------------------------------|
| | | | 140 mg/l, 48 hours |
| | | | 38.25 mg/l, 96 hours |
| Fish | LC50 | Fish | 15385 mg/l, 48 hours |
| | | | 147 mg/l, 24 hours |
| | | | 107 mg/l, 96 hours |
| Components | | Species | Test Results |
| DIETHANOLAMINE (CAS | 111-42-2) | | |
| Aquatic | | | |
| Crustacea | EC50 | Water flea (Ceriodaphnia dubia) | 61.8 - 86.04 mg/l, 48 hours |
| Fish | LC50 | Fathead minnow (Pimephales promelas) | 100 mg/l, 96 hours |
| ETHYLENEGLYCOLMONO | METHYL ETHER (C | AS 109-86-4) | |
| Aquatic | | | |
| Fish | LC50 | Bluegill (Lepomis macrochirus) | > 10000 mg/l, 96 hours |
| IODINE (CAS 7553-56-2) | | | |
| Aquatic | | | |
| Fish | LC50 | Rainbow trout,donaldson trout (Oncorhynchus mykiss) | 0.48 - 0.58 mg/l, 96 hours |
| | | | 0.48 - 0.58 mg/l, 96 hours |
| * Estimates for product n | nay be based on ac | lditional component data not shown. | |
| sistence and degradab | ility | | |
| accumulative potential | | | |
| Partition coefficient n | -octanol / water | (log Kow) | |
| DIETHANOLAMINE | | -1.43 | |
| IODINF | METHYLETHER | -0.77 2.49 | |
| bility in soil | No data avai | lable. | |
| ner adverse effects | The product potential. | contains volatile organic compounds which | have a photochemical ozone creation |
| . Disposal consider | ations | | |
| | | | |

| Disposal instructions | Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations. |
|--|--|
| Local disposal regulations | Dispose in accordance with all applicable regulations. |
| Hazardous waste code | The waste code should be assigned in discussion between the user, the producer and the waste disposal company. |
| Waste from residues / unused products | Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). |
| Contaminated packaging | Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. |

14. Transport information

| DOT | |
|----------------------------|---|
| UN number | UN1188 |
| UN proper shipping name | Ethylene glycol monomethyl ether mixture |
| Transport hazard class(es) | |
| Class | 3 |
| Subsidiary risk | - |
| Label(s) | 3 |
| Packing group | III |
| Special precautions for | Read safety instructions, SDS and emergency procedures before handling. |
| user | |
| Special provisions | B1, IB3, T2, TP1 |
| Packaging exceptions | 150 |

| Packaging non bulk | 203 |
|--|---|
| Packaging bulk | 242 |
| ΙΑΤΑ | |
| UN number | UN1188 |
| UN proper shipping name | Ethylene glycol monomethyl ether mixture |
| Transport hazard class(es) | |
| Class | 3 |
| Subsidiary risk | - |
| Packing group | III |
| Environmental hazards | No. |
| ERG Code | 3L |
| Special precautions for | Read safety instructions, SDS and emergency procedures before handling. |
| user | |
| Other information | |
| Passenger and cargo aircraft | Allowed with restrictions. |
| Cargo aircraft only | Allowed with restrictions. |
| IMDG | |
| UN number | UN1188 |
| UN proper shipping name | ETHYLENE GLYCOL MONOMETHYL ETHER MIXTURE |
| Transport hazard class(es) | |
| Class | 3 |
| Subsidiary risk | - |
| Packing group | III |
| Environmental hazards | |
| Marine pollutant | No. |
| EmS | F-E, S-D |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |
| Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code | Not established. |
| DOT | |





15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

ETHYLENEGLYCOLMONOMETHYL ETHER (CAS 109-86-4) 1.0 % One-Time Export Notification only.

CERCLA Hazardous Substance List (40 CFR 302.4)

DIETHANOLAMINE (CAS 111-42-2) SARA 304 Emergency release notification

Listed.

SULFUR DIOXIDE (CAS 7446-09-5) 500 LBS

| Not regulated. | egories (2) | | | | |
|---|---|---|--|--|---|
| Not regulated. | | | | | |
| US OSHA Hazard Cat | egories (3) | | | | |
| Not regulated. | egories (4) | | | | |
| Not regulated. | | | | | |
| US OSHA Hazard Cat | egories (5) | | | | |
| Not regulated. US OSHA Hazard Cat | egories (6) | | | | |
| Not regulated. US OSHA Hazard Cat | egories (7) | | | | |
| Not regulated. US OSHA Hazard Cat | egories (8) | | | | |
| Not regulated. | | | | | |
| US USHA Hazard Cat | egories (9) | | | | |
| US OSHA Hazard Cat | egories (10) | | | | |
| Not regulated. | | | | | |
| Superfund Amendments | and Reauthorizat | ion Act of 198 | 6 (SARA) | | |
| | Delayed Haz Fire Hazard Pressure Ha Reactivity H | azard - Yes zard - Yes - Yes azard - No lazard - No | | | |
| SARA 302 Extremely | hazardous substa | ance | | | |
| Chemical name | CAS number | Reportable quantity (pounds) | Threshold planning quantity (pounds) | Threshold planning quantity, lower value (pounds) | Threshold planning quantity, upper value (pounds) |
| | | | | | |
| SULFUR DIOXIDE | 7446-09-5 | 500 | 500 | | |
| SULFUR DIOXIDE SARA 311/312 Hazardous chemical | 7446-09-5 No | 500 | 500 | | |
| SULFUR DIOXIDE SARA 311/312 Hazardous chemical SARA 313 (TRI repor | 7446-09-5 No ting) | 500 | 500 | 0/ huud | |
| SULFUR DIOXIDE SARA 311/312 Hazardous chemical SARA 313 (TRI repor Chemical name DIETHANOLAMINE | 7446-09-5 No ting) | 500 C | 500 AS number 1-42-2 | % by wt. | |
| SULFUR DIOXIDE SARA 311/312 Hazardous chemical SARA 313 (TRI repor Chemical name DIETHANOLAMINE ETHYLENEGLYCOLI | 7446-09-5 No ting) MONOMETHYL ETHE | 500 C4 ER 10 | 500 AS number 1-42-2 9-86-4 | % by wt. 10 - < 20 80 - < 90 | |
| SULFUR DIOXIDE SARA 311/312 Hazardous chemical SARA 313 (TRI repor Chemical name DIETHANOLAMINE ETHYLENEGLYCOLI Other federal regulations | 7446-09-5 No ting) MONOMETHYL ETHE | 500 CA ER 10 | 500 AS number 1-42-2 9-86-4 | % by wt. 10 - < 20 80 - < 90 | |
| SULFUR DIOXIDE SARA 311/312 Hazardous chemical SARA 313 (TRI repor Chemical name DIETHANOLAMINE ETHYLENEGLYCOLI Other federal regulations Clean Air Act (CAA) S | 7446-09-5 No ting) MONOMETHYL ETHE Section 112 Hazar | 500 CA ER 11 HOUS Air Pollut | 500 AS number 1-42-2 9-86-4 tants (HAPs) List | % by wt. 10 - < 20 80 - < 90 | |
| SULFUR DIOXIDE SARA 311/312 Hazardous chemical SARA 313 (TRI repor Chemical name DIETHANOLAMINE ETHYLENEGLYCOLI Other federal regulations Clean Air Act (CAA) S DIETHANOLAMINE Clean Air Act (CAA) S | 7446-09-5 No ting) MONOMETHYL ETHE Section 112 Hazar (CAS 111-42-2) Section 112(r) Acc | 500 CA ER 11 rdous Air Pollut | 500 AS number 1-42-2 9-86-4 tants (HAPs) List se Prevention (40 CF | % by wt. 10 - < 20 80 - < 90 R 68.130) | |
| SULFUR DIOXIDE SARA 311/312 Hazardous chemical SARA 313 (TRI repor Chemical name DIETHANOLAMINE ETHYLENEGLYCOLI Other federal regulations Clean Air Act (CAA) S DIETHANOLAMINE Clean Air Act (CAA) S SULFUR DIOXIDE (| 7446-09-5 No ting) MONOMETHYL ETHE Section 112 Hazar (CAS 111-42-2) Section 112(r) Acc CAS 7446-09-5) | 500 CA ER 11 rdous Air Pollut cidental Releas | 500 AS number 1-42-2 9-86-4 tants (HAPs) List se Prevention (40 CF | <u>% by wt.</u> 10 - < 20 80 - < 90 R 68.130) | |
| SULFUR DIOXIDE SARA 311/312 Hazardous chemical SARA 313 (TRI repor Chemical name DIETHANOLAMINE ETHYLENEGLYCOLI Other federal regulations Clean Air Act (CAA) S DIETHANOLAMINE Clean Air Act (CAA) S SULFUR DIOXIDE (Safe Drinking Water (SDWA) | 7446-09-5 No ting) MONOMETHYL ETHE Section 112 Hazar (CAS 111-42-2) Section 112(r) Acc CAS 7446-09-5) Act Not regulate | 500 CA ER 11 dous Air Pollut cidental Releas | 500 AS number 1-42-2 9-86-4 tants (HAPs) List se Prevention (40 CF | <u>% by wt.</u> 10 - < 20 80 - < 90 R 68.130) | |
| SULFUR DIOXIDE SARA 311/312 Hazardous chemical SARA 313 (TRI repor Chemical name DIETHANOLAMINE ETHYLENEGLYCOLI Other federal regulations Clean Air Act (CAA) S DIETHANOLAMINE Clean Air Act (CAA) S SULFUR DIOXIDE (Safe Drinking Water (SDWA) Drug Enforcemen | 7446-09-5 No ting) MONOMETHYL ETHE Section 112 Hazar (CAS 111-42-2) Section 112(r) Acc CAS 7446-09-5) Act Not regulate th Administration | 500 CA 11 ER 10 dous Air Pollut cidental Releas ed. (DEA). List 1 8 | 500 AS number 1-42-2 9-86-4 tants (HAPs) List se Prevention (40 CF & 2 Exempt Chemical | <u>% by wt.</u> 10 - < 20 80 - < 90 R 68.130) Mixtures (21 CFR 1 | .310.12(c)) |
| SULFUR DIOXIDE SARA 311/312 Hazardous chemical SARA 313 (TRI repor Chemical name DIETHANOLAMINE ETHYLENEGLYCOLI Other federal regulations Clean Air Act (CAA) S DIETHANOLAMINE Clean Air Act (CAA) S SULFUR DIOXIDE (Safe Drinking Water (SDWA) Drug Enforcemen IODINE (CAS 7 DEA Exempt Che | 7446-09-5 No ting) MONOMETHYL ETHE Section 112 Hazar (CAS 111-42-2) Section 112(r) Acc CAS 7446-09-5) Act Not regulate the Administration (2553-56-2) mical Mixtures Co | 500 CA 11 ER 10 rdous Air Pollut cidental Releas ed. (DEA). List 1 8 ode Number | 500 AS number 1-42-2 9-86-4 tants (HAPs) List ise Prevention (40 CF & 2 Exempt Chemical 2.2 %WV 6699 | <u>% by wt.</u> 10 - < 20 80 - < 90 R 68.130) Mixtures (21 CFR 1 | .310.12(c)) |
| SULFUR DIOXIDE SARA 311/312 Hazardous chemical SARA 313 (TRI repor Chemical name DIETHANOLAMINE ETHYLENEGLYCOLI Other federal regulations Clean Air Act (CAA) S DIETHANOLAMINE Clean Air Act (CAA) S SULFUR DIOXIDE (Safe Drinking Water (SDWA) Drug Enforcemer IODINE (CAS 7 DEA Exempt Che IODINE (CAS 7 | 7446-09-5 No ting) MONOMETHYL ETHE Section 112 Hazar (CAS 111-42-2) Section 112(r) Acc CAS 7446-09-5) Act Not regulate t Administration (7553-56-2) mical Mixtures Co (7553-56-2) bstances Respirat | 500 CA ER 11 dous Air Pollut cidental Releas ed. (DEA). List 1 8 ode Number tory Health and | 500 AS number 1-42-2 9-86-4 tants (HAPs) List se Prevention (40 CF A 2 Exempt Chemical 2.2 %WV 6699 d Safety in the Flavo | % by wt. 10 - < 20 | .310.12(c)) orkplace |
| SULFUR DIOXIDE SARA 311/312 Hazardous chemical SARA 313 (TRI repor Chemical name DIETHANOLAMINE ETHYLENEGLYCOLI Other federal regulations Clean Air Act (CAA) S DIETHANOLAMINE Clean Air Act (CAA) S SULFUR DIOXIDE (Safe Drinking Water (SDWA) Drug Enforcemen IODINE (CAS 7 FEMA Priority Su SULFUR DIOXI | 7446-09-5 No ting) MONOMETHYL ETHE Section 112 Hazar (CAS 111-42-2) Section 112(r) Acc CAS 7446-09-5) Act Not regulate t Administration (7553-56-2) mical Mixtures Co (7553-56-2) bstances Respirat DE (CAS 7446-09-5 | 500 CA 11 ER 10 dous Air Pollut cidental Releas ed. (DEA). List 1 8 ode Number tory Health and) | 500 AS number 1-42-2 9-86-4 tants (HAPs) List se Prevention (40 CF & 2 Exempt Chemical 2.2 %WV 6699 d Safety in the Flavo High priority | <u>% by wt.</u> 10 - < 20 80 - < 90 R 68.130) Mixtures (21 CFR 1 r Manufacturing Wo | .310.12(c)) orkplace |
| SULFUR DIOXIDE SARA 311/312 Hazardous chemical SARA 313 (TRI repor Chemical name DIETHANOLAMINE ETHYLENEGLYCOLI Other federal regulations Clean Air Act (CAA) S DIETHANOLAMINE Clean Air Act (CAA) S SULFUR DIOXIDE (Safe Drinking Water (SDWA) Drug Enforcemen IODINE (CAS 7 DEA Exempt Che IODINE (CAS 7 FEMA Priority Su SULFUR DIOXI | 7446-09-5 No ting) MONOMETHYL ETHE Section 112 Hazar (CAS 111-42-2) Section 112(r) Acc CAS 7446-09-5) Act Not regulate th Administration 7553-56-2) mical Mixtures Co 7553-56-2) bstances Respirat DE (CAS 7446-09-5 WARNING: birth defect | 500 CA 11 ER 10 rdous Air Pollut cidental Releas ed. (DEA). List 1 8 ode Number tory Health and) This product cor s or other reprod | 500 AS number 1-42-2 9-86-4 tants (HAPs) List ise Prevention (40 CF 2.2 %WV 6699 d Safety in the Flavo High priority ntains a chemical known ductive harm. | % by wt. 10 - < 20 | .310.12(c)) orkplace rnia to cause cancer and |
| SULFUR DIOXIDE SARA 311/312 Hazardous chemical SARA 313 (TRI repor Chemical name DIETHANOLAMINE ETHYLENEGLYCOLI Other federal regulations Clean Air Act (CAA) S DIETHANOLAMINE Clean Air Act (CAA) S SULFUR DIOXIDE (Safe Drinking Water (SDWA) Drug Enforcemer IODINE (CAS 7 DEA Exempt Che IODINE (CAS 7 FEMA Priority Su SULFUR DIOXI US state regulations | 7446-09-5 No ting) MONOMETHYL ETHE Section 112 Hazar (CAS 111-42-2) Section 112(r) Acc CAS 7446-09-5) Act Not regulate th Administration 7553-56-2) mical Mixtures Co 7553-56-2) bstances Respirat DE (CAS 7446-09-5 WARNING: birth defect | 500 CA 111 ER 10 dous Air Pollut cidental Release ed. (DEA). List 1 8 ode Number tory Health and) This product cor s or other reproc RT: Listed date, | 500 AS number 1-42-2 9-86-4 tants (HAPs) List se Prevention (40 CF A 2 Exempt Chemical 2.2 %WV 6699 d Safety in the Flavo High priority ntains a chemical known ductive harm. /Carcinogenic substa | % by wt. 10 - < 20 | . 310.12(c)) or kplace rnia to cause cancer and |
| SULFUR DIOXIDE SARA 311/312 Hazardous chemical SARA 313 (TRI repor Chemical name DIETHANOLAMINE ETHYLENEGLYCOLI Other federal regulations Clean Air Act (CAA) S DIETHANOLAMINE Clean Air Act (CAA) S SULFUR DIOXIDE (Safe Drinking Water (SDWA) Drug Enforcemer IODINE (CAS 7 DEA Exempt Che IODINE (CAS 7 FEMA Priority Su SULFUR DIOXI US state regulations US - California Pu DIETHANOLAM | 7446-09-5 No ting) MONOMETHYL ETHE Section 112 Hazar (CAS 111-42-2) Section 112(r) Acc CAS 7446-09-5) Act Not regulate th Administration 7553-56-2) mical Mixtures Co 7553-56-2) bistances Respirat DE (CAS 7446-09-5 WARNING: birth defect roposition 65 - CR INE (CAS 111-42-2 roposition 65 - CR | 500 CA 111 ER 10 dous Air Pollut cidental Release ed. (DEA). List 1 8 ode Number tory Health and) This product cor s or other reproc ET: Listed date,) ET: Listed date | 500 AS number 1-42-2 9-86-4 tants (HAPs) List te Prevention (40 CF 2.2 %WV 6699 d Safety in the Flavo High priority ntains a chemical known ductive harm. /Carcinogenic substate Listed: June 22, 20 /Developmental toxi | % by wt. 10 - < 20 | .310.12(c)) Frkplace rnia to cause cancer and |
| SULFUR DIOXIDE SARA 311/312 Hazardous chemical SARA 313 (TRI repor Chemical name DIETHANOLAMINE ETHYLENEGLYCOLI Other federal regulations Clean Air Act (CAA) S DIETHANOLAMINE Clean Air Act (CAA) S SULFUR DIOXIDE (Safe Drinking Water (SDWA) Drug Enforcemer IODINE (CAS 7 DEA Exempt Che IODINE (CAS 7 FEMA Priority Su SULFUR DIOXI US state regulations US - California Pr DIETHANOLAM US - California Pr ETHYLENEGLY 109-85-4) | 7446-09-5 No ting) MONOMETHYL ETHE Section 112 Hazar (CAS 111-42-2) Section 112(r) Acc (CAS 7446-09-5) Act Not regulate th Administration (7553-56-2) mical Mixtures Co (7553-56-2) bstances Respirat (DE (CAS 7446-09-5 WARNING: birth defect roposition 65 - CR (INE (CAS 111-42-2 roposition 65 - CR (COLMONOMETHYL) | 500 CA 111 ER 10 rdous Air Pollut cidental Release ed. (DEA). List 1 8 ode Number tory Health and) This product cor s or other reproc CT: Listed date,) CT: Listed date, ETHER (CAS | 500 AS number 1-42-2 9-86-4 tants (HAPs) List se Prevention (40 CF 2.2 %WV 6699 d Safety in the Flavo High priority ntains a chemical known ductive harm. /Carcinogenic substa Listed: June 22, 20 /Developmental toxi Listed: January 1, 3 | % by wt. 10 - < 20 | .310.12(c)) orkplace rnia to cause cancer and |

US OSHA Hazard Categories (1)

US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

ETHYLENEGLYCOLMONOMETHYL ETHER (CAS Listed: January 1, 1989 109-86-4)

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

DIETHANOLAMINE (CAS 111-42-2) ETHYLENEGLYCOLMONOMETHYL ETHER (CAS 109-86-4) SULFUR DIOXIDE (CAS 7446-09-5)

International Inventories

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|--|------------------------|
| Australia | Australian Inventory of Chemical Substances (AICS) | Yes |
| Canada | Domestic Substances List (DSL) | Yes |
| Canada | Non-Domestic Substances List (NDSL) | No |
| China | Inventory of Existing Chemical Substances in China (IECSC) | Yes |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | Yes |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | No |
| Korea | Existing Chemicals List (ECL) | Yes |
| New Zealand | New Zealand Inventory | Yes |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | Yes |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

| Issue date | February-14-2013 |
|----------------------|--|
| Revision date | December-22-2016 |
| Version # | 02 |
| Disclaimer | The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. GFS Chemicals, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. |
| Revision information | This document has undergone significant changes and should be reviewed in its entirety. |